



# SignalTEK NT

Copper and Fibre Network Transmission Tester

# **SignalTEK NT**

Network Transmission Tester

# More than a qualifier

SignalTEK NT allows you to prove the performance up to Gigabit Ethernet transmission rates.

By simulating actual network traffic users are able to test and document

If you install, maintain or troubleshoot data cabling and Ethernet networks,

By simulating actual network traffic users are able to test and document network and data cable performance to Gigabit Ethernet standards.

Where system warranties are not required the SignalTEK NT is a cost effective way of proving your copper and fibre networks provide error-free performance.



No calibration required plus replaceable RJ45 contacts

# **Transmission testing proves real performance**

There is no industry standard defining the testing requirements of cable qualifiers, consequently passing a qualification test does not prove that the installed structured cabling will provide flawless data transmission.

Uniquely, SignalTEK NT utilises a test method known in wide area networks as transmission testing to prove the performance of a network by sending real Ethernet data frames through the cabling and/or network devices to compare the error rate against the IEEE802.3ab Gigabit Ethernet standard. This provides a clear standards based Pass/Fail of the link being tested.

SignalTEK NT requires no configuration from the user as the two handsets automatically pair ready for testing; just select a usage scenario to simulate the appropriate service, from VoIP to CCTV, Video, and web traffic.

# Voip: 0068 []=08124 FAILED 00:00:10 8 Line Rate 100 Mb/s-FD Frame Size 218 IR (Mb/s) 27 Tx Frames 154,816 10096 Rx Frames 122,144 7996 Errors 32,672 21% SETUP

VoIP fail - 21% packet loss

# **Installation testing**

### Cabling:

- Network traffic performance test on copper and fibre to IEEE802.3ab standard
- Wiremap test for open, shorts, miswires and split pairs to TIA-568 standard
- Gigabit link verification for copper and fibre cabling

### Active network:

- Network load testing through switches simulating CCTV/IPTV/VoIP/Web traffic
- PoE/PoE+ verification that displays available voltage at device location
- Check Ethernet connectivity at device location to 10/100/1000 Mb/s
- Verify network configuration (device IP/gateway address/subnet mask)
- Switch port identification via LLDP/CDP protocols


# Troubleshooting/diagnostics

### Cabling:

- Distance to fault using TDR technology (copper only)
- Ability to identify and trace cables with a compatible amplifier probe (62-164)
- Optical power indication (with compatible SFP modules)

### Active network:

- Network load testing through switches simulating CCTV/IPTV/VoIP/Web traffic
- Stress test network before installing bandwidth hungry devices
- Port blink to visually trace cable from work area outlet to network switch
- Displays port ID of LLDP/CDP enabled switches to eliminate manual cable tracing
- Identify network connection problems as hardware, network or configuration faults
- Ping local network devices and Internet URL's
- Count number of hops between network points with traceroute tests
- PoE load testing to confirm available power meets PoE device requirements



Wiremap test displaying open and short

# Send test reports from anywhere using the free app | IDEAL AnyWARE









# Step 1

### **Test**

- · Create job folder
- Enter job site information
- Perform autotest on copper/fibre cabling and copper/fibre networks

# Step 2

## Connect

- Activate SignalTEK NT wireless hotspot
- Connect your mobile phone or tablet with the IDEAL AnyWARE App
- Transfer test reports to your mobile device
- View test reports

# Step 3

### Send

- Select reports (PDF or CSV) to send
- Select preferred transfer method email, ftp, cloud storage etc.
- Send file
- Alternatively save test reports to USB key

# Download the FREE App today








# **Network Performance Test**

- Port speed 10/100/1000
- PoE/PoE+ detection
- Web data performance
- IP video performance
- IP CCTV performance
- · VoIP performance











IP Phone

### **Cable Performance Test**

- TDR wiremap
- IEEE 802.3ab Gigabit data



# Network diagnostics & troubleshooting

- Network speed 10/100/1000
- Network IP/DHCP configuration
- · CDP/LLDP port identification
- PoE/PoE+ detection/load test
- Ping/trace route
- Blink switch link LED





# **SignalTEK NT**

# **Network Transmission Tester**

# More than a qualifier

# Test Reporting

SignalTEK NT automatically generates test reports in PDF or CSV format.

The summary page of each report can be customised to include logo, company and operator details. Choose between 3 different reports that can show either passed, failed or all test reports in each report:

- Summary
- Brief
- Full (see example on the right side)

# Ordering Information

Part No.	Kit Contents
R156003	<b>SignalTEK NT</b> - Network Transmission Tester. Includes 1 x display, 1 x remote, 2 x NiMH batteries, 2 x patch cables - 30cm, Cat 5e STP, 2 x power supply with EU/UK/US adaptors, 1 x USB Wi-Fi adapter, 1 x user manual, 1 x carry case

For the copper only version without network troubleshooting, please check out our SignalTEK CT

# Optional Accessories

Part No.	Description		
MGKSX1	1 x 1000BASE-SX Fibre kit. Includes 850nm SFP (Small Form factor Pluggable) SX transceiver, LC/LC and LC/SC duplex multimode cables and SC/SC duplex adaptor		
MGKLX2	1 x 1000BASE-LX Fibre kit. Includes 1310nm SFP (Small Form factor Pluggable) LX transceiver, LC/LC and LC/SC duplex singlemode cables and SC/SC duplex adaptor		
MGKZX3	1x 1000BASE-ZX Fibre kit. Includes 1550nm SFP (Small Form factor Pluggable) ZX transceiver, LC/LC and LC/SC duplex singlemode cables and SC/SC duplex adaptor		
62-164	1 x IDEAL amplifier probe		
150058	1 x RJ45 insert extraction tool, 10 x lifejack RJ45 inserts		

For replacement accessories, please visit our website.

# **Basic Specifications**

Max. No. of Jobs		Max. Length	Battery Life	Dimensions per handset in mm	Weight per handset
50	5000	181 m/593 ft.	5 hours	175 x 80 x 40	0.4 kg

For detailed specifications, please visit our website.

IDEAL INDUSTRIES NETWORKS DIVISION Unit 3, Europa Court, Europa Boulevard, Warrington, Cheshire, WA5 7TN, UK.

CE

Tel. +44 (0)1925 444 446 | Fax. +44 (0)1925 445501 uksales@idealnwd.com

www.idealnetworks.net













Specification subject to change without notice. E&OE © IDEAL Networks 2015 Publications no.: 156884, Rev. 1



Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc.

All Rights Reserved. IDEAL, IDEAL NETWORKS, IDEAL ANYWARE and the SignalTEK logos are trademarks or registered trademarks of IDEAL INDUSTRIES LIMITED or IDEAL INDUSTRIES, INC.