

Differential current monitoring - EV-RCM-C1-AC30-DC6 - 1622450


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



The residual current module is used for AC and DC residual current detection in AC charging points. The higher-level safety equipment (e.g., residual current circuit breaker) is protected against potential DC residual currents. A 1 or 2-channel product version is available.



Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 039794
Weight per Piece (excluding packing)	190.0 g
Custom tariff number	90303399
Country of origin	Germany

Technical data

Dimensions

Width	36 mm
Height	90 mm
Depth	70.5 mm

General data

Supply voltage range	100 V AC ... 240 V AC (nominal voltage range)
Frequency range	45 Hz ... 60 Hz
Power consumption	< 5 VA
Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 80 °C (Operation)

Input data

Description of the input	pluggable; Frontseite
--------------------------	-----------------------

Differential current monitoring - EV-RCM-C1-AC30-DC6 - 1622450

Classifications

eCl@ss

eCl@ss 5.1	27371810
eCl@ss 6.0	27371810

ETIM

ETIM 5.0	EC001445
----------	----------