

Charging controller - EV-CC-AC1-M3-CBC-SER-HS - 1622452


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



The EV-CC-AC1-M3-CBC-SER-HS charging controller with housing for DIN rail mounting is used for charging electric vehicles at 3-phase AC networks according to IEC 61851-1, Mode 3. All charging functions, comprehensive configuration settings as well as a locking controller are already integrated.



Key Commercial Data

Packing unit	1 pc
GTIN	 4 055626 039756
Weight per Piece (excluding packing)	225.0 g
Custom tariff number	85371099
Country of origin	Germany

Technical data

Dimensions

Width	124 mm
Height	128 mm
Depth	64 mm

General data

Supply voltage range	100 V AC ... 240 V AC (nominal voltage range)
Frequency range	50 Hz ... 60 Hz
Power consumption	< 1 W (No-load)
Degree of protection	IP20
Ambient temperature (operation)	-35 °C ... 70 °C (Operation)

Input data

Description of the input	Digital input
Nominal input voltage U_N	12 V
Nominal current I_N	≤ 1 mA (12 V)
Input voltage range	0 V ... 3 V (Off)
	9 V ... 15 V (On)

Charging controller - EV-CC-AC1-M3-CBC-SER-HS - 1622452

Technical data

Switching outputs

Socket locking	Relay output
Maximum switching voltage	12 V (Internal supply)
Max. switching current	2 A (Internal supply)
Charging contactor output	Relay output
Minimum switching capacity	1500 VA
Maximum switching voltage	250 V AC (External supply)
Max. switching current	6 A (External supply)

Digital outputs

Number of outputs	4
Connection method	Screw connection
Output current	0.5 A (Total current for all outputs; internally supplied)
	0.6 A (Per output; externally supplied)
Minimum switching voltage	5 V
Maximum switching voltage	30 V

RS-485 interface

Designation	RS-485 interface, 2-wire + GND
Connection method	Screw connection
File format/coding	8, N, 1
Protocols supported	Modbus/RTU (Slave)
Transmission speed	9.6 kbps (Standard)
Transmission speed range	9.6 kbps ... 19.2 kbps (adjustable)

Classifications

eCl@ss

eCl@ss 5.1	27371810
eCl@ss 6.0	27371810

ETIM

ETIM 5.0	EC002839
----------	----------