SIEMENS

Data sheet

6GK5008-0BA10-1AB2

SCALANCE XB008 Unmanaged Industrial Ethernet Switch for 10/100 Mbit/s for setting up small star and line topologies; LED diagnostics, IP20, 24 V AC/DC power supply, with 8x 10/100 Mbit/s twisted pair ports with RJ45 sockets; Manual available as a download



Product type designation	SCALANCE XB008
Transmission rate	
Transfer rate	10 Mbit/s, 100 Mbit/s
Interfaces / for communication / integrated	
Number of electrical connections	
 for network components or terminal equipment 	8; RJ45
Number of 100 Mbit/s SC ports	
• for multimode	0
Interfaces / others	
Number of electrical connections	
• for power supply	1
Type of electrical connection	
• for power supply	3-pole terminal block
Supply voltage, current consumption, power loss	
Type of voltage / of the supply voltage	AC/DC
Supply voltage	
• external	24 V

• external / minimum	19.2 V
external / maximum	28.8 V
• at AC	24 V
Product component / fusing at power supply input	Yes
Fuse protection type / at input for supply voltage	0.6 A / 60 V
Consumed current / maximum	0.12 A
Power loss [W]	-
• at DC / at 24 V	2.88 W
Permitted ambient conditions	
Ambient temperature	
 during operation 	-10 +60 °C
 during storage 	-40 +80 °C
during transport	-40 +80 °C
Relative humidity	
• at 25 °C / without condensation / during	95 %
operation / maximum	
Protection class IP	IP20
Design, dimensions and weight	
Design	Box
Width	45 mm
Height	100 mm
Depth	87 mm
Net weight	0.18 kg
Mounting type	
 35 mm DIN rail mounting 	Yes
● wall mounting	Yes
 S7-1500 rail mounting 	No
Product functions / management, configuration	
Product function	
multiport mirroring	No
• CoS	Yes
PROFINET conformity class	A
Product function / switch-managed	No
-	
Product functions / Redundancy Product function	
Parallel Redundancy Protocol (PRP)/operation	Yes
in the PRP-network	
 Parallel Redundancy Protocol 	No
(PRP)/Redundant Network Access (RNA)	
Standarda anasificationa approvale	
Standards, specifications, approvals Standard	
Clandere	

• for FM	FM3611: Class 1, Divison 2, Group A, B, C, D / T4, CL.1, Zone 2,
	GP. IIC, T4
 for hazardous zone 	EN 60079-0:2009, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc,
	KEMA 07ATEX0145 X
 for safety / from CSA and UL 	UL 60950-1, CSA C22.2 No. 60950-1
 for emitted interference 	EN 61000-6-4 (Class A)
• for interference immunity	EN 61000-6-2

Standards,	specifications,	approvals /	′ CE
Certificate	of suitability / CE	marking	

Yes

Standards, specifications, approvals / miscellaneous	
Certificate of suitability	EN 61000-6-2, EN 61000-6-4
• C-Tick	Yes
 KC approval 	Yes

Standards,	specifications,	approvais /	product co	nformity
MTBF				214 v

nternet-Link	
 to website: Selector SIMATIC NET SELECTION TOOL 	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx Download Manager	http://www.siemens.com/cax
 to website: Industry Online Support 	https://support.industry.siemens.com

Security information

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Thirdparty products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

last modified: