

EcoStruxure™ Micro Data Center

42U R-Series

Installation and Operation

MDC42USRSI, MDC42UARS I



Release date: 1/2023

Legal Information

The Schneider Electric brand and any trademarks of Schneider Electric SE and its subsidiaries referred to in this guide are the property of Schneider Electric SE or its subsidiaries. All other brands may be trademarks of their respective owners.

This guide and its content are protected under applicable copyright laws and furnished for informational use only. No part of this guide may be reproduced or transmitted in any form or by any means (electronic, mechanical, photocopying, recording, or otherwise), for any purpose, without the prior written permission of Schneider Electric.

Schneider Electric does not grant any right or license for commercial use of the guide or its content, except for a non-exclusive and personal license to consult it on an "as is" basis. Schneider Electric products and equipment should be installed, operated, serviced, and maintained only by qualified personnel.

As standards, specifications, and designs change from time to time, information contained in this guide may be subject to change without notice.

To the extent permitted by applicable law, no responsibility or liability is assumed by Schneider Electric and its subsidiaries for any errors or omissions in the informational content of this material or consequences arising out of or resulting from the use of the information contained herein.

Table of Contents

General Information.....	5
Safety.....	9
Important Safety Instructions SAVE THESE INSTRUCTIONS.....	9
General Safety.....	10
Inventory.....	13
Equipment and Accessory locations.....	13
Cabinet Features.....	15
Pre-installed Equipment.....	16
Supplemental Equipment Box Contents.....	16
Hardware Bag.....	17
Installation.....	18
Side Panel Removal and Installation.....	22
Bringing Power to the Micro Data Center.....	27
Install the Roxtec Gasket.....	29
Install the Cooling Equipment.....	30
Fire Suppression.....	32
Lighting Installation.....	33
The UPS.....	34
Access the Micro DC Switch and EcoStruxure Gateway Appliance.....	34
Start-Up.....	35
EcoStruxure IT Gateway.....	36
Gateway Version 1.9 and Older.....	38
Gateway Version 1.10 and Newer.....	42
Configure Credentials.....	44
Discover Devices.....	50
Install Accessories and Your Equipment.....	55
Troubleshooting.....	58
Reset NetBotz after Cooling Unit Powered Off.....	58
Specifications.....	62
Enclosure Warranty.....	64
2 Year Parts Only Factory Warranty.....	64

General Information

	MDC42USRSI	MDC42UARSI
Enclosure	NetShelter RX 42U <ul style="list-style-type: none"> • 800W x 1200D • 19 in. Rails (905kg/2000 lb Load) • Heavy Duty Casters 	NetShelter RX 42U <ul style="list-style-type: none"> • 800W x 1200D • 19 in. Rails (905kg/2000 lb Load) • Filter and Fans • Heavy Duty Casters
UPS	SmartUPS 5kVA	SmartUPS 5kVA
Rack PDU	Metered PDU (Qty 2)	Metered PDU (Qty 2)
Cooling	3.5kW, Uniflair Rack Mount <ul style="list-style-type: none"> • Split System with Condensing Unit • Condensate Pump • Low Ambient Kit 	3.5kW, Uniflair Rack Mount <ul style="list-style-type: none"> • Split System with Condensing Unit • Condensate Pump • Low Ambient Kit • Emergency Fan Ventilation
Security	NetBotz 250 NBRK0250 <ul style="list-style-type: none"> • Standard Keylock • Temperature and Humidity Sensor AP9335TH • Door Contacts NBES0303 • Leak Sensor NBES0306 	NetBotz 750 NBRK0750 <ul style="list-style-type: none"> • Standard Keylock • Temperature and Humidity Sensor AP9335TH • Door Contacts NBES0303 • Leak Sensor NBES0306 • Camera NBPD0165
Accessories	<ul style="list-style-type: none"> • Interior Lighting • Cable Manager 	<ul style="list-style-type: none"> • Interior Lighting • Cable Manager • Rack Mount Fire Suppression
Service and Monitoring	2 Year Factory Warranty	2 Year Factory Warranty

Documents included with your Micro Data Center Enclosure

The documentation for each component in the EcoStruxure Micro Data Center is either shipped with the equipment or available online at www.apc.com and www.se.com. You can search for the product SKU or the part number of the document. Documents can be viewed or downloaded from the applicable product page on either website.

Cabinets and Pre-installed Accessories

SKU	Component	Document Type	Document Part Number
MDC42UARSI MDC42USRSI	NetBotz Spot Fluid Sensor (NBES0301)	Installation	990-3294A
MDC42UARSI MDC42USRSI	NetBotz Door Switch Sensor (NBES0303)	Installation	990-3375
MDC42UARSI	APC Temperature and Humidity Sensor (AP9335TH)	Installation	990-3506
MDC42UARSI	NetBotz Rack Monitor 750 (NBRK0750)	Installation and Quick Configuration	990-91106G-XXX
MDC42USRSI	NetBotz Rack Monitor 250 (NBRK0250)	Installation and Quick Configuration	990-9814G-XXX

Cooling and Accessories

SKU	Component	Document Type	Document Part Number
MDC42UARSI MDC42USRSI	3.5 kW Rack mount Air Conditioning, Split system, Indoor unit with gravity drain, 50Hz (ACRMD4KI-1)	User Manual	990-6186-XXX
MDC42UARSI MDC42USRSI	3.5 kW Rack mount Air Conditioning, Split system, Outdoor unit without pre-charged refrigerant (ACRMD4KI-3)		

Rack PDU

SKU	Component	Document Type	Document Part Number
MDC42UARSI MDC42USRSI	Rack PDU 2G, Metered, 0U, 16A, 230V, (18) 13 & (2) C-19 IEC309 Cord (AP8858)	Installation	990-3940D

UPS and Accessories

SKU	Component	Document Type	Document Part Number
MDC42UARSI MDC42USRSI	APC Smart-UPS SRT 5000VA RM 230V (SRT5KRMXLI)	Installation Operation Manual	990-91117 990-91120

Other Equipment

SKU	Component	Document Type	Document Part Number
MDC42UARSI MDC42USRSI	Low Temp Kit (-35C°) (ACAC10040)	Installation	990-91280B-001
MDC42UARSI MDC42USRSI	Toolless Cable Management Rings (AP7540)	Installation	990-5003A
MDC42UARSI	NetBotz Camera Pod 165 (NBPD0165)	Installation and Quick Start	990-5974A-XXX
MDC42USRSI MDC42UARSI	Condensate Pump	Installation	Blue Diamond Pumps S30-195/5
MDC42UARSI	Redetec Fire Suppression (ARFS600IP)	Installation and Operation	Redetec
MDC42USRSI MDC42UARSI	Interior Light Kit	Installation	QGH2632101-00
MDC42USRSI MDC42UARSI	Roxtec Gland Cable Seal	Installation	Roxtec
MDC42USRSI MDC42UARSI	EcoStruxure IT Gateway	Installation, Operation, FAQ, Troubleshooting	Available online at ecostruxureit.com
MDC42USRSI MDC42UARSI	Micro Data Switch	Installation	N/A

Safety

Important Safety Instructions

SAVE THESE INSTRUCTIONS

Read these instructions carefully and look at the equipment to become familiar with it before trying to install, operate, service or maintain it. The following safety messages may appear throughout this manual or on the equipment to warn of potential hazards or to call attention to information that clarifies or simplifies a procedure.



The addition of this symbol to a “Danger” or “Warning” safety message indicates that an electrical hazard exists which will result in personal injury if the instructions are not followed.



This is the safety alert symbol. It is used to alert you to potential personal injury hazards. Obey all safety messages with this symbol to avoid possible injury or death.

⚠ DANGER

DANGER indicates a hazardous situation which, if not avoided, **will result in death or serious injury.**

Failure to follow these instructions will result in death or serious injury.

⚠ WARNING

WARNING indicates a hazardous situation which, if not avoided, **could result in death or serious injury.**

Failure to follow these instructions can result in death, serious injury, or equipment damage.

⚠ CAUTION

CAUTION indicates a hazardous situation which, if not avoided, **could result in minor or moderate injury.**

Failure to follow these instructions can result in injury or equipment damage.

NOTICE

NOTICE is used to address practices not related to physical injury. The safety alert symbol shall not be used with this type of safety message.

Failure to follow these instructions can result in equipment damage.

Qualified Personnel

Electrical equipment should only be installed, operated, serviced, and maintained by qualified personnel.

A qualified person is one who has skills and knowledge related to the construction, installation, and operation of electrical equipment and has received safety training to recognize and avoid the hazards involved.

General Safety

This manual contains important instructions that should be closely followed during installation, maintenance, and operation of the EcoStruxure Micro Data Center. Read all safety and operating instructions before attempting to operate the EcoStruxure Micro Data Center.

Adhere to all Warning labels on the unit, in this manual and in the attendant manuals for each device within the system. Follow all operating and user instructions.

This product is not intended for use with life support or other designated “critical” devices. The maximum load must not exceed that shown on the rating label.

Operate this product in an indoor environment at an ambient temperature of 10°C to 40°C (50°F to 105°F).

Keep the doors closed to minimize room air intrusion into the cabinet.

DANGER

HAZARD OF ARC FLASH AND ELECTRICAL SHOCK

- Electrical equipment must be installed, operated, serviced, and maintained only by qualified personnel.
- The Micro Data Center is intended to be installed and operated by a skilled person in a controlled location with restricted access.
- The Micro Data Center must be installed in accordance with the National Electrical Code and all applicable local codes.
- Perform appropriate Lock Out/Tag Out procedures during equipment installation and maintenance.
- Remove incoming power to the Micro Data Center before performing any work. Because of the UPS, live power exists within the equipment when power is turned off. Always use a properly rated voltage sensing device to confirm there is no voltage in the system.
- Wear appropriate personal protective equipment (PPE) and follow safe electrical work practices. See NFPA 70E and follow all local codes and regulations.
- Do not insert anything into the fan grill.

Failure to follow these instructions will result in death or serious injury.

NOTICE

IMPROPER AIRFLOW

- Improper airflow can damage installed components. Verify that the system provides airflow needed by your equipment.
- Check the air filter regularly. Replace the filter when needed to prevent reduced airflow.
- Do not obstruct airflow by covering the fans.

Failure to follow these instructions can result in equipment damage.

NOTICE**EQUIPMENT DAMAGE**

- Only make equipment connections as directed in this manual.
- Do not use caustic detergents or abrasive materials to clean the sheet metal. A damp, soft cloth is usually sufficient to remove dust or debris.

Failure to follow these instructions can result in equipment damage.

ASHRAE has published guidelines for owners of Edge computing equipment such as your Micro Data Center. (Edge equipment performs computing outside of a commercial data center with strict environmental controls.) It is recommended that you follow these guidelines to help prevent equipment damage and extend the life of your Micro Data Center. You can download the guidelines from www.ashrae.org/technical-resources/bookstore/datacomseries.

NetBotz Safety**NOTICE****EQUIPMENT DAMAGE RISK**

- Connect only approved devices to ports on the appliance as directed in this manual. Plugging in other devices may result in equipment damage.
- Do not use crossover cables.

Failure to follow these instructions can result in equipment damage.

Cabinet Safety

The following are important instructions that must be followed during installation.

▲ WARNING

TIP/HEAVY EQUIPMENT HAZARD

- Use at least two people to unpack and move the cabinet.
- Do not load any additional equipment in the cabinet before moving the cabinet on its casters.
- When moving the cabinet on its casters, ensure the path of the cabinet is free of obstacles and debris.
- When moving the cabinet on its casters, make sure the leveling feet are raised and push the cabinet from the front or rear. Never push the cabinet from the sides.

Failure to follow these instructions can result in death, serious injury, or equipment damage.

▲ CAUTION

HEAD IMPACT HAZARD

The fan box location may interfere with your working space. Sharp corners exist on the fan box. Exercise care to avoid impact.

Failure to follow these instructions can result in injury or equipment damage.

Labels

Safety and informational labels are affixed to the Micro Data Center. Read and follow the instructions on the labels.

Tip Hazard and Weight limit labels are attached to the frame of the MDC. See the label illustrations in the Installation section of this manual for more details.


Inventory


Upon receipt of the equipment, inspect for damage and notify the shipping carrier and APC immediately if any damage is found. There will be several boxes containing various parts and accessory items. After opening a box, check the contents. Report missing or damaged components to: <http://www.apc.com/support>.

The shipping materials are recyclable. Save them for later use or dispose of them appropriately.


Equipment and Accessory locations

MDC42USRSI configuration shown.





Cabinet Features



Item	Description	Item	Description
1	Roxtec cable entry (provided for MDCs with cooling units only)	9	Caster
2	Roof	10	Leveling foot
3	Side panel lock	11	Rear door
4	Locking top side panel	12	Locking rear door handle
5	Locking bottom side panel	13	Ventilation louvers
6	Front door	14	Cable gland knockouts (4)
7	Locking front door panel	15	Entry point for mains power
8	Ventilation louvers	16	Keys

Pre-installed Equipment

	MDC42USRSI	MDC42UARS I
Enclosure	42U	42U
UPS	SmartUPS 5kVA	SmartUPS 5kVA
Rack PDU	Metered PDU (Qty 2)	Metered PDU (Qty 2)
Cooling	3.5kW, Uniflair Rack Mount Condensate pump	3.5kW, Uniflair Rack Mount Condensate pump Emergency Fan Ventilation
Security	NetBotz 250 NBRK0250 <ul style="list-style-type: none"> • Standard Keylock • Temperature and Humidity Sensor AP9335TH • Door Contacts NBES0303 • Leak Sensor NBES0306 	NetBotz 750 NBRK0750 <ul style="list-style-type: none"> • Standard Keylock • Temperature and Humidity Sensor AP9335TH • Door Contacts NBES0303 • Leak Sensor NBES0306
Network	EcoStruxure IT Gateway Micro DC Switch Kit	EcoStruxure IT Gateway Micro DC Switch Kit
Accessories	N/A	Rack Mount Fire Suppression
Supplementary Equipment	Ethernet cables Power Cables	Ethernet cables Power Cables

Supplemental Equipment Box Contents

NOTE: Box contents are dependent on your MDC configuration. Your MDC may not require all of the contents listed below.

Ethernet cables (for UPS, NetBotz, Rack PDU, EIT Gateway, Fire suppression system)
Power cables
Power inlet box
Roxtec sealing gland system
Magnetic Interior lights
Camera (provided for MDC42UARS I only)
Cable Manager
Hardware bag
Cable ties

NOTE: Refrigerant piping is shipped inside the MDC cabinet.

Equipment Shipped Separately

MDC42USRSI	MDC42UARS I
Outdoor refrigerant unit	Outdoor refrigerant unit

Hardware Bag


Contents of hardware bag:

Plastic cup washer (60)
Torx T30 / #2 Phillips tool (1)
M6 x 16 Phillips slot screw (60)
Cage nut (60)
Cage nut tool (1)

Installation

Location Requirements

The final location for the MDC should include sufficient space to allow for installation and service. There should be enough space to open the front and rear doors and to remove the side panels without obstruction. Ensure there is adequate overhead space above the MDC in order to complete the tasks required to install coolant piping, power, and network cables.



Move the EcoStruxure Micro Data Center to its Final Location

▲ WARNING


TIP/HEAVY EQUIPMENT HAZARD

- Use at least two people to unpack and move the MDC.
- Do not load any additional equipment in the MDC before moving it on its casters.
- When moving the MDC on its casters, ensure the path is free of obstacles and debris.
- When moving the MDC on its casters, make sure the leveling feet are fully raised and push the MDC from the front or rear. Never push the MDC from the sides.

Failure to follow these instructions can result in death, serious injury, or equipment damage.


Labels: The labels below can be found on the exterior of the MDC and serve to communicate the following information:

1. With the leveling feet lowered, the static MDC can be loaded with up to 1361 kg (3750 lb) of additional equipment.
2. Tip Hazard warning icons
3. Read the Instructions icons





Eye bolts: Remove the hole plugs and attach eye bolts in each corner of the top of the MDC frame. Use M12 eye bolts with a lift rating of 435 lbs.

NOTE: Use appropriate lifting hardware to ensure a straight-line pull on the eye bolts.




Leveling Feet


Tools Required (not provided)

	
<p>13-mm Open-ended wrench</p>	<p>Level</p>

When the MDC has been moved to the location where it will be installed, lower the leveling feet. Use a 13-mm open-ended wrench (not provided) to lower the leveling feet. Use a level (not provided) to ensure the MDC is level and plumb while lowering the leveling feet.



Equipment Connections in the EcoStruxure Micro Data Center



NOTICE

Low Ambient configuration not shown. Refer to the manuals for the Low Ambient Kit and Cooling Unit for proper placement of the Low Ambient components.

Failure to follow these instructions can result in equipment damage.




NOTICE

- It is important to check that all connections are secure before applying power to the MDC.
- Check that the power cable for the fan is connected.
- For units with fire suppression systems, check that a cable from the fire suppression system has been connected to the fan.

Failure to follow these instructions can result in equipment damage.

Side Panel Removal and Installation

Tools Required (not provided)

		
<p>T-25 Torx driver</p>	<p>10mm socket wrench</p>	<p>Torque wrench</p>



Remove the Side Panels

It may be easier to install some of the piping and cables if one or more side panels are removed to improve access. Since your MDC is a sealed unit, care must be used when removing and installing the side panels in order to ensure the gasket material will not be damaged.

<p>⚠ CAUTION</p>
<p>HEAVY EQUIPMENT HAZARD</p> <p>The side panels are heavy. Two people should remove or install side panels.</p> <p>Failure to follow these instructions can result in injury or equipment damage.</p>



<p>NOTICE</p>
<p>Use care when removing or installing the side panels. Avoid crushing or tearing the gasket material.</p> <p>Failure to follow these instructions can result in equipment damage.</p>

The side panels are secured to the frame with three (3) M6 nuts at the front and three (3) M6 nuts at the rear of the frame on the interior of the unit. One person should hold the panel in place from the outside while the M6 nuts are removed.



MDC enclosure is shown without components for clarity.

With one person holding the panel in place, remove the two (2) T25 screws holding the panels to the cross brace support. Lift the latch to release the side panel. Use care when removing the side panels.



Install the Side Panels


NOTICE

DAMAGE HAZARD


- To avoid damaging the gasket, do not use an electric screwdriver or drill to secure the hardware.
- Refer to the torque specifications to avoid overtightening the fasteners. Overtightening the fasteners may permanently damage the gasket and compromise the seal.

Failure to follow these instructions can result in equipment damage.

Fit the six (6) threaded studs on the side panel through the holes in the frame. Have one person hold the side panel in position while a second person secures the six (6) M6 nuts. Torque: 8 – 12 in lbs (0.9 – 1.4 Nm)
Rubber bumpers installed near the studs on the side panels help prevent over compression of the gasket. Observe the torque requirements and use care to prevent damage to the gaskets.



Install the two (2) T25 screws to the support. Torque: 8 – 12 in lbs (0.9 – 1.4Nm)
Press the side panel at the top to compress the gasket while securing the latch.
Use care not to damage the gasket. Check to make sure the latch is secured in the locked position.



Bringing Power to the Micro Data Center

⚡ ⚠ DANGER



HAZARD OF ARC FLASH AND ELECTRICAL SHOCK

- Adhere to all national and local electrical codes when bringing mains power to the system.
- Mains power must be installed and serviced by qualified electricians only.
- Follow safe electrical work practices and wear appropriate personal protective equipment (PPE) See NFPA 70E.
- This system does not have any user-serviceable parts. Repairs are to be performed by factory-trained service personnel only.
- The system does not incorporate a main power disconnect. Due to the use of the UPS, live power exists within the system when power is turned off at the input circuit breaker.

Failure to follow these instructions will result in death or serious injury.

Building power is brought to the Micro Data Center at the top of the enclosure.

1. Remove the sealing plate on top of the Micro Data Center. Save the screws for use when installing the power inlet box.
2. The power inlet box is located in the supplemental equipment box shipped inside the enclosure. There is a connector under the sealing plate. There is a black quick connect connector hanging from the power inlet box that connects to a black connector below the removed sealing plate. Those connectors should be pushed together until they make an audible click. Use the screws removed with the sealing plate to secure the power inlet box to the roof of the enclosure .




3. Bring mains power to the Micro Data Center using flexible cable and a receptacle compatible with the IEC309 IP67 connector in the power inlet box. Make sure the connector is the same voltage and current rating as required for the Micro Data Center.
For 5kVA UPS: 250V, 30A inlet connector

NOTE: The power cable inside the MDC enclosure has been installed at the factory. The power cable is hardwired into the 5K UPS.

Install the Roxtec Gasket

Remove the sealing plate and install the Roxtec cable entry system (provided in the supplemental equipment box) using the four (4) hex head screws included.



Install the Cooling Equipment

The cooling unit is installed in your EcoStruxure MDC but the refrigerant piping must be installed. The piping (with insulation) for installation in the interior of the cabinet is shipped inside the cabinet. Piping from the cooling unit to the outside condenser is not provided.

⚠ WARNING

EQUIPMENT DAMAGE HAZARD

Cooling equipment shall be installed and serviced only by qualified persons.

Failure to follow these instructions can result in death, serious injury, or equipment damage.

NOTES:

- Refer to the Installation Manual for your cooling unit for installation instructions.
- Perform all commissioning checks, leak detection, and vacuum pumping procedures as directed in your cooling installation manual.

The cooling unit is installed at the bottom of the cabinet.

Locate and remove the refrigerant pipes secured to the inside of the Micro Data Center cabinet. Connect the suction line valve and liquid line valve on your cooling unit.

The condensate drain line is coiled below the sealing plate where the Roxtec cable entry system will be installed.


Ensure the condensate drain hose is properly installed so that condensate can drain properly. Refer to the Installation instructions for your condensate pump.

Follow the instructions in the manual for your cooling unit to install the outdoor condenser. Connect the suction line valve and the liquid line valve from the condenser to the appropriate refrigerant lines in the cabinet. If your MDC includes a low ambient kit, refer to the installation instructions provided with the kit.

NOTES:

- Do not apply power to the outdoor cooling unit until the Micro Data Center is receiving power.
- Do not remove the covers of the line valves before connecting the pipes.
- Ensure the connections between the valves and the pipes are tight.


Ensure that any areas of exposed piping on the interior of the MDC are covered with insulation (not provided).



Fire Suppression

The Fire Suppression system requires the installation of the green connector (provided in the Accessory Box) to the top receptacle on the back of the unit. The green connector has a red jumper wire to activate the internal battery backup.


The key (provided in the Accessory Box) is necessary to change the setting from **Isolate** to **Normal**.




Refer to the Fire Suppression system Quick Start manual for start-up instructions.

Lighting Installation

The two LED lighting strips are packed inside the accessory box. Remove them from the shipping box. The light strips are magnetic and are installed to the inside of the roof at the front and rear of the enclosure.



Plug the light strips into the pre-installed power cables. The lights should be positioned towards the front and rear rack opening and doors so they do not interfere with cables and power cords.



The UPS


NOTE: Refer to the UPS manual included with your Micro Data Center for complete installation instructions.

Complete the setup of the UPS as described in the UPS Operation manual.

Access the Micro DC Switch and EcoStruxure Gateway Appliance

Remove the cover plates to obtain access to the Micro DC switch and EcoStruxure Gateway appliance.

There are two (2) cover plates covering access points on the frame. Remove two (2) Phillips head screws securing each plate to the frame.



NOTE: Replace the panels after cables have been secured to the Micro DC switch and EcoStruxure Gateway appliance.

Start-Up

NOTE: Check each cable and power cord to be sure the connection is secure. A loose cable or power cord will cause delays in configuring your Micro Data Center.

Checklist for Initial Start-up

1. Mains power is connected to the unit.
2. UPS batteries are secured.
3. The UPS powered ON. The UPS network cable is connected to the Micro DC Switch
 - Check the display on the UPS for status.
 - The Rack PDU(s) power cable(s) are connected to the UPS, and are powered ON. The Rack PDU(s) network cables are connected to the Micro DC Switch. Check the operation status on the Rack PDU display.
4. Determine which NetBotz model is installed in your MDC (NB250 or NB750). The Netbotz power cable is connected to the Rack PDU. The NetBotz appliance network cable is connected to the Relay Output port on NB250 and to the Relay 1 port on NB750. This network cable is connected at the other end to the Micro DC Switch. MDCs with cooling units and fans have an additional cable attached to the relay output on the NetBotz appliance.
5. Sensors are positioned and cables connected to the NetBotz device.
 - Temperature/Humidity sensors: MDCs with cooling units have three (3) temp/humidity sensors. One (1) temp/humidity sensor will be secured to the side of the U-space. After the customer equipment is installed, move this sensor and secure it to the approximate center (left-to-right) to ensure that the sensor is located in the active airflow of the equipment. The other two (2) temp/humidity sensors are factory installed to the air conditioning unit.
 - Spot leak sensor (only on MDCs with cooling units)
 - Door contact sensors
 - Camera


Refer to the NetBotz User Guide for more complete instructions.
6. The cooling unit power cord is connected to the Rack PDU. A USB communication cable connects the cooling unit to the EcoStruxure IT Gateway.
7. The fire suppression system power cord is plugged into the Rack PDU and its network cable is connected to the Micro DC Switch. The smoke detection sensors are in place. An additional power cord is plugged into the fire suppression system at one end and the fan box at the other end.
8. The Micro DC Switch power cord is plugged into the Rack PDU and powered ON.
9. The fan power cord is plugged into the Rack PDU on MDCs with fan-only ventilation. The fan is plugged into the NetBotz appliance on MDCs with both a cooling unit and fan.
10. The EcoStruxure IT Gateway appliance: The EcoStruxure IT Gateway power cable is plugged into the Rack PDU. Review the previous steps in this section to make sure all connections are correct before initiating the Gateway appliance. Go online to <https://helpcenter.ecostruxureit.com>. Information is available here to help you log in and set up accounts. Follow the instructions on the EcoStruxure IT Help Center pages.

EcoStruxure IT Gateway

Sign Up and Create an EcoStruxure IT Account

Open a browser window on your computer and navigate to <https://ecostruxureit.com/> and sign up for an EcoStruxure IT account.

Connections to the EcoStruxure Gateway



The EcoStruxure Micro Data Center is configured at the factory with the EcoStruxure IT Gateway appliance and the Micro DC switch installed along with a complement of power, cooling, and sensing devices, depending on the model. The communication cables from the devices installed in the MDC are connected to the Micro DC switch or directly to the EcoStruxure IT Gateway appliance as required. See the illustration above.

Software versions on the EcoStruxure IT Gateway appliance may vary. Instructions are available at <https://helpcenter.ecostruxureit.com/> to explain how to configure your Gateway appliance.

- Software versions 1.9.0 and older use Webmin to configure the network. Instructions for software versions 1.9.0 and older are available on the helpcenter Web pages.
- Software versions 1.10 and newer configure the network from EcoStruxure Web pages. Instructions for software versions 1.10 and newer are also available on the helpcenter Web pages.


Connect Your Computer to the Gateway Appliance

NOTE: Remove the cover plates to obtain access to the Micro DC switch and EcoStruxure Gateway appliance.


The EcoStruxure IT Gateway appliance has two network connection ports, LAN1 and LAN2.

The LAN1 port connects the Gateway appliance to the Public network. This is the port that the Gateway appliance uses to communicate with your building network. Connect your building's network to the LAN1 port with a communication cable (not provided).

The LAN2 port connects you to the Private network of the Gateway appliance. Connect your computer with a communication cable (not provided) to the LAN2 port to set up the Gateway appliance or, because the LAN2 port already has a cable connected to the Micro DC Switch at the factory, you can make your connection to LAN2 from an empty port on the Micro DC Switch.



View of Gateway from rear of MDC



View of Micro DC Switch from front of MDC

NOTE: Check that the power cables are securely connected to the Gateway appliance and the Micro DC switch.

Check that the Gateway appliance is powered on. If the Gateway appliance is not on, press the power button to turn it on.

Wait ten minutes to allow the Gateway appliance to fully initialize.

Open a browser window on your computer. Enter the IP address 192.168.0.1. If the EcoStruxure login page opens, your software version is 1.10 or newer. If the attempt does not succeed, enter the IP address 192.168.0.1:10000 to connect to Webmin. If you succeed in connecting to Webmin, your software version is 1.9 or older.

Continue setup using the instructions for your software version available in the helpcenter.


NOTICE

Following configuration of your EcoStruxure IT Gateway, you must then allow the Gateway to discover the devices and sensors connected. Any devices or sensors you add after the initial setup will require you to run Discover Devices again so the new devices can be discovered by the EcoStruxure IT Gateway.


Gateway Version 1.9 and Older

Prerequisite: Your computer is connected to the building network and to the LAN 2 port (Private side) of the Gateway.

1. On your computer, open a browser window and enter the IP Address of Webmin (192.168.0.1:10000).




Login at the Webmin prompt. The credentials for user and password are both **setup**.

A screenshot of the Webmin login page. At the top is the Webmin logo (a stylized 'W' with three hands) and the text "Webmin". Below this is the instruction: "You must enter a username and password to login to the server on 192.168.0.1". There are two input fields: the first is for the username, with a user icon on the left and the text "setup" inside; the second is for the password, with a lock icon on the left, the text "setup" inside, and a "show/hide" eye icon on the right. Below the input fields is a blue button with a right-pointing arrow and the text "Sign in".

You will be prompted to change your password. You must change the default password before you will be allowed to continue.


 You must select a new password to replace your temporary login.



The image shows the Webmin interface for changing a password. At the top, the Webmin logo is displayed next to the text "Webmin". Below the logo, the text "Set new password for user *setup*" is shown. There are three input fields for the password: the first field is for the current password (containing five dots), the second field is for the new password (containing seven dots), and the third field is for the confirm password (containing seven dots). Each field has a small icon to its left: a key for the current password and a plus sign for the new and confirm passwords. A blue button with a lock icon and the text "Change" is located below the input fields.

Your password has been successfully changed. You may now [login again](#) with the new password.


2. Log in with your new password.




Navigate to: **System Configuration > Network Configuration > Network Interfaces**

On the page that opens, in the Navigation pane on the left side of the page:

- Click on the arrow next to **System Configuration** to open the dropdown menu.
- Select **Network Configuration** from the dropdown menu to open the Network Configuration page.
- Click the **Network Interfaces** icon on the page.




- The **Network Interfaces** page will open.
- The Network Interfaces page shows the interfaces list in the **Activated at Boot** tab by default. Select the **Active Now** tab to open the list of available Active Network Interfaces.




- The **Active Now** list of Network Interfaces will show the interfaces that are currently active on the system.
- **eth0** is the name of the interface for the LAN1 port of the EcoStruxure IT Gateway appliance. This is the Gateway Public network. Make a note of the IP address of **eth0**. You will need this IP address to access the Gateway Public network.

NOTE: eth1 is the interface for LAN2, the Gateway Private network.



3. Close Webmin and disconnect your computer from the LAN2 port (or the port on the Micro DC switch).
4. With your computer connected to the building network, open a browser window and enter the **Public IP address** of your Gateway appliance (eth0): *https://<Public_IP_Address>/*
5. When the Web page opens, enter the EcoStruxure IT Gateway initial credentials: Username: **admin** and Password: **admin**



6. You will be prompted to change your password. You must change your password in order to continue.



To continue setup, go to Configure Credentials in this manual.


Gateway Version 1.10 and Newer

Prerequisite: Your computer is connected to the building network and to the LAN 2 port (Private side) of the Gateway.


1. On your computer, open a browser window and enter the IP Address of the Gateway appliance (192.168.0.1).




2. The Initial Login page will open. Enter the EcoStruxure IT Gateway initial credentials: Username - **admin** and Password - **setup**.



3. You will be prompted to change your password. You must change your password before you can continue.



4. On the page that opens, you can verify the Gateway appliance configuration. Click on the **Configure and manage appliance** bar to view or modify the settings.



5. The **Appliance Settings** page will open. On the **Public Network** tab, the IP Address and other information related to the public network interface (LAN1 on the Gateway) is shown. Make a note of the IP Address and the other information.
- On the Private Network tab, the information related to the private network can be viewed or modified.
- Make sure the information on both the Public Network tab and Private Network tab is correct before proceeding to discover the devices connected to your Gateway appliance. These settings depend on your network configuration.

NOTICE

Your network administrator can provide a root certificate and proxy settings as necessary.

The screenshot shows the 'Appliance Settings' page for the 'Public Network' tab. The page title is 'Configure public network interface (LAN1 or Gb1)'. There are buttons for 'Add root certificate', 'Proxy settings', and 'Setup tips'. The 'Hostname' is 'localhost.localdomain'. The 'Ethernet connection' is 'Up'. A note states: 'The Gateway uses the public network to communicate with EcoStruxure IT. You use the public network to access the Gateway application on your local area network.' The 'Use DHCP (Basic)' option is selected. Below this, there are fields for 'IPv4 address' (192.168.68.175), 'Subnet mask' (255.255.255.0), 'Default gateway' (192.168.68.1), and 'Search domain'. The 'DNS servers' field contains '71.10.216.1, 71.10.216.2, 192.168.68.1'. A warning message at the bottom states: 'These settings depend on your network configuration. Consult your IT department if you are unsure of what settings to use.' There are 'Apply' and 'Cancel' buttons at the bottom.

6. Disconnect from the Private network. From the Public Network, continue with the setup procedure. Go to Configure Credentials on the next page.

Configure Credentials

NOTICE

- A firewall on your building network could prohibit the connection to the EcoStruxure IT cloud. See your network administrator for the necessary root certificate if required.
- Before configuring credentials for the devices connected to the Gateway appliance, update the EcoStruxure software version to the latest version available. See the instructions on the EcoStruxure Help Center website.

Prerequisite: Your computer must be connected to the building network. Open a browser window and enter the IP address you obtained from the Private Network.

NOTICE

- The devices connected to your Gateway appliance were configured to use SNMPv3 at the factory. If you configure your Gateway appliance using different SNMPv3 settings or credentials or if SNMPv1 will be used, the connected devices will need to be re-configured to match. For security reasons, SNMPv3 is recommended.
- It is recommended that you login to all the devices connected to the Gateway and change the default passwords to enhance your cybersecurity.


Configure SNMPv3 Credentials

Instructions for setting up SNMPv1 and SNMPv3 credentials are available online. The EcoStruxure IT Gateway installed in the MDC, requires you to configure SNMPv3 because the devices attached have been configured to use SNMPv3. From the EcoStruxure IT Gateway's opening page, click on the **Lets get started** button to open the Device Credentials page.

Follow these steps to start monitoring your devices in the EcoStruxure IT cloud.



Click on **New Device Credentials** to open the dropdown menu. Select **SNMPv3**.



Complete the Credentials form for SNMPv3.

Label: SNMPv3

Username: SEMDC1

Authentication type: SHA

Authentication password: MDC-NNMP-AUTH-1

Encryption type: AES128

Encryption password: MDC-SNMP-ENC-1

Port: 161

Click on the **Create Setting** button at the bottom of the page to save your settings.

Create Device Credentials



SNMPv3

Label *

Username *

Authentication type

Authentication password *



Encryption type

Encryption password *



Port *

Create setting

Configure SCP File Transfer Credentials

1. Configure SCP-apc credentials:

On the EcoStruxure IT Gateway, SCP (Secure Copy Protocol) is the protocol used to upgrade the firmware of the NMC-based devices in your MDC. When updated firmware is available, you can push the latest firmware to all of the connected devices with a click of a button.

NOTICE
NMC-based devices (Rack PDUs, UPS, and NetBotz 250) use the username apc for configuring SCP credentials.

- Click on **New File Transfer Credentials** to see the dropdown menu. Select **SCP**.



- The **Create Device Credentials for SCP** dialog box will open. Enter the required information for SCP-apc in the form.

Label: SCP-apc
Username: apc
Password: MDC-APC-1
Port: 22

Click on the **Create Setting** button at the bottom of the dialog box to save your information.

Create Device Credentials

✕

SCP

Label *

Username *

Password *

 👁

Port *

Create setting

2. Configure SCP-root credentials: (for MDCs with NetBotz 750 only)

<h2>NOTICE</h2>
<ul style="list-style-type: none">• The NetBotz 750 is not an NMC-based device. The NetBotz 750 uses Linux. With Linux, root is the only way to access SCP for firmware upgrades.• Currently, NetBotz 750 does not support SCP to update its firmware through the EcoStruxure IT Gateway.• Configure the SCP-root credentials for the NetBotz 750 to avoid an error message from the EcoStruxure IT Gateway that it is unable to communicate over SCP with the NetBotz 750.

- Click on **New File Transfer Credentials** to see the dropdown menu. Select **SCP**.



- The **Create Device Credentials for SCP** dialog box will open. Enter the required information for SCP-root in the form.

Label: SCP-root
Username: root
Password: apc
Port: 22

Click on the **Create Setting** button at the bottom of the dialog box to save your information.

Create Device Credentials

✕

SCP

Label *

Username *

Password *


👁

Port *

Create setting

Confirm Settings

The Device Credentials page should now show that the Device Credentials have been set to SNMPv3 and the File Transfer Credentials have been set to SCP-apc and SCP-root.



EcoStruxure IT Gateway

- **DEVICE CREDENTIALS**
- DISCOVER DEVICES
- REGISTER GATEWAY

Device Credentials

Manage the settings this EcoStruxure IT Gateway uses to communicate with your devices.

Discovery and Polling

Add device credentials. These settings are required to discover and poll devices. [+ NEW DEVICE CREDENTIALS ▾](#)

S3	SNMPv3 SNMPv3 SEMDCC1
----	-----------------------------

Device Configuration and Firmware Update

Add APC Network Management Card file transfer credentials. These settings are required to retrieve and configure settings for your devices and to apply firmware updates. [+ NEW FILE TRANSFER CREDENTIALS](#)

SCP	SCP - apc SCP apc
SCP	SCP - root SCP root

© 2021 Schneider Electric

DISCOVER DEVICES [Next](#)

NOTE: Discovery of device credentials using SCP-root is only required if your MDC contains a **NetBotz 750** appliance.

Discover Devices

Discover all devices connected to the EIT Gateway.

Prerequisite: Your computer is connected to the building network (the same network as the Gateway appliance), you are logged in to the Gateway (with the same password you created while on the private network) and have navigated to the Discover Devices page.

On the Discover Devices page, enter the IP search range: **192.168.0.*** at the **IP search range bar**.

Click the **Discover Devices** button to initiate the search.

Go to the helpcenter online for more information:

<https://helpcenter.ecostruxureit.com/hc/en-us/articles/360021184553-Discover-devices>

The screenshot shows the 'Discover Devices' interface. On the left, there are navigation options: 'DEVICE CREDENTIALS', 'DISCOVER DEVICES' (selected), and 'REGISTER GATEWAY'. The main area has a heading 'Discover Devices' and a sub-heading 'Locate devices and begin monitoring them with EcoStruxure IT.' Below this is an 'IP search range' input field containing '192.168.0.*' and an 'Import...' button. A 'Discovering a Modbus device?' message is shown below the input. A green 'Discover devices' button is prominent. To the right, there are 'Device Discovery Tips' and a 'USE ALL CREDENTIALS' dropdown. The footer includes '© 2021 Schneider Electric', 'REGISTER GATEWAY', and a green 'Next' button.

The devices are shown in the Summary section of the page when the search is complete. The number of devices will vary depending upon the configuration of your MDC.

NOTE: Any devices that are discovered but have configuration issues will be noted in red in the Summary.

This screenshot shows the 'Discover Devices' page after a search. The 'Summary' section is visible, showing '2 discovered' devices. Below this, it says 'Total devices discovered' and provides a 'Go to devices' link. The rest of the page, including the search range '192.168.0.*' and the 'Discover devices' button, remains the same as in the previous screenshot. The footer also remains the same.

Discover the Cooling Unit

NOTICE

Due to a current unresolved issue, EcoStruxure IT cannot discover the cooling unit. The issue is under investigation. The cooling unit will operate normally. EcoStruxure IT will not display the cooling unit settings at this time.

NOTE: The Cooling Unit may not be discovered until you register your EcoStruxure IT Gateway appliance and update the firmware (if necessary) to the most recent version. If you previously discovered your devices, you may need to re-discover your devices after updating to the latest Gateway firmware revision.

1. From your laptop connected to the same building network as the Gateway appliance, login to the Gateway.
2. Navigate to the **Discover Devices** page
3. Click on **Discovering a Modbus device?**

Discover Devices

Locate devices and begin monitoring them with EcoStruxure IT.

IP search range

[Import...](#)

Enter IP search range. Supports wildcards, dashes, and commas.

[USE ALL CREDENTIALS](#) ▼

[Discovering a Modbus device?](#)

[Discover devices](#)

Set the following on the Discover Devices page and click on **Discover Modbus device** when the form has been completed.

Serial (radio button)
Type: Crac
Vendor: Uniflair
Family: Rack_mount_room_cooling
Server address: 1

Default settings for Serial:

Port: ttyUSB0
Baud Rate: 9600
Data Bits: 8
Parity: None
Stop Bits: 1
Flow Control: None

Discover Devices

Locate devices and begin monitoring them with EcoStruxure IT. [Device Discovery Tips +](#)

Type	Vendor	Family	Server address
Crac	Uniflair	Rack_mount_room_cooling	1

TCP Serial

Port	Baud Rate	Data Bits
ttyUSB0	9600	8

Parity	Stop Bits	Flow Control
None	1	None

[Not discovering a Modbus device?](#)

Discover Modbus device

Confirm the values shown on the page with the values specified in your cooling unit manual.

NOTICE

To confirm that the Cooling Unit (and other devices) are connected, navigate to the Devices page and check that they are all connected and reporting data. The data updates every 5 minutes.

Discover Fire Suppression

NOTE: The Fire Suppression system may not be discovered until you register your EcoStruxure IT Gateway appliance and update the firmware (if necessary) to the most recent version. If you previously discovered your devices, you may need to re-discover your devices after updating to the latest Gateway firmware revision.

1. From your laptop connected to the same building network as the Gateway appliance, login to the Gateway.
2. Navigate to the **Discover Devices** page
3. Click on **Discovering a Modbus device?**

Discover Devices

Locate devices and begin monitoring them with EcoStruxure IT.

IP search range [Import...](#)

USE ALL CREDENTIALS ▾

[Discovering a Modbus device?](#)

[Discover devices](#)

Set Type, Vendor, and Family as shown below. Set the IP Address to 192.168.0.2 and the Server Address to 1.

Click on “Discover Modbus Device.”

If the Redetec Fire Suppression unit is not discovered, change the IP Address to 192.168.0.3 and try to discover again. If not discovered, repeat the process incrementing the IP Address by 1 each time until the Redetec unit is discovered.

Discover Devices

Locate devices and begin monitoring them with EcoStruxure IT.

Type: Vendor: Family:

TCP Serial

IP address: Server address: [Import...](#)

Port:

[Not discovering a Modbus device?](#)

[Discover Modbus device](#)

Optional Setup Information


Redetec Default Passwords

To change the SNMP credentials from default:

From the private network of the gateway, go to `http://<ip_address_of_Redetec>/setup.html`

The administrator username is admin.


PASSWORDS

 **ADMINISTRATOR**
Access to all setup and control pages. Username: "admin"

Enter Password:

Re-enter Password:

Hide / Show Password


 **MANAGER**
Access to Tasks and Control Pages. Username: "manager"

Enable Manager Login:

Enter Password:

Re-enter Password:

Hide / Show Password


 **USER**
Access to Control Pages only. Username: "user"

Enable Password Requirement:

Install Accessories and Your Equipment

Install the Cable Managers


Cable managers are included in the accessory box. There are installation posts on the side and rear of the cable manager. The cable managers can be installed from either post. The posts of the cable manager are installed to the rear of the MDC as shown in the illustration below.



Cage Nuts

Proper location in the rack for the cage nuts:

1. Locate the top and bottom U space on the vertical mounting rails. Every third hole on the mounting rails is numbered to indicate the middle of a U space.
2. Install the cage nuts on the interior of the vertical mounting rail; then install the shelf.




⚠ CAUTION

FALLING EQUIPMENT HAZARD

Do NOT install cage nuts vertically with the tabs engaging the top and bottom of the square hole.


Failure to follow these instructions can result in injury or equipment damage.

- Install cage nuts horizontally, with the tabs engaging the sides of the square hole.
- Install the cage nuts on the interior of the vertical mounting rail.



Install the cage nut:

1. From the inside of the rack, insert the cage nut into the square hole.
2. Hook one tab of the cage nut assembly through the far side of the hole.
3. Place the cage nut tool on the other side of the cage nut and pull to snap into position.




Remove the cage nut:

1. Remove any attached screw.
2. Grasp the cage nut, squeeze the tabs on the sides, and push to release it from the square hole.

Install Your Equipment

If possible, install your equipment starting from the bottom of the MDC and working your way up. Use the cage nuts and M6 screws supplied in the hardware bag to secure the equipment in the MDC.




Troubleshooting

Reset NetBotz after Cooling Unit Powered Off

Perform this task if the in-rack cooling unit has shut down and the ventilation fan has been enabled by your NetBotz appliance.

NetBotz 750

1. Log in to the NetBotz appliance. Go to: **Setting > Alarm Configuration**



2. Navigate to the Edit Alarm Configuration page and choose the MDC Supply Air Temperature (High) alarm configuration. Click on the **Output 1** (ACRM Disable) box to remove the check mark then, click OK at the bottom of the page.

Edit Alarm Configuration

Name

Type
 Temperature

Operation

Value
 °F

Severity
 Critical Warning Informational

[Sensors](#) [Clip Capture](#) [Control](#) [Schedule](#)

Choose controls

2 selected

Name	Pod	Port	On alarm active	On alarm clear
<input type="checkbox"/> Output 2	Appliance	2	Active	Inactive
<input checked="" type="checkbox"/> Output 1	Appliance	1	Active	Active
<input checked="" type="checkbox"/> Switched Outlet	Appliance		Active	Active

3. Change the state of **Output 1** from Active to Inactive

The screenshot displays a monitoring interface. At the top left, there is a video feed labeled 'No Motion' showing a dark, blurry image. To the right of the video is a camera icon. Below the video is a table titled 'Appliance' with columns for 'Port', 'Label', and status. The 'Output 1' row is highlighted in yellow. A pop-up window for 'Output 1' is overlaid on the table, showing the status 'Active' in large yellow text and a blue button labeled 'SET TO INACTIVE'.

Port	Label	Status
Switched Outlet		Active
1	Temperature 1	84 °F 68 % RH
2	Temperature 2	83.1 °F 68 % RH
3	Spot Leak 3	Leak
4	Temperature 4	80.6 °F 69 % RH
6	Temperature 6	82.8 °F 59 % RH
1	Output 1	Active
2	Output 2	
1	Current In	
2	Current In	

4. When the cooling unit is operating, the settings can be returned to their original state.

Navigate to the **MDC Supply Air Temperature (High)** page.

Click on the **Output 1** (ACRM Disable) box to insert the check mark then, click OK at the bottom of the page.

Go to **NetBotz > Overview**

Change the state of the **Switched Outlet** from Active to Inactive.

The screenshot shows the NetBotz 750 interface. At the top, there is a header with the NetBotz logo, the device name 'NetBotz 750', and two status indicators (a red 'x' and a yellow warning triangle). Below the header, there is a section for 'APC-9A2016Y00364 Auto' with a 'No Motion' status and a video feed area. The main content is a table titled 'Appliance' with columns for 'Port', 'Label', and 'Active'. A modal window is open over the 'Switched Outlet' row, showing its current state as 'Active' and a 'SET TO INACTIVE' button.

Port	Label	Active
⊗	Switched Outlet	Active
⚠	1 Temperatu	86 % RH
⚠	2 Temperatu	88 % RH
⊗	3 Spot Leak	
⚠	4 Temperatu	69 % RH
⚠	6 Temperatu	77 % RH
↔	1 Output 1	
↔	2 Output 2	
⚡	1 Current Input 1	0 mA
⚡	2 Current Input 2	0 mA

5. If the ventilation fan comes back on, the temperature is above 35°C. This is the temperature setting at which the ventilation fan is set to come on. You will need to repeat the task again starting at Step 1.

6. Edit the Alarm Configuration:

NOTICE

HAZARD OF EQUIPMENT DAMAGE

Failure to reset to the original settings as defined in this step may damage equipment.

Failure to follow these instructions can result in equipment damage.

Ensure you have completed all of the following steps on the Alarm Configuration page:

- Edit the settings for the **MDC Supply Air Temperature (High)** alarm.
- Under the **Control** tab, select Output 1
Confirm that the box is checked
Confirm that the state on the **On alarm clear** column is set to Active.
- Click OK to save your settings.

Edit Alarm Configuration ✕

Name

Type
Temperature

Operation Value

Severity
 Critical Warning Informational

[Sensors](#) [Clip Capture](#) [Control](#) [Schedule](#)

Choose controls 2 selected

Name	Pod	Port		On alarm active	On alarm clear
<input type="checkbox"/> Output 2	Appliance	← 2	set to	Active ▾	Inactive ▾
<input checked="" type="checkbox"/> Output 1	Appliance	← 1	set to	Active ▾	Active ▾
<input checked="" type="checkbox"/> Switched Outlet	Appliance	⚡	set to	Active ▾	Active ▾

Specifications

	MDC42USRSI	MDC42UARS1
Electrical		
Rated Input Voltage	230 VAC 50Hz	
Rated Input Current	30A	
Power Inlet	IEC 309 250 V IP 67 2P 3W	
Power Connector (Customer Provided)	IEC 309 250 V IP67 2P 3W 30A (IEC)/32A (UL)	IEC 309 250 V IP67 2P 3W 30A (IEC)/32A (UL)
Load Rating	3.5 kW	
UPS Input	5 kVA	
Rack PDUs (Quantity 2)	AP8858 — 16A, 230V, IEC-320–C20 Inlet IEC-320 C-13 outlets, (18) and IEC-320 C-19 outlets (2)	
Security	Standard Keylock Door Contacts	Standard Keylock Door Contacts Camera
Sensors	Temp and Humidity, Leak	
Cooling	3.5 kW Uniflair Rack Mount	3.5 kW Uniflair Rack Mount Emergency Fan Ventilation
Total Cooling Capacity	3.5 kW (11,900 BTU/hr)	
Rated Air Volume	700 m ³ /h (410 SCFM)	
Environmental		
Operating Temperature	Fan only: 10–35°C (50–95°F) ACRM only: 10–40°C (50–104°F) ACRM and Fan: 10–35°C (50–95°F)	
Storage Temperature	-5°C to 45°C (23°F to 115°F)	
Humidity Range	<95% RH	
Altitude	0 – 3000 m (0 – 10000 ft) / 0 — 15000 m (0 — 50000 ft)	
Noise Rating	64 dBA	62.5 dBA 72 dBA (Emergency Ventilation)

	MDC42USRSI	MDC42UARS I
Physical		
Dimensions 42U MDC only		
As shipped : H x W x D mm (in)	2006 x 800 x 1212 (79 x 31.5 x 47.7)	2006 x 800 x 1220 (79 x 31.5 x 48)
With Power Inlet Installed: H x W x D mm (in)	2146 x 800 x 1212 (84.5 x 31.5 x 47.7)	2146 x 800 x 1220 (84.5 x 31.5 x 48)
Packaged 42U MDC on pallet H x W x D mm (in)	2170 x 1105 x 1321 (85.4 x 43.5 x 52)	
Load Ratings: kg (lb) Static: Dynamic: Shipped:	1361 kg (3750 lb) Maximum load with leveling feet lowered 1022 kg (2250 lb) Maximum load while rolling the unit on its casters 909 kg (2000 lb) Maximum weight as shipped on pallet with the required brackets	
Clearance Requirements:	1 m (3 ft) front and rear	
Compliance		
EMC verification	EN 55032, EN 55035, EN 61000-3-2, EN 61000-3-3, BS EN 55032, BS EN 55035	
IT Earthing system	Yes	

Enclosure Warranty

The warranty below extends to the enclosure only. Components included in the MDC enclosure are covered by warranties specific to the component.

2 Year Parts Only Factory Warranty

The limited warranty provided by Schneider Electric in this Statement of Limited Factory Warranty applies only to products you purchase for your commercial or industrial use in the ordinary course of your business.

Terms of Warranty

Schneider Electric warrants its products to be free from defects in materials and workmanship for a period of three years from the date of purchase. The obligation of Schneider Electric under this warranty is limited to repairing or replacing, at its sole discretion, any such defective products. This warranty does not apply to equipment that has been damaged by accident, negligence or misapplication or has been altered or modified in any way. Repair or replacement of a defective product or part thereof does not extend the original warranty period. Any parts furnished under this warranty may be new or factory-remanufactured.

Non-transferable warranty

This warranty extends only to the original purchaser who must have properly registered the product. The product may be registered at the Schneider Electric website, www.se.com.

Exclusions

Schneider Electric shall not be liable under the warranty if its testing and examination disclose that the alleged defect in the product does not exist or was caused by end user's or any third person's misuse, negligence, improper installation or testing. Further, Schneider Electric shall not be liable under the warranty for unauthorized attempts to repair or modify wrong or inadequate electrical voltage or connection, inappropriate on-site operation conditions, corrosive atmosphere, repair, installation, start-up by non-Schneider Electric designated personnel, a change in location or operating use, exposure to the elements, Acts of God, fire, theft, or installation contrary to Schneider Electric recommendations or specifications or in any event if the Schneider Electric serial number has been altered, defaced, or removed, or any other cause beyond the range of the intended use.

THERE ARE NO WARRANTIES, EXPRESS OR IMPLIED, BY OPERATION OF LAW OR OTHERWISE, OF PRODUCTS SOLD, SERVICED OR FURNISHED UNDER THIS AGREEMENT OR IN CONNECTION HEREWITH. SCHNEIDER ELECTRIC DISCLAIMS ALL IMPLIED WARRANTIES OF MERCHANTABILITY, SATISFACTION AND FITNESS FOR A PARTICULAR PURPOSE. SCHNEIDER ELECTRIC EXPRESS WARRANTIES WILL NOT BE ENLARGED, DIMINISHED, OR AFFECTED BY AND NO OBLIGATION OR LIABILITY WILL ARISE OUT OF, SCHNEIDER ELECTRIC RENDERING OF TECHNICAL OR OTHER ADVICE OR SERVICE IN CONNECTION WITH THE PRODUCTS. THE FOREGOING WARRANTIES AND REMEDIES ARE EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES AND REMEDIES. THE WARRANTIES SET FORTH ABOVE CONSTITUTE SCHNEIDER ELECTRIC'S SOLE LIABILITY AND PURCHASER'S EXCLUSIVE REMEDY FOR ANY BREACH OF SUCH WARRANTIES.

SCHNEIDER ELECTRIC WARRANTIES EXTEND ONLY TO PURCHASER AND ARE NOT EXTENDED TO ANY THIRD PARTIES.

IN NO EVENT SHALL SCHNEIDER ELECTRIC, ITS OFFICERS, DIRECTORS, AFFILIATES OR EMPLOYEES BE LIABLE FOR ANY FORM OF INDIRECT, SPECIAL, CONSEQUENTIAL OR PUNITIVE DAMAGES, ARISING OUT OF THE USE, SERVICE OR INSTALLATION, OF THE PRODUCTS, WHETHER SUCH DAMAGES ARISE IN CONTRACT OR TORT, IRRESPECTIVE OF FAULT, NEGLIGENCE OR STRICT LIABILITY OR WHETHER SCHNEIDER ELECTRIC HAS BEEN ADVISED IN ADVANCE OF THE POSSIBILITY OF SUCH DAMAGES. SPECIFICALLY, APC BY SCHNEIDER ELECTRIC IS NOT LIABLE FOR ANY COSTS, SUCH AS LOST PROFITS OR REVENUE, LOSS OF EQUIPMENT, LOSS OF USE OF EQUIPMENT, LOSS OF SOFTWARE, LOSS OF DATA, COSTS OF SUBSTITUENTS, CLAIMS BY THIRD PARTIES, OR OTHERWISE.

NO SALESMAN, EMPLOYEE OR AGENT OF SCHNEIDER ELECTRIC IS AUTHORIZED TO ADD TO OR VARY THE TERMS OF THIS WARRANTY. WARRANTY TERMS MAY BE MODIFIED, IF AT ALL, ONLY IN WRITING SIGNED BY A SCHNEIDER ELECTRIC OFFICER AND LEGAL DEPARTMENT.

Warranty claims

Customers with warranty claims issues may access the Schneider Electric customer support network through the Support page of the Schneider Electric website, www.se.com/support. Select your country from the country selection pull-down menu at the top of the Web page. Select the Support tab to obtain contact information for customer support in your region.

APC
70 Mechanic Street
02035 Foxboro, MA
USA

www.apc.com

As standards, specifications, and design change from time to time,
please ask for confirmation of the information given in this publication.

© – 2023 Schneider Electric. All rights reserved.

990–6350A-001