



# SAFETY DATA SHEET

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name or designation of the mixture KONTAKT PCC

Registration number -

Synonyms None.

Product code BDS002425AE

Issue date 19-May-2021

Version number 01

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Cleaners - Precision

Uses advised against None known.

### 1.3. Details of the supplier of the safety data sheet

Company name CRC Industries Europe bv

Address Touwslagerstraat 1  
9240 Zele  
Belgium

Telephone +32(0)52/45.60.11

Fax +32(0)52/45.00.34

E-mail hse@crcind.com

Website www.crcind.com

1.4. Emergency telephone number Tel.: +32(0)52/45.60.11 (office hours)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Regulation (EC) No 1272/2008 as amended

##### Physical hazards

Aerosols	Category 1	H222 - Extremely flammable aerosol. H229 - Pressurized container: May burst if heated.
----------	------------	-------------------------------------------------------------------------------------------

##### Health hazards

Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
---------------------------	------------	--------------------------------

Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.
-----------------------------------	------------	---------------------------------------

Specific target organ toxicity - single exposure	Category 3 narcotic effects	H336 - May cause drowsiness or dizziness.
--------------------------------------------------	-----------------------------	-------------------------------------------

##### Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard	Category 3	H412 - Harmful to aquatic life with long lasting effects.
----------------------------------------------------------------	------------	-----------------------------------------------------------

### Hazard summary

Aerosol CONTENTS UNDER PRESSURE.  
Pressurised container may explode when exposed to heat or flame. May cause drowsiness or dizziness. Causes serious eye irritation. Causes skin irritation. Dangerous for the environment if discharged into watercourses. Occupational exposure to the substance or mixture may cause adverse health effects.

### 2.2. Label elements

#### Label according to Regulation (EC) No. 1272/2008 as amended

Contains: 1-ethoxypropan-2-ol; 2PG1EE; 1-ethoxy-2-propanol; propylene glycol monoethyl ether, Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane, Propan-2-ol; Isopropyl alcohol; Isopropanol

## Hazard pictograms



## Signal word

Danger

## Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurized container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

## Precautionary statements

### Prevention

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing mist/vapours.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

### Response

Not assigned.

### Storage

P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
-------------	----------------------------------------------------------------------------

### Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	-----------------------------------------------------------------------------------------------------

**Supplemental label information** Regulation (EC) No 648/2004 on detergents: aliphatic hydrocarbons 15-30%

## 2.3. Other hazards

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII. The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Propan-2-ol; Isopropyl alcohol; Isopropanol	25 - 50	67-63-0 200-661-7	01-2119457558-25	603-117-00-0	
<b>Classification:</b> Flam. Liq. 2;H225, Eye Irrit. 2;H319, STOT SE 3;H336					
ethanol; ethyl alcohol	10 - 25	64-17-5 200-578-6	01-2119457610-43	603-002-00-5	
<b>Classification:</b> Flam. Liq. 2;H225, Eye Irrit. 2;H319					
Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclics,< 5% n-hexane	10 - 25	EC921-024-6 -	01-2119475514-35	-	
<b>Classification:</b> Flam. Liq. 2;H225, Skin Irrit. 2;H315, STOT SE 3;H336, Asp. Tox. 1;H304, Aquatic Chronic 2;H411					
1-ethoxypropan-2-ol; 2PG1EE; 1-ethoxy-2-propanol; propylene glycol monoethyl ether	5 - 10	1569-02-4 216-374-5	01-2119462792-32	603-177-00-8	
<b>Classification:</b> Flam. Liq. 3;H226, Eye Irrit. 2;H319, STOT SE 3;H336					
Carbon dioxide	5 - 10	124-38-9 204-696-9	Exempt	-	#
<b>Classification:</b> Press. Gas;H280					
Methanol	0 - 1	67-56-1 200-659-6	01-2119433307-44	603-001-00-X	#
<b>Classification:</b> Flam. Liq. 2;H225, Acute Tox. 3;H301;(ATE: 100 mg/kg), Acute Tox. 3;H311;(ATE: 300 mg/kg), Acute Tox. 3;H331;(ATE: 3 mg/l), STOT SE 1;H370					
<b>Specific Concentration Limits:</b> STOT SE 1;H370: C >= 10 %, STOT SE 2;H371: 3 % <= C < 10 %					

## List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**Composition comments** The full text for all H-statements is displayed in section 16.

## SECTION 4: First aid measures

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

### 4.1. Description of first aid measures

**Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison centre or doctor/physician if you feel unwell.

**Skin contact** Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

**Eye contact** Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

**Ingestion** In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth.

**4.2. Most important symptoms and effects, both acute and delayed** May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

**4.3. Indication of any immediate medical attention and special treatment needed** Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

## SECTION 5: Firefighting measures

**General fire hazards** Extremely flammable aerosol.

### 5.1. Extinguishing media

**Suitable extinguishing media** Alcohol resistant foam. Powder. Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

**5.2. Special hazards arising from the substance or mixture** Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

### 5.3. Advice for firefighters

**Special protective equipment for firefighters** Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

**Special fire fighting procedures** Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

**Specific methods** Use standard firefighting procedures and consider the hazards of other involved materials. In the event of fire and/or explosion do not breathe fumes.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

**For emergency responders** Keep unnecessary personnel away. Avoid breathing mist/vapours. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

**6.2. Environmental precautions** Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

**6.3. Methods and material for containment and cleaning up** Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. The product is immiscible with water and will spread on the water surface. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

**6.4. Reference to other sections** For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

### 7.2. Conditions for safe storage, including any incompatibilities

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Storage class (TRGS 510): 2B (Aerosol dispensers and lighters)

### 7.3. Specific end use(s)

Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value	
Carbon dioxide (CAS 124-38-9)	STEL	27400 mg/m <sup>3</sup>	
		15000 ppm	
	TWA	9150 mg/m <sup>3</sup>	
ethanol; ethyl alcohol (CAS 64-17-5)	TWA	5000 ppm	
		1920 mg/m <sup>3</sup>	
		1000 ppm	
Methanol (CAS 67-56-1)	STEL	333 mg/m <sup>3</sup>	
		250 ppm	
	TWA	266 mg/m <sup>3</sup>	
Methylal (CAS 109-87-5)		200 ppm	
	STEL	3950 mg/m <sup>3</sup>	
	TWA	1250 ppm	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)		3160 mg/m <sup>3</sup>	
	STEL	1000 ppm	
	TWA	1250 mg/m <sup>3</sup>	
		500 ppm	
	TWA	999 mg/m <sup>3</sup>	
		400 ppm	

##### EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU

Components	Type	Value
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m <sup>3</sup>
		5000 ppm
Methanol (CAS 67-56-1)	TWA	260 mg/m <sup>3</sup>
		200 ppm

### Biological limit values

No biological exposure limits noted for the ingredient(s).

### Recommended monitoring procedures

Follow standard monitoring procedures.

### Derived no effect levels (DNELs)

#### General Population

Components	Value	Assessment factor	Notes
1-ethoxypropan-2-ol; 2PG1EE; 1-ethoxy-2-propanol; propylene glycol monoethyl ether (CAS 1569-02-4)			
Long-term, Systemic, Dermal	44.3 mg/kg bw/day	48	Repeated dose toxicity

Short-term, Systemic, Inhalation	300 mg/m <sup>3</sup>	5	Repeated dose toxicity
ethanol; ethyl alcohol (CAS 64-17-5)			
Long-term, Systemic, Dermal	206 mg/kg bw/day	40	Repeated dose toxicity
Long-term, Systemic, Oral	87 mg/kg bw/day	20	Repeated dose toxicity
Short-term, Local, Inhalation	950 mg/m <sup>3</sup>		respiratory tract irritation
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane (CAS EC921-024-6)			
Long-term, Systemic, Dermal	699 mg/kg bw/day		
Long-term, Systemic, Inhalation	608 mg/m <sup>3</sup>		
Long-term, Systemic, Oral	699 mg/kg bw/day		
Methanol (CAS 67-56-1)			
Long-term, Local, Inhalation	50 mg/m <sup>3</sup>	5	Acute toxicity
Short-term, Local, Inhalation	50 mg/m <sup>3</sup>	5	Acute toxicity
Short-term, Systemic, Dermal	8 mg/kg bw/day	5	Acute toxicity
Methylal (CAS 109-87-5)			
Long-term, Systemic, Dermal	18.1 mg/kg bw/day	200	Repeated dose toxicity
Long-term, Systemic, Inhalation	31.5 mg/m <sup>3</sup>	50	Repeated dose toxicity
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)			
Long-term, Systemic, Dermal	319 mg/kg bw/day	2	Repeated dose toxicity
Long-term, Systemic, Inhalation	89 mg/m <sup>3</sup>	2	Repeated dose toxicity
Long-term, Systemic, Oral	26 mg/kg bw/day	2	Repeated dose toxicity

### **Workers**

<b>Components</b>	<b>Value</b>	<b>Assessment factor</b>	<b>Notes</b>
1-ethoxypropan-2-ol; 2PG1EE; 1-ethoxy-2-propanol; propylene glycol monoethyl ether (CAS 1569-02-4)			
Long-term, Systemic, Dermal	74 mg/kg bw/day	29	Repeated dose toxicity
Short-term, Systemic, Inhalation	500 mg/m <sup>3</sup>	3	Repeated dose toxicity
ethanol; ethyl alcohol (CAS 64-17-5)			
Long-term, Systemic, Dermal	343 mg/kg bw/day	24	Repeated dose toxicity
Long-term, Systemic, Inhalation	950 mg/m <sup>3</sup>		
Short-term, Local, Inhalation	1900 mg/m <sup>3</sup>		respiratory tract irritation
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane (CAS EC921-024-6)			
Long-term, Systemic, Dermal	773 mg/kg bw/day		
Long-term, Systemic, Inhalation	2035 mg/m <sup>3</sup>		
Methanol (CAS 67-56-1)			
Long-term, Local, Inhalation	260 mg/m <sup>3</sup>		Acute toxicity
Short-term, Local, Inhalation	260 mg/m <sup>3</sup>		Acute toxicity
Short-term, Systemic, Dermal	40 mg/kg bw/day		Acute toxicity
Methylal (CAS 109-87-5)			
Long-term, Systemic, Dermal	17.9 mg/kg bw/day	100	Repeated dose toxicity
Long-term, Systemic, Inhalation	0.31 mg/m <sup>3</sup>	12.5	Repeated dose toxicity
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)			
Long-term, Systemic, Dermal	888 mg/kg bw/day	1	
Long-term, Systemic, Inhalation	500 mg/m <sup>3</sup>	1	

### **Predicted no effect concentrations (PNECs)**

<b>Components</b>	<b>Value</b>	<b>Assessment factor</b>	<b>Notes</b>
1-ethoxypropan-2-ol; 2PG1EE; 1-ethoxy-2-propanol; propylene glycol monoethyl ether (CAS 1569-02-4)			
Freshwater	10 mg/l	50	
Sediment (freshwater)	37.6 mg/kg		
Soil	1.97 mg/kg		
ethanol; ethyl alcohol (CAS 64-17-5)			
Freshwater	0.96 mg/l	10	
Sediment (marine water)	2.9 mg/kg		
Soil	0.63 mg/kg	1000	
Methanol (CAS 67-56-1)			
Freshwater	20.8 mg/l	10	
Sediment (freshwater)	77 mg/kg		
Soil	100 mg/kg	10	
STP	100 mg/l	10	
Methylal (CAS 109-87-5)			
Freshwater	14.577 mg/l	10	
Secondary poisoning	7.3 mg/kg	30	Oral
Sediment (freshwater)	13.135 mg/kg		

Soil	4.654 mg/kg		
STP	10 g/l	1	
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)			
Freshwater	140.9 mg/l	1	
Secondary poisoning	160 mg/kg	30	Oral
Sediment (freshwater)	552 mg/kg		
Soil	28 mg/kg		

## Exposure guidelines

### UK EH40 WEL: Skin designation

Methanol (CAS 67-56-1) Can be absorbed through the skin.

## 8.2. Exposure controls

### Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

### Individual protection measures, such as personal protective equipment

#### General information

Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

#### Eye/face protection

Wear safety glasses with side shields (or goggles). Use eye protection conforming to EN 166.

#### Skin protection

##### - Hand protection

When handling the product wear chemical-resistant gloves (standard EN 374). The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Full contact: Glove material: nitrile. Use gloves with breakthrough time of 480 minutes. Minimum glove thickness 0.38 mm.

##### - Other

Wear appropriate chemical resistant clothing.

#### Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with organic vapour cartridge and full facepiece. (Filter type AX)

#### Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

### Hygiene measures

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

### Environmental exposure controls

Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Form	Aerosol
Colour	Colourless.
Odour	Characteristic odor.
Melting point/freezing point	-114.1 °C (-173.4 °F) estimated
Boiling point or initial boiling point and boiling range	Not available.
Flammability (solid, gas)	Not available.
<b>Upper/lower flammability or explosive limits</b>	
Flammability limit - lower (%)	1.8 % estimated
Flammability limit - upper (%)	36 % estimated
Flash point	-35.0 °C (-31.0 °F) Closed cup
Auto-ignition temperature	> 200 °C (> 392 °F)
Decomposition temperature	Not available.
pH	Not applicable.
<b>Solubility(ies)</b>	
Solubility (water)	Insoluble in water

Partition coefficient (n-octanol/water)	Not available.
Vapour pressure	5006.1 hPa estimated
Vapour density	Not available.
Relative density	0.77 g/cm <sup>3</sup>
Relative density temperature	20 °C (68 °F)
Particle characteristics	Not available.

## 9.2 Other safety characteristics

Chemical family	Cleaner
Explosive properties	Not explosive.
Heat of combustion (NFPA 30B)	14.22 kJ/g estimated
Oxidising properties	Not oxidising.
VOC	745 g/l

## SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid high temperatures.
10.5. Incompatible materials	Strong oxidising agents. Aluminium. Chlorine. Isocyanates.
10.6. Hazardous decomposition products	Carbon oxides.

## SECTION 11: Toxicological information

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

### Information on likely routes of exposure

Inhalation	May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

**Symptoms** May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

### 11.1. Information on toxicological effects

**Acute toxicity** Classification based on calculation method. Based on available data, the classification criteria are not met.

Product	Species	Test Results
KONTAKT PCC		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	3222 mg/kg
<b>Inhalation</b>		
LC50	Rat	26421 mg/l/4h
<b>Oral</b>		
LD50	Rabbit	4184 mg/kg
<b>Components</b>		
<b>Species</b>		
<b>Test Results</b>		
1-ethoxypropan-2-ol; 2PG1EE; 1-ethoxy-2-propanol; propylene glycol monoethyl ether (CAS 1569-02-4)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 5000 mg/kg
<b>Inhalation</b>		
LC50	Rat	> 10000 mg/l/4h

Components	Species	Test Results
<b>Oral</b> LD50	Rat	> 5000 mg/kg
ethanol; ethyl alcohol (CAS 64-17-5)		
<b>Acute</b>		
<b>Dermal</b> LD50	Rabbit	> 15800 mg/kg
<b>Inhalation</b>		
LC50	Rat	116.8 - 133.8 mg/l, 4 h
<b>Oral</b> LD50	Rat	10470 mg/kg
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane		
<b>Acute</b>		
<b>Dermal</b> LD50	Rat	2920 mg/kg bw/day, 24 h
<b>Inhalation</b>		
LC50	Rat	25200 mg/m <sup>3</sup> , 4 h
<b>Oral</b> LD50	Rat	5840 mg/kg bw/day
Methanol (CAS 67-56-1)		
<b>Acute</b>		
<b>Dermal</b> LD50	Rabbit	15800 mg/kg
<b>Inhalation</b>		
LC50	Rat	87.5 mg/l, 6 Hours
<b>Oral</b> LD50	Rat	5628 mg/kg
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)		
<b>Acute</b>		
<b>Dermal</b> LD50	Rabbit	12800 mg/kg
<b>Inhalation</b>		
LC50	Rat	> 25000 mg/m <sup>3</sup> , 6 h
<b>Oral</b> LD50	Rat	4.7 g/kg
<b>Skin corrosion/irritation</b>	Causes skin irritation.	
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.	
<b>Respiratory sensitisation</b>	Based on available data, the classification criteria are not met.	
<b>Skin sensitisation</b>	Based on available data, the classification criteria are not met.	
<b>Germ cell mutagenicity</b>	Based on available data, the classification criteria are not met.	
<b>Carcinogenicity</b>	Based on available data, the classification criteria are not met.	
<b>Reproductive toxicity</b>	Based on available data, the classification criteria are not met.	
<b>Specific target organ toxicity - single exposure</b>	May cause drowsiness or dizziness.	
<b>Specific target organ toxicity - repeated exposure</b>	Based on available data, the classification criteria are not met.	
<b>Aspiration hazard</b>	Not likely, due to the form of the product.	
<b>Mixture versus substance information</b>	Not available.	
<b>11.2. Information on other hazards</b>		
<b>Endocrine disrupting properties</b>	The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.	
<b>Other information</b>	Not available.	



## SECTION 12: Ecological information

**12.1. Toxicity** Harmful to aquatic life with long lasting effects.

Components		Species	Test Results
1-ethoxypropan-2-ol; 2PG1EE; 1-ethoxy-2-propanol; propylene glycol monoethyl ether (CAS 1569-02-4)			
<b>Aquatic</b>			
<i>Acute</i>			
Crustacea	EC10	Crustacea	4600 mg/l, 16 h
	EC50	Daphnia	21100 - 25900 mg/l, 48 h
Fish	LC50	Fish	4600 - 10000 mg/l, 96 h
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane			
<b>Aquatic</b>			
<i>Acute</i>			
Algae	EC50	Algae	30 - 100 mg/l, 72 h
Crustacea	EC50	Daphnia	3 mg/l, 48 h
Fish	LC50	Fish	11.4 mg/l, 96 h
Methanol (CAS 67-56-1)			
<b>Aquatic</b>			
<i>Acute</i>			
Crustacea	EC50	Water flea (Daphnia magna)	> 10000 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	> 100 mg/l, 96 hours
Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)			
<b>Aquatic</b>			
<i>Acute</i>			
Crustacea	LC50	Brine shrimp (Artemia salina)	> 10000 mg/l, 24 hours
Fish	LC50	Bluegill (Lepomis macrochirus)	> 1400 mg/l, 96 hours

**12.2. Persistence and degradability** No data is available on the degradability of any ingredients in the mixture.

### 12.3. Bioaccumulative potential

#### Partition coefficient

##### n-octanol/water (log Kow)

ethanol; ethyl alcohol	-0.31
Methanol	-0.77
Propan-2-ol; Isopropyl alcohol; Isopropanol	0.05

**Bioconcentration factor (BCF)** Not available.

**12.4. Mobility in soil** No data available.

**12.5. Results of PBT and vPvB assessment** This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.

**12.6. Endocrine disrupting properties** None known

**12.7. Other adverse effects** The product contains volatile organic compounds which have a photochemical ozone creation potential.  
GWP: 0

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Residual waste</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.
<b>EU waste code</b>	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Disposal methods/information</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Special precautions</b>	Dispose in accordance with all applicable regulations.

## SECTION 14: Transport information

### ADR

14.1. UN number	UN1950
14.2. UN proper shipping name	AEROSOLS
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Hazard No. (ADR)	Not available.
Tunnel restriction code	(D)
ADR/RID - Classification code:	5F
14.4. Packing group	Not applicable
14.5. Environmental hazards	No
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

### IATA

14.1. UN number	UN1950
14.2. UN proper shipping name	AEROSOLS
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
14.4. Packing group	Not applicable
14.5. Environmental hazards	No
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

### IMDG

14.1. UN number	UN1950
14.2. UN proper shipping name	AEROSOLS
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
14.4. Packing group	Not applicable
14.5. Environmental hazards	
Marine pollutant	No
EmS	F-D, S-U
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

14.7. Maritime transport in bulk according to IMO instruments Not established.

ADR; IATA; IMDG



## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended**  
Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended**  
Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended**  
Not listed.

**Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended**  
Carbon dioxide (CAS 124-38-9)

**Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA**  
Not listed.

#### Authorisations

**Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended**  
Not listed.

#### Restrictions on use

**Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended**

ethanol; ethyl alcohol (CAS 64-17-5)

Methanol (CAS 67-56-1)

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

**Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.**

Not listed.

#### Other EU regulations

**Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended**

1-ethoxypropan-2-ol; 2PG1EE; 1-ethoxy-2-propanol; propylene glycol monoethyl ether (CAS 1569-02-4)

ethanol; ethyl alcohol (CAS 64-17-5)

Methanol (CAS 67-56-1)

Propan-2-ol; Isopropyl alcohol; Isopropanol (CAS 67-63-0)

#### Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

#### National regulations

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

#### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

#### List of abbreviations

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.

ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).

CAS: Chemical Abstract Service.

Ceiling: Short Term Exposure Limit Ceiling value.

CEN: European Committee for Standardization.

CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.

GWP: Global Warming Potential.

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals).

RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer).

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit.

TLV: Threshold Limit Value.

TWA: Time Weighted Average.

VOC: Volatile organic compounds.

vPvB: Very persistent and very bioaccumulative.

**References****Information on evaluation method leading to the classification of mixture****Full text of any H-statements not written out in full under Sections 2 to 15**

STEL: Short-term Exposure Limit.

Not available.

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H336 May cause drowsiness or dizziness.

H370 Causes damage to organs.

H411 Toxic to aquatic life with long lasting effects.

**Revision information**

None.

**Training information**

Follow training instructions when handling this material.

**Disclaimer**

CRC Industries Europe bvba cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.