



Datasheet

Switching D.C. Power Supply









FEATURES

- Dual Measurement Display
- 0.01 % High Regulation
- Constant Voltage and Constant Current Operation
- High Efficiency
- High Power Density
- Over Voltage Protection
- Remote Output ON/OFF Control





The IPS-Series is single output, 360W, switching DC power supply. OVP protects the IPS-Series and their load from unexpected conditions. High regulation is maintained at 0.01%. Remote sensing adds an extra level of precision by compensating cable losses between loads. Turning the output On/Off from external device is available through Remote control terminals. The IPS-Series is an ideal solution for power-efficient bench-top or portable applications requiring high regulation.

SPECIFICATIONS			
OUTPUT			
	IPS-1820D	IPS-3610D	IPS-606D
Voltage	0 ~ 18V	0 ~ 36V	0 ~ 60V
Current	0 ~ 20A	0 ~ 10A	0 ~ 6A
CONSTANT VOLTAGE OPERATION			
Regulation	Line regulation ≤5mV		
	Load regulation≤5mV		
Ripple & Noise	≤5mVrms, 100mVp-p 20Hz ~ 20MHz		
Recovery Time	≤500μS		
	(50% Load change, Minimum load 0.5A)		
Temp. Coefficient	≤ 100ppm /°C		
Output Range	0 to rating voltage continuously adjustable		
CONSTANT CURRENT OPERATION			
Regulation	Line regulation ≤3mA		
	Load regulation ≤3mA		
Ripple Current	≤3mArms (SPS-606)		
• •	≤5mArms (SPS-3610)		
	≤10mArms (SPS-2415)		
	≤10mArms (SPS-1820)		
	≤30mArms (SPS-1230)		
Output Range	0 to rating current continuously adjustable		
	(HI/LO range switchable)		
METER			
Туре	3 1/2 digit, 0.39" LED display		
Accuracy	\pm (0.5% of rdg + 2digits)		
INSULATION			
Chassis and Terminal	20M $Ω$ or above (DC 500V)		
Chassis and AC Cord	30 M Ω or above (DC 500V)		
POWER SOURCE			
AC 115V/ 230V ±15 %, 50/60Hz			
DIMENSIONS & WEIGHT			
128(W) x 151(H) x 295(D) mm, Approx. 3.2kg			

ORDERING INFORMATION

IPS-1820D 360W Switching D.C. Power SupplyIPS-3610D 360W Switching D.C. Power SupplyIPS-606D 360W Switching D.C. Power Supply

ACCESSORIES:

User manual x 1, Power cord x 1, Test lead GTL-203A x 1

