

FEATURES

- Crosscut probe tip
- Made of phosphor bronze
- Contact resistance of 30 mΩ
- Length of 17.04 mm
- Pitch of 1.9 mm
- Current rating of 3 A
- Spring pressure of 1.47 N(g)

RS PRO Crosscut, Test Probe, 3A

RS Stock No.: 261-5165



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Spring Test Probes



Product Description

These RS PRO spring test probes come in a pack of five and have been rigorously tested for high performance. Ideal for use with test lands, pads and leads, they have spring-loaded tips and crosscut heads. The sharp, penetrating points provide excellent electrical contact. The bodies of the probes are made of phosphor bronze and are gold plated for reliable conductivity. Designed for testing printed circuit boards (PCBs), the probes are used with a receptacle, which you can order separately. By using these two components together, you can remove the probe for cleaning or replacement without having to disconnect any cabling. The receptacles are push-fitted to the mounting plate for an airtight seal that's free of adhesives

General Specifications

Body Material	Phosphor bronze
Probe Tip Type	Crosscut
Body Plating	Gold
Applications	Test lands, pads, leads and holes Penetrates oxides and fluxes as well as contaminated boards

Electrical Specifications

Current Rating	3A
Contact Resistance	30mΩ

Mechanical Specifications

Pitch	1.9mm
Length	17.04mm

Approvals

Compliance/Certifications	EN61340
---------------------------	---------



