

**IE-ANT-CELL-MIMO-DO-SMAM****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Antennas and antenna accessories (coax cables and mounts)**

- State-of-the-art antennas
- Industry proven
- Robust design (up to IP67 protection)
- For outdoor and indoor use
- Latest technology support
- Up to Wi-Fi 6 and Wi-Fi 6E (2.4 GHz, 5 GHz, 6 GHz)
- Up to 5G (NR) support (700 MHz - 3.8 GHz)
- Also support for other technologies (e.g. Bluetooth, GNSS, etc.)
- Appropriate coax cables at different lengths
- Suitable pole and wall mounts

**General ordering data**

Version	Omni-directional antenna, Cellular antenna, Up to 5G (NR), Linear, Vertical, 2x SMA male, IP67, Impedance: 50 Ω
Order No.	<a href="#">2788 120000</a>
Type	IE-ANT-CELL-MIMO-DO-SMAM
GTIN (EAN)	4064675066385
Qty.	1 pc(s).

Creation date March 10, 2023 8:36:06 AM CET

Catalogue status 03.03.2023 / We reserve the right to make technical changes.

## IE-ANT-CELL-MIMO-DO-SMAM

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

## Technical data

### Dimensions and weights

Height	100 mm	Height (inches)	3.937 inch
Net weight	700 g		

### Temperatures

Operating temperature	-40 °C...85 °C	Operating temperature, min.	-40 °C
Operating temperature, max.	85 °C		

### Enclosure material

Colour	black
--------	-------

### Included in delivery

Included in delivery	1 x antenna
----------------------	-------------

### Mechanical and material properties of cable

Cable length	1 m	Min. bending radius, repetitive	25 mm
--------------	-----	---------------------------------	-------

### Technical data

Amount of antenna elements (MIMO)	2	Antenna gain	2.5 dBi
Composite power max.	50 W	Frequency range	690-950 MHz, 1.7-3.8 GHz
Impedance	50 Ω	Polarisation	Linear, Vertical
Standing wave ratio	< 2.0 typical, 3.0 max.	Type of connection	2x SMA male

### Environmental conditions

Operating temperature, max.	85 °C	Operating temperature, min.	-40 °C
-----------------------------	-------	-----------------------------	--------

### Classifications

ETIM 6.0	EC001698	ETIM 7.0	EC001698
ETIM 8.0	EC001698	ECLASS 9.1	19-07-01-90
ECLASS 10.0	19-07-01-07	ECLASS 11.0	19-07-01-07
ECLASS 12.0	19-07-01-07		

### Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
SCIP	e4cad7fc-a55e-4d5c-8f05-417a6385e9b6

### Approvals

ROHS	Conform
------	---------

### Downloads

Engineering Data	<a href="#">CAD data – STEP</a>
Technical Documentation	<a href="#">Radiation Pattern</a>
User Documentation	<a href="#">Hardware Installation Guide</a>
Catalogues	<a href="#">Catalogues in PDF-format</a>

Creation date March 10, 2023 8:36:06 AM CET

Catalogue status 03.03.2023 / We reserve the right to make technical changes.