

Overview

HP Engage Thermal Receipt Printer**Model**

HP Engage Serial Ethernet USB Thermal Receipt Printer (Black Ebony)

299U7AA

HP Engage PUSB Thermal Receipt Printer (Black Ebony)

299V0AA

Introduction

Redefine your perception of retail printing with the HP Engage Thermal Receipt Printer, an eye-catching, compact, cubist printer.

Key Features and Benefits

- Boasts a sleek and ultra-compact, yet functional ID.
- Allows for front- and top- paper-loading.
- Prints quickly, at up to 250 mm per second, to complete transactions more quickly and improve the efficiency of the check-out process.
- Allows for both 58 mm- and 80 mm- sized receipt paper to accommodate customer's preference
- Supports both full and partial cuts.
- Features 8 MB of integrated (flash) memory which allows customers to add their logos, special offers or coupons to receipts and the 203 DPI ensures optimal printing quality.
- Features anti-jam feature which assists in jam recovery, to enable associates to return to their duties more quickly and preventing damage to the platen roller and to the auto-cutter.
- Offers flexibility of connecting to your retail system with an optional Serial, Ethernet, or USB cable (Serial/ Ethernet/ USB model), or PUSB cable (PUSB model) (cables sold separately) and driving up to two optional cash drawers through connections on the printer.
- Features an internal steel frame that can withstand the everyday wear and tear of retail environments and a cutter life of 1 million cuts for maximum durability.
- Usage of ocean-bound plastics, in addition to protecting the oceans and the planet, creates new opportunities for economic advancement and education in local communities.

Overview

- USB Type A pass-through port enables the addition of another USB device, e.g. keyboard or scanner, to the configuration without using a hub

Compatibility

The HP Engage Serial Ethernet USB Thermal Receipt Printer is compatible with all HP point of sale systems.

The HP Engage PUSB Thermal Receipt Printer is compatible with HP point of sale systems with a 24V powered USB (PUSB) port. System connectivity requirements for this printer are as follows:

- The HP Engage Essential requires the Advanced Stand, the Advanced Swivel Stand, or the HP Engage Pro VESA Hub.
- The HP Engage One, HP Engage Go, and HP Engage Go 10 all require the Advanced I/O Connectivity Base.
- The HP Engage One Pro requires the HP Engage One Pro Column Hub, HP Engage One Pro VESA Hub, or the HP Engage One Pro Advanced Fanless Hub.
- The HP Engage Flex Pro and Engage HP Flex Pro-C systems must be ordered with the optional PUSB port.
- The Engage Flex Mini requires the HP Engage One Retail Advanced I/O Connectivity Base.

NOTE: Not all Point of Sale system models are available in all regions. Not all HP Cash Drawer models are available in all regions. This printer does not comply as is with fiscalization requirements that may be required in certain countries.

Service and Support

Three (3) year limited warranty with advance exchange when purchased from HP.

Technical Specifications

General

Supported Character Set/ Resident Code Pages:

290 Japanese/ Katakana
 437 US
 720 Arabic
 737 Greek
 850 Multi-lingual
 852 Slavic
 855 Cyrillic
 857 Turkish
 858 with Eurosymbol
 860 Portuguese
 862 Hebrew
 863 French Canadian
 864 Arabic
 865 Nordic
 866 Cyrillic
 932 Shift JIS
 949 Korean - Hangul
 1125 Ukrainian
 1250 Latin
 1251 Cyrillic
 1252 Windows Latin I
 1253 Greek
 1254 Turkish
 1255 Hebrew
 1256 Arabic
 1257 Baltic
 1258 Vietnamese
 GB18030 Chinese (Simplified & Traditional)
 ISO8859-2 Latin 2
 KU42 Thai (Not available at product launch.)
 Unicode support for resident fonts/ Code Pages

Bar Codes

1D: UPC-A, UPC-E, EAN8, EAN13, Code 39, Code 93, Interleaved 2 of 5 Codabar, Code 128, EAN 128, GS1 Databar
2D: Datamatrix, QR code, PDF 417

Print Method

Direct Thermal

Printing Speed

Up to 250 mm/sec throughput monochrome

Printer Sensor

Paper presence, Low paper, Anti-jam

Resolution

203 DPI

Roll Width

80 mm or 58 mm

Print Width

72 mm with 80 mm paper roll
 52.5 mm with 58 mm paper roll

Flash Memory

8 MB

RAM

8 MB

Knife

Full and partial cuts supported

Receipt-Columns

44/56 (80mm paper roll) or 32/41 (58mm paper roll)

Paper Type

Thermal Paper

Paper Loading

Drop-in

Paper Thickness Range

55 g/m²– 80 g/m² or 0.08 mm – 0.1 mm

Technical Specifications

Roll Core Diameter	25 mm
External Paper Diameter	80 mm max
Cash Drawers	1 connector can drive 2 cash drawers with separately purchased splitter cable (default configuration is connection to 1 cash drawer)

Mechanical

Dimensions (WxDxH)	4.52 in. X 4.52 in. X 5.11 in. (115 mm X 115 mm X 130 mm)
Weight	2.91 lb (1.32 kg)
Color	Ebony Black

Interface/Connection

29907AA Interface	RS232 (9-pin male) USB 2.0 type B USB 2.0 type A Ethernet 10/100 24V cash drawer support with RJ12 interface
299V0AA Interface	PUSB 24V USB 2.0 Type A 24V cash drawer support with RJ12 interface

Power

Power	60W
Operating Voltage	24V
Full Load Current	1.8° Average
Idle Current	25 mA USB type A port will supply up to 500 mA

Temperature Range

Operating	41°F to 95°F (5°C to 35°C) at 5% to 90% humidity 95°F to 122°F (35°C to 50°C) at 5% to 40% humidity Transit range: -40°F to 140°F (-40°C to 60°C) at 5% to 95% humidity
Non-Operating	Storage range: 14°F to 122°F (-10°C to 50°C) at 5% to 90% humidity

Drivers

Windows, OPOS, JPOS

Operating Systems

Windows

- Windows 11 Pro 64-bit
- Windows 10 Pro 64-bit
- Windows 10 IoT Enterprise 2019 LTSC 64-bit (RS5-based)
- Windows 10 IoT Enterprise 2016 LTSB 64-bit (RS1-based)

Linux

- CentOS: 8.4.2105-x86_64
- Fedora: Workstation-Live-x86_64-34-1.2
- OpenSUSE: Leap-15.3-DVD-x86_64
- SUSE Linux: 12-SP5-Server-DVD-x86_64-GM-DVD1, SUSE Linux-15-SP2-Full-x86_64, SUSE Linux 15-SP3-Full-x86_64
- Ubuntu: 18.04.5-desktop-amd64, ubuntu-20.04.2.0-desktop-amd64, ubuntu-mate-20.04.2.0-desktop-amd64

Technical Specifications

Android

- HP Android 8.1 (HP Engage One Prime, HP Engage One, HP Engage Go (12"))
- HP Android 11 and above (HP Engage One Essential, HP Engage One Pro, HP Engage Go 10)

Reliability

Knife Cuts: 1 million cuts

Print Head Life: 150 km

Agency Certifications

Safety:

UL 62368-1

CAN/CSA- C22.2 No. 62368-1

IEC/EN 62368-1 2nd Edition

GB4943.1-2011-China

IS 13252-1 (2010)/A1: 2013/A2: 2015

Radiated Emissions:

FCC 47CFR, Part 15, Class B

ICES-003: 2012, Issue 6, Class B

EN 55032: 2015 Class B

CISPR22 Class B

VCCI: V-3/2015.04 Class B

AS/NZS 3548

Immunity:

EN 55035

EN 61000-4-2 Level 4 (8kV direct, 15kV air discharge)

EN 61000-4-3: Level 3 (10V/m)

EN 61000-4-6 Level 3 (10V rms)

EN 61000-4-4: Level 3 (2kV mains, 1kV data lines)

RoHS, WEEE

Option Kit Contents

HP Engage Thermal Receipt Printer, starter paper roll, paper width guide

Cabling Options

299U7AA: HP Engage Serial Ethernet USB Thermal Receipt Printer

Cables sold separately

HP 6-ft USB cable black (5C2B7AA)

HP 10-ft Serial DB9 to DB9 cable black (5R8R4AA)

Requires 60W power adapter 3A2P5AA# (sold separately)

Alternate configurations:

HP 10-ft power-only PUSB cable black (requires serial cable for data) (5R8R5AA)

OR

HP PUSB Y Cable (BM477AA)

299V0AA HP Engage PUSB Thermal Printer

Cables sold separately

HP 6-ft PUSB cable black (5C2B8AA)

NOTE: For cable-routing configuration information, refer to applicable HP system QuickSpecs.

Summary of Changes

Date of change:	Version History:		Description of change:
December 3, 2021	From v1 to v2	Changed	Interface/connection section
January 6, 2022	From v2 to v3	Changed	Compatibility section and Changed Image page 1
March 9, 2022	From v3 to v4	Changed	Supported Character Set/ Resident Code Pages, Printer Sensor and Full Load Current sections
June 17, 2022	From v4 to v5	Changed	Cabling Options section
August 19, 2022	From v5 to v6	Changed	General section
September 2, 2022	From v6 to v7	Changed	General section
January 11, 2023	From v7 to v8	Changed	General section

© Copyright 2023 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.