# **SIEMENS**

## Data sheet

## 6GK5793-8DK00-0AA0

### Product type designation



#### Antenna ANT793-8DK

ANT793-8DK IWLAN antenna vertically-horizontally polarized with strong directional effect incl. 2x N-female socket; 23 dBi; IP67 (-45-+70°C), 5 GHz; Wi-Fi compliance and Observe national approvals; Mounting on wall or mast; compact instructions as hard copy English/German; scope of delivery: 1x ANT793-8DK, 1x mounting aid for alignment

| Wireless frequencies                                   |                |
|--|----------------|
| Type of mobile network / is supported                  | WLAN           |
| Operating frequency                                    |                |
| <ul> <li>for WLAN in 5 GHz frequency band 1</li> </ul> | 5.15 5.875 GHz |

| Electrical data  |                                 |
|--|---------------------------------|
| Impedance  | 50 Ω                            |
| Polarization   | dual linear vertical-horizontal |
| Radiation characteristic   | directional                     |
| Antenna gain compared to spherical radiator  • of the WLAN antenna / in the 5 GHz frequency band | 23 dB                           |
| Standing wave ratio (VSWR) / maximum   | 1.7                             |
| Radiating angle of the antenna   |                                 |
| <ul> <li>in the 5 GHz frequency band / horizontal</li> </ul>                                     | 9°                              |
| • in the 5 GHz frequency band / vertical   | 9°                              |
| Number of electrical connections / of the antenna  | 2                               |
| Type of electrical connection / of the antenna   | N-Connector                     |
| Design of plug-in connection   | female                          |

| Angle of inclination / downward / maximum         | 0°  |
|---|---|
| Crosstalk attenuation / between the antenna       | 40 dB   |
| connections                                       | 40 db   |
| Front-to-back ratio                               | 35 dB   |
| Mechanical data                                   |   |
| Material  |   |
| • of outer shell                                  | Polycarbonate   |
| Permitted ambient conditions                      |   |
| Ambient temperature                               |   |
| <ul><li>during operation</li></ul>                | -45 +70 °C  |
| during storage                                    | -45 +70 °C  |
| during transport                                  | -45 +70 °C  |
| Protection class IP                               | IP67  |
| Wind load / maximum                               | 389 N; frontal at 220 km/h                                    |
| Design, dimensions and weight                     |   |
| Width   | 371 mm  |
| Height  | 371 mm  |
| Depth   | 40 mm   |
| Net weight  | 2500 g  |
| Mounting type                                     | -   |
| mast mounting                                     | Yes   |
| wall mounting                                     | Yes   |
| • roof mounting                                   | No  |
| directly on the device                            | No  |
| Standards, specifications, approvals              |   |
| Certificate of suitability                        |   |
| RoHS conformity                                   | Yes   |
| Wireless approval                                 | Current national approvals can be found on the Internet under |
|   | www.siemens.com/funkzulassungen                               |
| Further Information / Internet Links              |   |
| Internet-Link                                     |   |
| • to website: Selector SIMATIC NET SELECTION TOOL | http://www.siemens.com/snst                                   |
| • to website: Industrial communication            | http://www.siemens.com/simatic-net                            |
| • to website: Industry Mall                       | https://mall.industry.siemens.com                             |
| to website: Information and Download Center       | http://www.siemens.com/industry/infocenter                    |
| • to website: Image database                      | http://automation.siemens.com/bilddb                          |
| • to website: CAx Download Manager                | http://www.siemens.com/cax                                    |
| • to website: Industry Online Support             | https://support.industry.siemens.com                          |
| last modified:                                    | 10/30/2018  |