SIEMENS

Data sheet

6GK5795-4MA00-0AA3

Product type designation



Antenna ANT795-4MA

ANT795-4MA IWLAN antenna with omnidirectional Characteristic, Radially rotatable, with additional joint, incl. RSMA connector: 3/5 dBi, IP30 (-20-+60°C), 2.4/5 GHz; Wi-Fi compliance and Observe national approvals; Direct mounting on SCALANCE W with RSMA connection system; scope of delivery: 1x ANT795-4MA, compact instructions as hard copy German/English

| Wireless frequencies | |
|--|----------------|
| Type of mobile network / is supported | WLAN |
| Operating frequency | |
| for WLAN in 2.4 GHz frequency band | 2.4 2.4835 GHz |
| for WLAN in 5 GHz frequency band 1 | 5.15 5.35 GHz |
| for WLAN in 5 GHz frequency band 2 | 5.725 5.85 GHz |

| Electrical data | |
|--|-----------------|
| Impedance | 50 Ω |
| Polarization | linear vertical |
| Radiation characteristic | omnidirectional |
| Antenna gain compared to spherical radiator | |
| of the WLAN antenna / in the 2.4 GHz frequency band | 3 dB |
| of the WLAN antenna / in the 5 GHz frequency band | 5 dB |
| Standing wave ratio (VSWR) / maximum | 2 |
| Radiating angle of the antenna | |
| • in the 2.4 GHz frequency band / horizontal | 360° |

| • in the 5 GHz frequency band / horizontal | 360° | |
|---|---|--|
| Number of electrical connections / of the antenna | 1 | |
| Type of electrical connection / of the antenna | R-SMA Connector | |
| Design of plug-in connection | male, variable 0-90° | |
| Angle of inclination / downward / maximum | 0° | |
| , tigio oi momatori, downward, maximam | ŭ | |
| Mechanical data | | |
| Material | | |
| • of outer shell | Polycarbonate | |
| Permitted ambient conditions | | |
| Ambient temperature | | |
| during operation | -20 +65 °C | |
| during storage | -20 +65 °C | |
| during transport | -20 +65 °C | |
| Protection class IP | IP30 | |
| Design dimensions and weight | | |
| Design, dimensions and weight Width | 35 mm | |
| Height | 160 mm | |
| Depth | 13 mm | |
| Net weight | 29 g | |
| Mounting type | 20 9 | |
| mast mounting | No | |
| wall mounting | No | |
| • roof mounting | No | |
| | Yes | |
| directly on the device | 165 | |
| Product properties, functions, components / genera | al | |
| Product feature / silicon-free | Yes | |
| Standards, specifications, approvals | | |
| Certificate of suitability | | |
| RoHS conformity | Yes | |
| Product conformity | UL 94-HB | |
| Wireless approval | Current national approvals can be found on the Internet under | |
| | www.siemens.com/funkzulassungen | |
| Further Information / Internet Links | | |
| Internet-Link | | |
| to website: Selector SIMATIC NET SELECTION TOOL | http://www.siemens.com/snst | |
| to website: Industrial communication | http://www.siemens.com/simatic-net | |
| to website: Industry Mall | https://mall.industry.siemens.com | |
| to website: Information and Download Center | http://www.siemens.com/industry/infocenter | |
| to website: Image database | http://automation.siemens.com/bilddb | |
| - to website. image database | | |

• to website: CAx Download Manager

• to website: Industry Online Support

last modified:

http://www.siemens.com/cax

https://support.industry.siemens.com

10/30/2018