## 5-Port 100BASE-TX Industrial Eco Switch







The 852-111 has 5 ports with each port featuring Auto-negotiation and auto MDI/MDI-X detection. Existing 10Mbps networks can now be upgraded effortlessly to higher speed 100Mbps Fast ETHERNET networks.

The 852-111 5-port density can be used to create multiple segments to alleviate client congestion and provide dedicated bandwidth to each user node. The 852-111 is a cost-effective solution to keep up with the constant demands for emerging IP-based industry communication needs.

The switch can be easily configured and installed and is also ideally suited for small to medium-sized networks.

## Features:

- 5-port 10/100 Mbps Auto-negotiation ETHERNET ports
- Comprehensive front-panel diagnostic LEDs
- Supports Auto-MDI/MDI-X
- Full/half-duplex transfer modes for each port
- Wire speed reception and transmission
- Store-and-forward switching method
- Integrated address Look-Up Engine, supports 2K absolute MAC addresses
- Supports surge protection
- IEEE 802.3x flow control for fullduplex
- Supports DIN 35 rail

Description	Item no.	Pack. unit
5-Port 100BASE-TX Industrial Eco Switch	852-111	1
whilest to design changes WAC	CO Kontakttachnik	

Technical Data		
Ports	5 x 10/100Base-TX (RJ-45)	
Standards	IEEE 802.3 10Base-T;	
	IEEE 802.3u 100Base-TX/FX;	
	IEEE 802.3x Flow Control	
Topology	Star	
LED	each device:	
	1 x Power (PWR), green;	
	each port:	
	1 x Link/Activity (LNK/ACT), green;	
	1 x Speed (100 Mbps), green	
Supply voltage	DC 18 V 30 V	
Energy consumption max.	3 W	
Operating temperature	0 °C +60 °C	
Storage temperature	-20 °C +80 °C	
Relative air humidity (no condensation)	95 %	
Dimensions (mm) W x H x L	23.4 x 73.8 x 109.2	
Mounting	Height from upper-edge of DIN 35 rail	
Weight	350 g	
3	3	