

## FEATURES

- 17.5mm width
- DIN Rail mounting
- Off delay timing function
- Integrated dual voltage
- LED indications for power and relay status
- Wide supply voltage range
- IP20 (terminals), IP40 (enclosure) protection
- Offers a “one stop solution” for your power management system
- The two LED status indicators indicate status at a glance

## RS PRO SPDT Timer Relay - 0.3 s → 30 h, 1 Contacts, OFF Delay, DIN Rail

RS Stock No.: 896-6822



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

## Product Description

RS PRO Off delay time delay relay is a dual voltage, single function timer that is compact in size and suitable for DIN Rail mounting.

## General Specifications

<b>Switch Configuration</b>	SPDT
<b>Mode of Operation</b>	Off Delay
<b>Contact Configuration</b>	CO
<b>Number of Timer Functions</b>	Single
<b>Number of Contacts</b>	1
<b>Time Range</b>	0.3s to 30h
<b>Time Increment</b>	Seconds
<b>Time Delay</b>	100ms
<b>Power on indication / Timing</b>	Green LED
<b>Relay Status</b>	Red LED
<b>Applications</b>	Production, Safety, On-delay timers, Off-delay timers, Interval-on-operate, Flasher, Repeat cycle

## Electrical Specifications

<b>Power Supply</b>	External
<b>Supply Voltage</b>	24V ac/dc, 240V ac
<b>Maximum Voltage</b>	24 V ac/dc, 240 V ac
<b>Current Maximum</b>	5A
<b>Current Minimum</b>	0.1A
<b>Terminal Type</b>	Screw

## Mechanical Specifications

Mounting Type	DIN-Rail
Depth	58.5 mm
Width	90 mm
Length	17.5 mm

## Operation Environment Specifications

Maximum Operating Temperature	55°C
Minimum Operating Temperature	-10°C

## Protection Category

IP Rating	IP20; IP40
-----------	------------

## Approvals

Compliance/Certifications	CE, RoHS
---------------------------	----------



