



X2 pro 7

7" HMI with iX runtime

800 × 480 pixel (16:9)
 TFT-LCD touch screen
 1.5 GB application memory
 Ethernet 1x100 Mbit
 -10°C to +60°C operating temperature
 CE, FCC, KCC, UL approvals
 DNV GL, KR, LR, ABS, CCS, BV, NK marine approvals

Facts

General description

Part number	630000205
Part status	Active
Warranty	2 year

Certifications

General	CE, FCC, KCC, UL 61010-2-201
Marine	KR, LR, ABS, BV, CCS, NK, DNV GL

Mechanical

Mechanical size	204 x 143 x 50mm
Mounting option	Panel Mount, VESA 75 x 75
Number of touches	1million finger touch operations
Touch type	Resistive
Cut-out size	189 x 128mm
Weight	0.8 kg
Housing material	Powder-coated aluminum, Gray

Power

Input voltage 24 V DC (18 to 32 VDC) CE: The power supply must conform with the requirements according to IEC 60950 and IEC 61558-2-4. UL and cUL: The power supply must conform with the requirements for class II power supplies.

Power consumption (max)	14.4W
Input fuse	Internal DC fuse

System

CPU	i.MX6Solo Single Cortex-A9 1.0GHz 512kBL2cache
RAM	512 MB
FLASH	2GB SSD(eMMC), 1.5GB free for application

Display

Size diagonal	7" diagonal
Resolution	800x480 pixels
Backlight	LED Backlight
Backlight life time	20000 hours
Backlight brightness	350 cd/m ²
Backlight dimming	Industrial Dimming
Display type	TFT-LCD with LED backlight

Communication serial

Number of serial ports	1 Port 9pin DSUB
Serial port 1	RS 232 (RTS/CTS)
Serial port 2	RS422/485
Serial port 3	RS485 (only if COM 2 is RS485)

Ethernet communication

Number of Ethernet ports	1
Ethernet port 1	1x10/100 Base-T (shielded RJ45)

Expansion interface

Expansion port	Yes, ciX expansion module
SD card	SD and SDHC
USB	1xUSB 2.0 500mA

Environmental

Operating temperature	-10°C to +60°C
Storage temperature	-20°C to +70°C
Shock	15g, half-sine, 11ms according to IEC60068-2-27
Vibration	1g, according to IEC 60068-2-6, Test Fc
Sealing front	IP65, NEMA 4X/ 12 and UL Type 4X/ 12
Sealing back	IP20
Humidity	5% – 85% non-condensed

 Drivers

ABB - COMLI Master (5.7.2)

ABB - COMLI Slave (4.11.0)

ABB - TotalFlow (5.2.1)

Allen Bradley - ControlLogix Ethernet IP (4.24.1)

Allen Bradley - DF1 (5.8.0)

Allen Bradley - DH485 (4.6.2)

Allen Bradley - MicroLogix Ethernet (5.6.0)

Allen Bradley - SLC5/PLC5 Ethernet (5.4.0)

Altus - Alnet I (5.8.0)

Animatics - SmartMotor (5.2.1)

LS Industrial System - Glofa (5.3.0)

LS Industrial System - Master K (5.4.0)

Matsushita - MEWTOCOL-COM (5.9.2)

Mitsubishi Electric - Alpha2 (5.7.0)

Mitsubishi Electric - A-series (C24) (5.6.0)

Mitsubishi Electric - A-series (CPU) (5.10.0)

Mitsubishi Electric - A-series (E71) (5.4.0)

Mitsubishi Electric - Freqrol FR-A PLC (5.8.2)

Mitsubishi Electric - FX Series ADP/BD (5.10.0)

Mitsubishi Electric - FX Series ENET (5.4.1)

More drivers ▼