

DIGITUS mini GBIC (SFP) Module, 10Gbps, 0.3km, with DDM Feature

DN-81200
EAN 4016032324133



10G SFP+ Module, Multimode, DDM LC Duplex Connector, 850nm, up to 300m

The DIGITUS® mini GBIC (SFP) transceiver modules offer highest quality and reliability. Whether from switch to switch, converter to switch, converter to converter or any else application: The wide product range of DIGITUS® modules makes possible a flexible usage of the fiber technology. The conformity to the MSA (Multi Source Agreement) standard ensures a compatibility to third party manufacturers.

The plug and play fiber connection

- Mini GBIC SFP (Small Form Factor Pluggable) module
- Compatible with the following manufacturers: Allied Telesis, Allnet, CISCO, D-Link, Edimax, Hirschmann, Intellinet, KTI Networks, Level One, Netgear, PLANET, Tenda, TP-Link, TRENDnet, ZyXEL, ZTE
- Supports DDM (Digital Diagnostic Monitoring)
- High quality and excellent reliability
- 10 Gbps Maximum Data Rate
- Compliant to IEEE802.3ae 10 Gigabit Standard
- Class 1 laser product compliant with EN 60825-1
- Easy plug-and-play installation

- MSA (Multi Source Agreement) compliant
- Hot pluggable
- Connector: 1x LC Duplex
- Wavelength: 850nm
- Transmission Power: Minimum -5 dBm, Maximum -1 dBm
- Empfangssensitivität: Minimum -11,5 dBm
- For a distance of up to 0.3km
- Safe fast-locking mechanism
- 3.3V power supply
- Operating temperature: 0 °C ~ 70 °C
- Broadcasting Mode: Unidirectional
- Manufacturer compatibility: Cisco
- Connector: LC
- DDM Support: yes
- Distance (km): 0.3
- Mode: Multimode
- Ethernet speed: 10 Gigabit
- Wavelength: 850 nm

Package contents

- SFP module

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm ³
Packaging Unit Carton	20	0.80	41.00	26.00	16.00	17,056.00
Packaging Unit Inside	1	0.04	3.00	11.50	9.00	310.50
Packaging Unit Single	1	0.04	3.00	11.50	9.00	310.50
Net single without Packaging	1	0.03	5.50	1.20	0.80	0.00

More images:



SFP Modules							
Part Number	Data Rate	Speed	Distance	Connector	Wavelength	Operating Temperature	Industrial Model
Fast Ethernet							
DS-4940	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4941	4000000000	10 Gbps	200m	LC Duplex	1550nm	0 to 70 °C	✓
DS-4942	4000000000	10 Gbps	200m	LC Duplex	1550nm	0 to 70 °C	✓
DS-4943	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4944	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4945	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4946	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4947	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4948	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4949	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4950	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4951	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4952	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4953	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4954	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4955	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4956	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4957	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4958	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4959	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4960	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4961	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4962	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4963	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4964	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4965	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4966	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4967	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4968	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4969	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4970	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4971	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4972	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4973	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4974	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4975	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4976	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4977	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4978	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4979	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4980	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4981	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4982	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4983	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4984	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4985	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4986	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4987	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4988	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4989	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4990	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4991	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4992	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4993	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4994	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4995	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4996	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4997	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4998	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-4999	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓
DS-5000	4000000000	10 Gbps	200m	LC Duplex	1310nm	0 to 70 °C	✓