80 Series V **Digital Multimeters**

New

True RMS











Accessories and Ordering Information

Included Accessories

TL75 test leads, AC72 alligator clips, holster, 80BK temperature probe (87V only), 9 V battery (installed), CD-ROM (user's manual and technical notes) and operator's guide.

Ordering Information

Fluke 83V Multimeter

Fluke 87V True RMS Multimeter

Fluke 87V/E Industrial Electrician Combo Kit

Performance and accuracy for maximum industrial productivity

The new Fluke 80 Series V has improved measurement functions, troubleshooting features, resolution and accuracy to solve more problems on motor drives, in plant automation, power distribution, and electro-mechanical equipment. The 80 Series V operates very similar to the classic 80 Series, but with more problemsolving power, safety, convenience and impact protection.

The new Fluke 87V has a unique function for accurate voltage and frequency measurements on adjustable speed motor drives and other electrically noisy equipment.

A built-in thermometer conveniently allows you to take temperature readings without having to carry a separate instrument.

Electrical safety

All inputs are protected to EN61010-1 (2nd edition) CAT III, 1000 V and CAT IV 600V. They can withstand impulses in excess of 8.000 V and reduce risks related to surges and spikes.

Features

non lir	MS voltage and current for accurate measurements near signals
Bandw	ridth (voltage/current)
Digital	display counts (default/selectable)
	able filter for accurate voltage and frequency rements on motor drives
Large of	display with analog bargraph and 2 level bright wh ght
Auto a	nd manual ranging for maximum flexibility
Built-ir	n thermometer lets you carry one less tool
Peak c	apture to record transients as fast as 250 μs
	re mode to remove test lead resistance from low ohr rements
	ax–Average recording with Min/Max Alert to capture ons automatically
Touch !	Hold® to capture stable readings avoiding noisy signa
Audible	e continuity, diode test and duty cycle
Input A	llert
	c" design with new removable holster with built in ad and probe storage
Improv	ed selectable sleep mode for long battery life
	attery and fuse exchange without opening the ste case

87V
•
20 kHz
20000 / 6000
•
•
•
•
•
•
•
•
•
•
•
•
•

Specifications (Check the Fluke Web for detailed specifications)

Functions	Maximum Range	
11.11 200	1000 11	
Voltage DC	1000 V	
Voltage AC	1000 V	
Current DC	10 A **	
Current AC	10 A **	
Resistance	50 MΩ	
Conductance	60 nS	
Capacitance	9999 µГ	
Frequency	> 200 kHz	
Temperature	-200 to 1090 °C	
80BK temperature probe	- 40 to 260 °C	

8	3 V	87V*		
Max. resolution	Accuracy	Max. resolution	Accuracy	
0.1 mV	±(0.1+1%)	10 μV	±(0.05%+1)	
0.1 mV	±(0.5%+2)	10 μV	±(0.7%+2)	
0.1 μΑ	±(0.4%+2)	0.01 µA	±(0.2%+2)	
0.1 μΑ	±(1.2%+2)	0.01 µA	±(1.0%+2)	
0.1 Ω	±(0.4%+1)	0.01 Ω	±(0.2%+1)	
0.01 nS	±(1.0%+10)	0.001 nS	±(1.0%+10)	
0.01 nF	±(1.0%+2)	0.01 nF	±(1.0%+2)	
0.01 Hz	±(0.005%+1)	0.01 Hz	±(0.005%+1)	
	-	0.1 °C	1.0%	
	-	-	2.2 °C or 2%	

Accuracies are best accuracies for each function.

* 87V accuracy is stated for 6.000 counts and resolution for 20.000 counts

** 20 A up to 30 seconds

Battery Life: Over 400 hours typical (alkaline).

Size (without holster) (HxWxD): 186 mm x 86 mm x 32 mm

Weight: 0.36 kg Lifetime Warranty

Fluke 87V: The ideal multimeter for measuring adjustable speed drives



The Fluke 87V DMM overcomes measurement problems caused by the adjustable speed motor drives. These drives adjust the speed of alternating current motors using pulse width modulation that generates a very 'noisy' or 'chopped' signal.

Ordinary DMMs may indicate voltage higher than the voltage actually supplied to the motor. Measurements may not agree with drive controls, and frequency measurements may be erratic. Bottom line: the technician can't tell whether a problem lies with the controls, drive or motor.

With the press of a button, the Fluke 87V DMM solves these problems. The 87V blocks unwanted high frequencies generated by inverters and provides accurate and stable measurements of motor drives: AC voltage, frequency (to calculate motor rpm) and AC current (using the current clamp accessory).

Fluke 87V/E Industrial Electrician Combo Kit

This new combo kit is based on the Fluke 87V and includes special accessories to make industrial troubleshooting even more productive. Save over 60% compared with the individual purchase price of all the accessories.



- Fluke 87V True RMS Multimeter
- TL224 SureGrip™ Silicone Test Lead Set
- TP238 SureGrip[™] Slim Reach Test Probe Set (insulated tips with 4 mm of exposed metal)
- AC220 SureGrip[™] Alligator Clip Set
- Magnetic Hanger
- 80BK Temperature Probe
- C800 Hard Case

Recommended accessories with the new Fluke 80 Series V

80i400 AC Current Clamp (400 A)



TPAK ToolPak, Meter Hanging Kit



C90 Soft Case



C800 Hard Case



L210 Probe light and probe extenter



Fluke. Keeping your world up and running.

Fluke Corporation

P.O. Box 9090 Everett, WA USA 98206

Fluke Europe B.V. P.O. Box 1186 5602 BD Eindhoven

The Netherlands

For more information call:

For more minormation can:
In the U.S.A. (800) 443-5853
or Fax (425) 446 -5116
In Europe/M-East/Africa +31 (0)40 2 675 200
or Fax +31 (0)40 2 675 222
In Canada (905) 890-7600
or Fax (905) 890-666
From other countries +1 (425) 446 -5500
or Fax +1 (425) 446 -5116

Visit us on the world wide web at:

http://www.fluke.com

Fluke (UK) Ltd.

52 Hurricane Way
Norwich
Norfolk
NR6 6JB
United Kingdom
Tel.: 0207 942 0700
Fax: 0207 942 0701
E-mail: industrial@uk.fluke.nl

Visit us on the world wide web at:

http://www.fluke.co.uk

© Copyright 2004 Fluke Corporation. All rights reserved. Printed in the Netherlands 04/04 Data subject to alteration without notice. Pub_ID: 10718-eng