

GENERAL PRODUCT SPECIFICATION

Item No. DTA25

Date	16-6-2017	Replaces	03-16-06	No. Pages	1

Product Description:

StyleDrum Top CoverItem Size (each)56 cm diameter

Color Gray

Composition Polypropylene >98%, Surfactant < 1.0%, color pigment < 0.1 %

Structure A nonwoven mat of randomly oriented Micro-fibers [2-10 micron diameters]

Technology Meltblown, 3-ply

Absorbency Universal (**Hydrophilic** + Oleophilic)

Bonding Ultrasonic "Oil Drop Dimple" staggered pattern + Mechanical entanglement

Intended Application Drum Top Cover of Low -Lint Chemical Resistant Sorbent for Water, Oil, or

Solvent Base Liquids

Absorbency Capacity 26 l per bale (saturated; medium viscosity-12.5x)

Packaging Description:

Package configuration	Case	Pkg. Weight	2.7 kg (1.8kg)
Items per Package	25-Pads/Case	Pkg. Dimensions	57cm x 57cm x
			11cm (H)
Container type	Carton		

Physical Properties;

<u>Parameter</u>	SPC Test Method	<u>Units</u>	Nominal Nominal	(+/-)Tolerance
Basis Weight	SPCTM-002A	G/M2	290	30
Caliper	SPCTM-003A	mm	4.5	0.4
Absorbency** (med.	SPCTM-004B	gL/gS	12.5	2
Oil)				
Tensile Strength	SPCTM-007	daN	7.3	0.7
Color	Visual		Gray	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped. ** The "Absorbency" Spec and "SPCTM004" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes Product will be free of foreign material contamination, rips, holes, and tears. **Labeling** Each package to be clearly labeled with Company Name, Address, Item No.,

Date, and/or Package Code (Bar Code).

Certification Make no changes in basic process or composition without notifying customer.

Claims for non-conformance of goods must be made within 60-days of delivery.

WH Brady NV – Division SPC International, Atealaan 71, I.Z. Klein Gent, B-2200 Herentals, Belgium Tel +32(0)14 321855 Fax +32(0)14 320440 www.bradyeurope.com