

GENERAL PRODUCT SPECIFICATION

Item No.	HAZ412					
Date	16-6-2017	Replaces	6-1-16	No. Pages	1	

Product Description:

I Touuce Description.			
Style	SOC		
Item Size (each)	7.6 cm dia x 122 cm long		
Color	Green with green logo printing		
Composition	Polypropylene >98%, Surfactant < 1.0%, color pigment < 1.0%		
Structure	Sorbent fill: Micro-fibrous meltblown polypropylene (2-10 micron diameters)		
	Outer covering: Spunbond polypropylene nonwoven (15-30 micron dia. fiber)		
Technology	Meltblown + Spunbond + Sealed or Enclosed Ends		
Absorbency	Hydrophilic + Oleophilic		
Intended Application	ended Application Chemical Resistant "Universal" Sorbent Sock for Spills of Water Base, Oil		
	Base, or Solvent Base Liquids		
Absorbency Capacity	43 l per case (saturated; medium viscosity- 9x)		

Packaging Description:

Package configuration	Case	Pkg. Weight	4.7 kg (4.1kg)
Items per Package	12 SOCS/Case	Pkg. Dimensions (approx.)	57cm x 32cm x 38cm (H)
Container type	Carton		

Physical Properties;

Parameter	SPC Test Method	Units	Nominal	(+/-)Tolerance
SOC Weight	Gravimetric	kg	0.36	0.09
Absorbency (med. oil)	SPCTM-012B	gL/gS	9	8-min.
Color	Visual		Green	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped. ** The "Absorbency" Spec and "SPCTM012" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.
Labeling	Each package to be clearly labeled with Company Name, Address, Item No.,
	Date, and/or Package Code (Bar Code).
Certification	Make no changes in basic process or composition without notifying customer.
	Claims for non-conformance of goods must be made within 60-days of delivery.