HP Engage One 10.1" Display

Overview

HP Engage One 10.1" Display



### Models

HP Engage One 10.1" Display (Black)	1XD80AA
HP Engage One 10.1" Display (White)	3FH66AA
HP Engage One 10.1" Display w/ VESA (Black)	3F1W9AA

### Introduction

Share dynamic videos and content with customers on a display that gets attention in any room with the HP Engage One 10.1" Non-Touch Display for the HP Engage One AiO System. It has durable, cleanable, edge-to-edge glass, an adjustable stand for



#### **Overview**

optimal counter placement, and simple USB-C<sup>™</sup> connectivity.

#### **Key Features and Benefits**

- Maintain a streamlined counter space with single-cable connectivity through USB-C™.
- Place the durable, 10.1" diagonal LCD display in a range of high-traffic areas. The edge-to-edge, bezel-less glass
  is easy to clean, helps provide protection from dust, and retains the modern aesthetic of the HP Engage One AiO
  System.
- Use the included low-profile, adjustable tilt stand to find the perfect spot in your retail and hospitality environment to grab customer attention.
- Rest easy that your IT investment is supported by a three-year standard limited warranty.

#### Compatibility

The HP Engage One 10.1" Display is compatible with the HP Engage One AiO System.

**NOTE:** Not all HP Retail system models are available in all regions. **NOTE:** Also compatible with some other HP products via USB-C flex port USB-C DP Alt-mode technology\*

\*Compatibility to all products not tested

#### Service and Support

Three (3) year limited warranty with advance exchange.



### **Technical Specifications**

General	Display Size (diagonal)	10.1 in
	Display Type	IPS w/LED backlight
	Color	Ebony Black or Ceramic White
	Input Connectors	USB-C (Upstream) ( 5 Gbits/sec, 5V/3A, Alt mode )
	Native Resolution	1280 x 800 @ 60 Hz
	Aspect Ratio	16:10
	Brightness	500 cd/m²
	Static Contrast Ratio - Typical	800:1
	Dynamic Contrast Ratio (DCR)	N/A
	Pixel Pitch	0.1695 (H) x 0.1695 mm(V)
	Pixels Per Inch (PPI)	149
	Backlight Lamp Life	50k minimum
	Anti-Glare Panel	Yes
	BrightView Panel	Νο
	Response Time	25ms
	Color Gamut	45%
	Color Support	Up to up to 16.1 million colors
	Horizontal Viewing Angle (typical CR>10)	170°
	Vertical Viewing Angle (typical CR>10)	170°



#### **Technical Specifications**

3D Vertical Viewing Angle	N/A	

	Panel Active Area	216.96 (H) x 135.60 (V)
	Preset Graphic Modes/Supported Resolutions	640 x 480 @ 60Hz 800 x 600 @ 60 Hz 1024 x 768 @ 60 Hz 1280 x 720 @ 60 Hz 1280 x 800 @ 60 Hz
	Maximum Resolution	1280 x 800@ 60 Hz
	<b>Recommended Resolution</b>	1280 x 800 @ 60 Hz
	Vertical Scan Range	50 - 60 Hz
	Horizontal Scan Range	30~54 kHz
	Default Color Temperature	Neutral (6500)
	Maximum Pixel Clock Speed	110 MHz
	Exterior Color of Monitor Bezel and Stand	Black in bezel and hinge
	Plug & Play	Yes
	Tilt	15 to + 90 degrees
	Swivel	No
	Pivot	No
	Security Lock Ready	No
	Height Adjustment	No
	Height Adjustment Range (Min-Max)	N/A
	Detachable Base	No
	Warranty	3/3/0 : WW
	Webcam	N/A
	Speakers Output Power	N/A
	VESA Mounting	Yes
On Screen Display (OSD)	On Screen Display User Controls	Brightness, Contrast, Color Control, Input Control, Image Control, Power Control. Menu Control. Management. Language. Information. Exit

(hp)

### **Technical Specifications**

	User Programmable Modes	Yes, 10
	Monitor Control Buttons or Switches	Menu/OK, Minus button/Down/Information, Plus button/Up/Color Control, Exit/Back/Brightness, Power
	Audio Controls	N/A
	Languages	10 (English, Spanish, German, French, Italian, Netherlands, Portuguese, Japanese, T-Chinese and S-Chinese)
Power	Power Supply	No
	Power Source	USB-C 5V/3A,15W
	Power Consumption - Maximum	15w
	Energy Saving/Standby Mode	0.5w
	Power Consumption - Tvoical	12w
	Power Cable Length	N/A
	Operational Mode at 100 VAC	18.01KHw/year
	Operational Mode at 115 VAC	18.01KHw/year
	Operational Mode at 230 VAC	18.01KHw/year
Operating Conditions	Operating Temperature	5° - 35°C 41° - 95°F
	Non-operating Temperature	- 20° - 60°C 29° - 140°F
	Operating Humidity	20% - 80% (non-condensing)
	Non-operating Humidity	5% - 95%
	Operating Altitude	0 - 5,000 m (16,400 ft.)
	Non-operating Altitude	0 - 12.192 m (40,000 ft.)
Dimensions	Unpacked without stand	9.69 x 6.07 x 1.38 in 24.62 x 17.02 x 3.52cm
	Packed	12.05 x 4.33 x 9.13 in 30.6 x 11 x 23.2cm
	Display Head Dimensions (Unpacked without stand)	9.69 x 6.07 x 0.59 in 24.62 x 17.02 x 1.5cm
	Base Area Footprint	4.72 x 7.09in 119.98 x 179.97mm



### **Technical Specifications**

Environmental	Bezel Measurements Weight (unpacked with stand) Weight (packed) Mercury-free display	top 0.063 in, side 0.063 in, bottom 0.063in top 1.6 mm. side 1.6mm. bottom 1.6 mm 3.3lb (1.49kg) 4.26lb(single pack) 1.93kg(single pack) 23.51lb(bulk pack) 10.67kg(bulk pack) Yes, Mercury-free LED backlighting
	backlighting Arsenic-Free Display Glass	Yes
	Alsellic-rice Display Glass	
	Low Halogen	Yes
	Agency Approvals and Certifications	WW application CE/CB/MSIP/Mexico CoC/ICES/ISO 9241-307/ EAC/cTUVus/CCC/TUV-Barunt /VCCI/FCC/RCM/BSMI/WEEE/Ukraine/Morocco
	Microsoft WHQL Certification	Win-7, 8, 10
	China Energy Label	NA
	TCO Certified Edge	Νο
	TCO Certified	No
	SmartWay Transport Partnership	Yes (NA SKU)
	Contains Recycled Plastics in Back Cover	85%
	Contains Recycled Plastics in Base/Stand	85%
	Contains Recycled Plastics in Other Parts	85% (Deco, Middle Frame)
	Recyclable Plastics	All
	Recyclable Packaging	All
Software	N/A	
What's in the Box	Captive USB TYPE C cable (1.8m) and stand (15 to +90°)	
Options	The Engage One POS VESA Plate – 2WY48AA	
Country of Origin	China	

### Summary of Changes

Date of change:	Version History:		Description of change:
October 19, 2017	From v1 to v2	Added	Options section added referring ElitePOS POS VESA Plate
January 14, 2018	From v2 to v3	Added	New part number and model colors
August 1, 2018	From v3 to v4	Changed	Product name
October 1, 2019	From v4 to v5	Removed	ENERGY STAR and EPEAT certifications
January 22, 2020	From v5 to v6	Changed	Format page 6
October 13, 2021	From v6 to v7	Changed	Environmental section
February 14, 2022	From v7 to v8	Changed	Models section

© Copyright 2022 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. Microsoft and Windows are trademarks of the Microsoft group of companies.

