

Description

- 1.6 x 1.2mm crystal oscillator in a ceramic package with a seam sealed metal lid, hermetically sealed.
- Model IQXO-986
- Model Issue number 1

Frequency Parameters

- Frequency 32.7680kHz
- Frequency Stability ± 50.00 ppm
- Operating Temperature Range -40.00 to 85.00°C
- Frequency Stability: Includes Frequency Tolerance @ 25°C , operating temperature range, supply voltage variation and load variation.

Electrical Parameters

- Supply Voltage $1.8\text{V} \pm 10\%$
- Current Draw (typ) 0.024mA

Output Details

- Output Compatibility CMOS
- Drive Capability 15pF max
- Rise and Fall Time 200.0ns max
- Duty Cycle 45/55
- Output Voltage Levels:
 Output Low (VoL): $10\%V_s$ max
 Output High (VoH): $90\%V_s$ min
- Start Up Time: 10ms max

Output Control

- Stand-by Mode:
 Logic '0' ($30\%V_s$ max) to pad 1 disables the oscillator output, the output goes to a high impedance state.
 Logic '1' ($70\%V_s$ min) or no connection to pad 1 enables oscillator output.
- Stand-by Current: $1.4\mu\text{A}$ typical $3\mu\text{A}$ max

Environmental Parameters


- Storage Temperature Range: -40 to 85°C

Compliance


- RoHS Status (2011/65/EU) Compliant
- REACH Status Compliant
- MSL Rating (JDEC-STD-033): Not Applicable

Packaging Details


- Pack Style: Cutt In tape, cut from a reel
- Pack Size: 100
- Alternative packing option available




Outline (mm)



- Pad Connections
- Standby Operation
 - GND
 - Output
 - +Vs



Test Circuit




Sales Office Contact Details:

UK: +44 (0)1460 270200
 Germany: 0800 1808 443

France: 0800 901 383
 USA: +1.760.318.2824

Email: info@iqdfrequencyproducts.com
 Web: www.iqdfrequencyproducts.com

Wave Form



Sales Office Contact Details:

UK: +44 (0)1460 270200
Germany: 0800 1808 443

France: 0800 901 383
USA: +1.760.318.2824

Email: info@iqdfrequencyproducts.com
Web: www.iqdfrequencyproducts.com