



NX-PF0730

NX I/O power feed unit, 5-24 V DC input, 8 terminals, 10A, screwless push-in connector, 12mm wide

Specifications

I/O system	NX I/O Bus
Type of module	Power feed
I/O connection type	Push-in
Number of I/O connectors	1
Detachable I/O connector	✓
Suitable for safety functions	✗
SIL according to IEC 61508	None
Number of IOV (V+) terminals	4
Number of IOG (V-) terminals	4
Number of FG terminals	0
Degree of protection (IP)	IP20
Product Height (unpacked)	104.5 mm
Product Width (unpacked)	12 mm
Product Depth (unpacked)	80.1 mm
Product Weight (unpacked)	65 g

Accessories



NX-AUX02

Terminal block coding pins for 10x NX I/O units (terminal block: 30 pins, unit: 30 pins)



NX-TBA082

Replacement screwless push-in connector with 8 wiring terminals (marked A+B)

Downloads

CAD Library



IO-Link Series Brochure

EN PDF 6.26 MB



Machine Safety Solution Brochure

EN PDF 2.86 MB



NX-HAD Brochure

EN PDF 1.22 MB



NX-TC Brochure

EN PDF 3.83 MB




NX-series System Unit - NX-PD/PF/PC/TBX Datasheet

EN PDF 3.25 MB



NX-series System Units Users Manual

EN PDF 5.59 MB



Omron GX-JC0x-x EtherCAT Junction Box EtherCAT ESI file

EN ZIP 3.36 KB



PLC I/O Interface Wiring System Selection Connection Guide

EN PDF 1.54 MB



Sysmac Catalogue

EN PDF 43.5 MB



Sysmac: A Fully Integrated Platform Brochure

EN PDF 10.2 MB

