



Kvaser PCICanx HS/HS

EAN: 73-30130-00331-6

Kvaser PCICanx HS/HS is a dual channel, high speed CAN (controller area network) interface that can be used in both regular PCI and PCI-X slots. Galvanically isolated CAN bus drivers protect the hardware, whilst the on board micro controller ensures high throughput.

Major Features

- Quick and easy plug-and-play installation.
- High-speed ISO 11898 compliant driver circuits.
- Compliant with PCI 2.3.
- The board fits in 3.3V PCI-X, and 3.3V and 5V PCI busses.
- Compatible with our PCICan boards.
- I/O mapped for quick reaction times.
- SJA1000 CAN Controllers from Philips, with 64-byte receive FIFO.
- Supports CAN 2.0 A and 2.0 B (active).
- Pin assignment according to CiA-DS102.

- 16 MHz CAN oscillator frequency.
- Galvanic isolation between the CAN-controller and the CAN-driver.
- Interfaces the CAN bus with DSUB CAN connectors.
- Wide temperature range, -40°C - +85°C.

Warranty

- 2-Year Warranty. See our General Conditions and Policies for details.

Support

- Free Technical Support on all products available by contacting support@kvaser.com.

Software

- Documentation, software and drivers can be downloaded for free at www.kvaser.com/downloads.
- Kvaser CANLIB SDK is a free resource that includes everything you need to develop software for the Kvaser CAN interfaces. Includes full documentation and many program samples, written in C, C++, C#, Delphi, and Visual Basic.
- All Kvaser CAN interface boards share a common software API. Programs written for one interface type will run without modifications on the other interface types!
- J2534 Application Programming Interface available.
- RP1210A Application Programming Interface available.
- On-line documentation in Windows HTML-Help and Adobe Acrobat format.

TECHNICAL DATA - KVASER PCICANX HS/HS

TIMESTAMP RESOLUTION (US)	N/A
SOUND	No
ON-BOARD TX BUFFER	N/A
MSGRATE RX MAX	14000
MINIMUM BITRATE (KBPS)	N/A
ERROR FRAME DETECTION	Yes
PC INTERFACE	PCI
RUGGED	No
EMBEDDED SCRIPT	No
ERROR FRAME GENERATION	No
CONNECTOR	DSUB 9
WIDTH (MM)	120
MSGRATE TX MAX	18000
CASING MATERIAL	-
MAXIMUM BITRATE (KBPS)	1000
ERROR COUNTERS READING	Yes
HEIGHT (MM)	20
LENGTH (MM)	95
OPERATING SYSTEM	Win Vista,Win 8,Win 7,Win XP
CLOCK SYNC	No
NETWORK CHANNEL(S)	2 x CAN HS
# OF CAN CHANNELS	2
API, LICENCED	None
ON-BOARD BUFFER	No
IP CLASS	N/A
ON-BOARD RX BUFFER	N/A
CERTIFICATIONS	CE,RoHS



Kvaser PClcanx HS/HS

SILENT MODE	Yes
OPERATING TEMPERATURE RANGE (C)	-40.00 to 85.00
STATUS	Active
GALVANIC ISOLATION	Yes
API, FREE	Kvaser API, J2534, RP 1210
WEIGHT (G)	100.0

The information herein is subject to change without notice