

Data Sheet FUJITSU PLAN EP X710-T2L OCPV3 2x 10GBase-T Ethernet Network Adapter

X710-T2L OCPV3 2x 10GBase-T

Ethernet cards enable data exchange between all the devices connected in a local network (LAN). A networked IT infrastructure that functions well is of great significance when managing and controlling critical business processes in a company. The wide range of complex information transported across the network relies on fast and reliable data processing by the network cards.

PLAN EP X710-T2L OCPV3 2x 10GBase-T Ethernet Network Adapter

10 GbE for the Broad Market. Intel(R) Ethernet 700 Series Network Adapters are the foundation for server connectivity, providing broad ineroperability, critical performance optimizations, and increased agility for Telecommunications, Cloud, and Enterprise IT network solutions. The Intel Ethernet Network AdapterX710-T2L OCPV3 is the newest innovation in Intel's leadership to drive 10 GbE into the broad server market, and the easiest and most versatile 10GbE interface that can deployed anywhere in the data center.

Simplify the Transition to 10GbE. With 10GBASE-T, migration to 10GbE is dramatically simplified with backward compatibility for your existing GbE network infrastructure. Install a Fujitsu PLAN EP X710-T2L OCPV3 Dual Port OCPV3 adapter into a server and the autonegotiation between 1 GbE and 10 GbE provides the necessary backwards compatibility that most customers require for a smooth transition and easy migration to 10 GbE.

10GBASE-T uses the copper twisted-pair cables that are very familiar to IT professionals today.



Features & Benefits

Main Features

Scalable performance

Intel® Ethernet Network Adapter X710-T2L OCPV3

Flexible technology options Enhanced Low-Profile Solution

Efficient networking RJ45 Connections over CAT 6A Cabling

Connectivity

Enhanced Network Virtualization Overlays

Benefits

- Standard CAT 6a cabling with four RJ45 connectors for maximum system density
- Enables higher bandwidth and throughput from standard and lowprofile PCIe slots and servers
- Ensures compatibility with cable length up to 100 meters. Backwards compatible with existing 100BASE-T and 1000BASE-T networks
- Network Virtualization offloads including VXLAN, GENEVE, NVGRE, MLPS, and VLAN-GPE with Network Service Headers (NSH) preserve application performance for overlay networks, and the network traffic can be distributed across CPU cores, increasing network throughput

Technical details

Technical details

Controller Silicon	Intel [®] Ethernet C	ontroller XL710				
Controller type	Ethernet Ctrl.					
Connector type	RJ45					
Released drivers list link	http://support.ts	.fujitsu.com/Downlo	oad/Index.asp			
Number of ports	2					
Number of Connectors	2					
Number of external ports	2					
Data transfer rate(s)	100 MBit/s; 1 Gbi	t/s; 10 Gbit/s				
Auto Negotiation support	Yes					
Bus interface	OCPV3					
Bus transfer rate	8GT/s					
Network protocol and standards						
compatibility	IEEE 802.1q VLAN IEEE 802.3ad LAC IEEE 802.3 2005 f		t			
HW Virtualization	PCI-SIG SR-IOV w	ith up to 128 virtua	l functions per device			
Interrupt Levels	INTA; MSI; MSI-X					
WoL	No					
Virtualization	PCI-SIG SR-IOV u	p to 128 per device.	ies) up to 256 maximum VMI The physical configuration o ing) provides traffic load bala	f each port is divided into		
Teaming	Provided by the	OS				
Remote boot support	iSCSI ; PXE	·				
iSCSI support	Yes					
Offloading		Tx/Rx IP, SCTP, TCP and UDP checksum offloading (IPv4 & IPv6). Benefit: lower processor usage. Checksum and segmentation capability to extend to new standard packet type				
Data transfer rate up to	10 Gbit/s					
Order code	Product Name		Height of bracket	Number of ports	Related product	
PYBLA342U	PLAN EP X710-T2	L OCPV3	OCPV3	2	PRIMERGY Server	
PY-LA342U	PLAN EP X710-T2	2L OCPV3	OCPV3	2	PRIMERGY Server	
PY-LA342U Supported Interface Modules / C		2L OCPV3	OCPV3	2	PRIMERGY Server	
		7 nt to TSB-155) Cat 6A or CAT 7	OCPV3	2	PRIMERGY Server	
Supported Interface Modules / C	ables 10GBASE-T - 100m on Cat 6A or Cat - 55m on Cat 6 (complia 1000BASE-T - 100m on Cat 5e, Cat 6, 100BASE-T	7 nt to TSB-155) Cat 6A or CAT 7	OCPV3	2	PRIMERGY Server	
Supported Interface Modules / C Description optional cable	ables 10GBASE-T - 100m on Cat 6A or Cat - 55m on Cat 6 (complia 1000BASE-T - 100m on Cat 5e, Cat 6, 100BASE-T	7 nt to TSB-155) Cat 6A or CAT 7	OCPV3	2	PRIMERGY Server	
Supported Interface Modules / C Description optional cable Environment	ables 10GBASE-T - 100m on Cat 6A or Cat - 55m on Cat 6 (complia 1000BASE-T - 100m on Cat 5e, Cat 6, 100BASE-T	7 nt to TSB-155) Cat 6A or CAT 7	OCPV3	2	PRIMERGY Server	
Supported Interface Modules / C Description optional cable Environment Compliance	ables 10GBASE-T - 100m on Cat 6A or Cat - 55m on Cat 6 (complia 1000BASE-T - 100m on Cat 5e, Cat 6, 100BASE-T - 100m on Cat 5e, Cat 6,	7 nt to TSB-155) Cat 6A or CAT 7	OCPV3	2	PRIMERGY Server	
Supported Interface Modules / C Description optional cable Environment Compliance Europe	ables 10GBASE-T - 100m on Cat 6A or Cat - 55m on Cat 6 (complia 1000BASE-T - 100m on Cat 5e, Cat 6, 100BASE-T - 100m on Cat 5e, Cat 6, CE FCC Class B	7 nt to TSB-155) Cat 6A or CAT 7	OCPV3	2	PRIMERGY Server	
Supported Interface Modules / C Description optional cable Environment Compliance Europe USA/Canada	ables 10GBASE-T - 100m on Cat 6A or Cat - 55m on Cat 6 (complia 1000BASE-T - 100m on Cat 5e, Cat 6, 100BASE-T - 100m on Cat 5e, Cat 6, CE FCC Class B UL	7 nt to TSB-155) Cat 6A or CAT 7	OCPV3	2	PRIMERGY Server	
Supported Interface Modules / C Description optional cable Environment Compliance Europe USA/Canada Japan	ables 10GBASE-T - 100m on Cat 6A or Cat - 55m on Cat 6 (complia 1000BASE-T - 100m on Cat 5e, Cat 6, 100BASE-T - 100m on Cat 5e, Cat 6, CE FCC Class B UL VCCI	7 nt to TSB-155) Cat 6A or CAT 7	OCPV3	2	PRIMERGY Server	
Supported Interface Modules / C Description optional cable Environment Compliance Europe USA/Canada Japan South Korea	ables 10GBASE-T - 100m on Cat 6A or Cat - 55m on Cat 6 (complia 1000BASE-T - 100m on Cat 5e, Cat 6, 100BASE-T - 100m on Cat 5e, Cat 6, CE FCC Class B UL VCCI KCC	7 nt to TSB-155) Cat 6A or CAT 7	OCPV3	2	PRIMERGY Server	
Supported Interface Modules / C Description optional cable Environment Compliance Europe USA/Canada Japan South Korea Australia/New Zealand	ables 10GBASE-T - 100m on Cat 6A or Cat - 55m on Cat 6 (complia 1000BASE-T - 100m on Cat 5e, Cat 6, 100BASE-T - 100m on Cat 5e, Cat 6, CE CE FCC Class B UL VCCI KCC C-Tick BSMI	7 nt to TSB-155) Cat 6A or CAT 7		2	PRIMERGY Server	

More information

Fujitsu products, solutions & services

In addition to Fujitsu with PLAN EP X710-T2L OCPV3 2x 10GBase-T Ethernet Network Adapter, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products www.fujitsu.com/global/products/ computing/

Software www.fujitsu.com/software/

More information

Learn more about Fujitsu Server PLAN EP X710-T2L OCPV3 2x 10GBase-T Ethernet Network Adapter, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website. www.fujitsu.com/primergy

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at http://www. fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/ emeia/resources/navigation/terms-of-use. html

Copyright 2022 Fujitsu LIMITED

Disclaimer

Please note that the data sheet reflects the technical specification with the maximum selection of components for the named system and not the detailed scope of delivery. The scope of delivery is defined by the selection of components at the time of ordering. The product was developed for normal business use.

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact Fujitsu Limited Website: www.fujitsu.com/primergy 2022-12-02 WW-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html Copyright 2022 Fujitsu LIMITED