# Mini Circuit Breaker





## **Electrical Features**

Rated Current	40 A
Poles	2 P
Rated Voltage Ue	230/400 V~
Insulation Voltage Ui	500 V
Rated Frequency	50/60 Hz
Rated Breaking Capacity	10
Energy Limiting Class	3
Rated Impluse withstand Voltage	4,000 V
Dielectric Test Voltage	2 kV
Pollution Degree	2
Thermo-magnetic Release Characteristic	С


## **Mechanical Features**

Electrical Life	8,000 Cycles
Mechanical Life	20,000 Cycles
Contact Position Indicator	Yes
Protection Degree	IP20
Reference Temperature for setting of thermal element	30 °C
Ambient Temperature	-5 °C ~ 40 °C
Storage Temperature	-25 °C ~ 70 °C

## Installation

Cable/Pin-type busbar/U-type busbar			
25 mm <sup>2</sup> 18-3 AWG			
25 mm <sup>2</sup> 18-3 AWG			
2.5 Nm 22 In-Ibs			
On DIN rail EN60715(35mm)			
Power supply in both directions			
	25 mm² 18-3 AWG 25 mm² 18-3 AWG 2.5 Nm 22 In-Ibs On DIN rail EN60715(35mm)		

#### **Characteristics Curves**



Thermal Tripping			Magnetic Tripping			
As per	No	Tripping	Time	Hold	Trip	Time
IEC60898	tripping	current	Limits	current	current	Limits
	current	I <sub>2</sub>	t	$I_4$	$I_5$	t
B Curve	1.13×I <sub>N</sub>		≥1h	3×I <sub>N</sub>		≥0.1s
		1.45×I <sub>N</sub>	<1h		$5 \times I_N$	<0.1s
C Curve	$1.13\times I_{\scriptscriptstyle N}$		≥1h	$5\times I_N$		≥0.1s
		1.45×I <sub>N</sub>	<1h		$10{\times}I_{\scriptscriptstyle N}$	<0.1s
D Curve	1.13×I <sub>N</sub>		≥1h	10×I,		≥0.1s
D Curve	1.13 V IN			TO VIN		
		1.45×I <sub>N</sub>	<1h		$20\times I_N$	<0.1s

## **Tripping Characteristics**

Based on the Tripping Characteristics, MCB are available in "B", "C" and "D" curve to suit different types of applications.

"B" Curve for protection of electrical circuits with equipment that does not cause surge current (lighting and distribution circuits) Short circuit release is set to (3-5)In.

"C" Curve for protection of electrical circuits with equipment that cause surge current (inductive loads and motor circuits) Short circuit release is set to (5-10)In.

"D" Curve for protection of electrical circuits with cause high inrush current ,typically 12-15 times the thermal rated

## **Circuit Diagram**



## Overall and Installation Dimension(mm)

