## Silencer



## Features


- Used for suppressing the nise of air release, applied to exhausted port of machine
- Excellent noise suppresion effect
- Several options of material(brass, stainless steel, plastic)
- Compact design is suitable for installing in confined psace



## **Specification**

| Material              | Brass           |  |  |  |  |
|-----------------------|-----------------|--|--|--|--|
| Thread                | BSPP            |  |  |  |  |
| Working Medium        | Air             |  |  |  |  |
| Working Pressure      | 0-0.9 MPa       |  |  |  |  |
| Proof Pressure        | 1.32 Mpa        |  |  |  |  |
| Proof Vacuum Pressure | -100Kpa(10Torr) |  |  |  |  |
| Working Temperature   | 0 °C ~ 60 °C    |  |  |  |  |

## **Product Range & Drawing**



| Part Number   | R     | A (mm) | B (mm) | L (mm) | H (mm) | øD (mm) |
|---------------|-------|--------|--------|--------|--------|---------|
| RND 425-00327 | G 1/8 | 6      | 4      | 24.5   | 12     | 7       |
| RND 425-00328 | G 1/4 | 7      | 4      | 26     | 15     | 9.5     |
| RND 425-00329 | G 3/8 | 9      | 5      | 36.5   | 18     | 11.5    |
| RND 425-00330 | G 1/2 | 11     | 5      | 40     | 21     | 14      |