

Hexalobular Socket Head Cap Screws



Features

- No burrs and sharp edges
- Screw material: A2 stainless steel
- Passivated finish
- Material and finish comply with 211/65/EU (RoHS)
- Meets ISO 14580 standard

Length	L
3	2.8~3.2
4	3.76~4.24
5	4.76~5.24
6	5.76~6.24
8	7.71~8.29
10	9.71~10.29
12	11.65~12.35
14	13.65~14.35
16	15.65~16.35
20	19.58~20.42
25	24.58~25.42
30	29.58~30.42
35	34.5~35.5
40	39.5~40.5
45	44.5~45.5
50	49.5~50.5
55	54.05~55.95
60	59.05~60.95

Thread (6g)	L	PART NO.
M2x0.4	4	RND 610-00519
	6	RND 610-00520
	8	RND 610-00521
M2.5x0.45	4	RND 610-00524
	6	RND 610-00525
	8	RND 610-00526
	10	RND 610-00522
	12	RND 610-00523
M3x0.5	6	RND 610-00535
	8	RND 610-00537
	10	RND 610-00527
	12	RND 610-00529
	16	RND 610-00531
M4x0.7	20	RND 610-00533
	8	RND 610-00549
	10	RND 610-00539
	16	RND 610-00542
	20	RND 610-00544
	25	RND 610-00546
30	RND 610-00548	

u	=)	= =	o k	o k) u
U	=)	= =	u		
U			u		
U			u		
U			u		
U			u		
U			u		
U			u		
U			u		
U			u		

u	O	h° kuV\
U		kV)
		kV)
		kV)
		kV)
		kV)
U		kV)
		kV)
		kV)
		kV)
		kV)

