

ROLINE Converter RS-232 to RS-422/485, with Isolation, for DIN Rail, Professional

Product No.	12.02.1006
Manufacturer	ROLINE
Manufacturer No.	12.02.1006
EAN (single piece)	7611990196753



- Converter for the connection of a RS-422 or RS-485 device to a PC's RS-232 port
- RS-232 and RS-422/485 can have a different baud rate
- Auto direction flow control on RS-485
- Addressable and non-addressable mode configurable
- Data transfer rate of up to 115.2 Kbit/s
- Surge protection on signal pins of RS-422/485
- Isolation Voltage: 3000 VDC (optical)
- Signals: TXD, RXD, RTS, CTS for RS-232
- Baud rate (transfer rate) can be different to all devices
- Built-in microprocessor
- Dual Watch dog/Watchdog timer function
- All communication setups stored in EEPROM
- Power and data flow indicator for troubleshooting
- Connectors: RS-232: DB9 Female, RS-422/485: 7-pin terminal block
- Easy setup and installation
- For DIN rail mounting
- Supports: Windows 2000/Server 2003/XP/Server 2008/XP/Vista/7, Mac OS X
- Contents: Converter, manual

Technical specifications

Manufacturer	ROLINE
--------------	--------

Product group	Adapters, Terminators, Converters
Product type	Serial interface converter
Colour	black
Scope of delivery	Converter, manual
Side 1 connection (PC)	RS232
Side 2 connection (Peripherals)	Terminal block
Side 1 Connector Type	D-Sub 9-pin (DB-9)
Side 1 Connector Gender	Female
Side 2 Connector Type	Terminal block
Side 2 Connector Gender	Female
Conversion direction	RS422/RS485- RS232
Area of application	External