

Data Sheet FUJITSU PRAID EP540i

RAID Controller SAS 12Gbit/s 4GB cache based on Broadcom MegaRAID® for internal storage devices

The RAID concept (Redundant Array of Independent Disks) refers to several independent hard disks which form a large logical drive when switched together.

Redundancy information is calculated from several data blocks (except for RAID 0) and saved distributed to the individual hard disks. Your operating system no longer accesses the individual hard disks, but the array.

The actual objective of the RAID concept is to increase availability and prevent downtimes in the event of a hard disk failure. However, the theoretical security of the RAID concept is only as good as the RAID controller used. Benefit from the Fujitsu RAID controllers where technology, experience and practical implementation all ensure the security that your company needs in the event of an emergency.

PRAID EP540i

The Fujitsu RAID Controller PRAID EP540i with 4GB cache and16x12Gbit/s SAS ports improves performance for storage intensive workloads such as databases and sets new speed and data security standards for internal storage drives. The new PRAID EP540i supports up to 16 SAS/SATA drives, up to 4 NVMe PCle drives or a mixture of SAS/SATA and NVMe drives. NVMe is an interface with lower overhead, lower latency and drastically increased bandwidth and IOP's. The RAID stack is based on the Broadcom MegaRAID® and offers high data throughput, a comprehensive fault tolerance

function and user-friendly management options. Moreover, the Controller management is integrated seamlessly into the Fujitsu server management concept. All controller functions are supported by the Fujitsu ServerView RAID Manager. The PRAID EP540i is designed for 3, 6 and 12Gbit/s SAS as well as for 3 and 6Gbit/s SATA drives. Regardless of the drive speed, it delivers significant performance improvements in both read and write applications. The controller firmware also supports FastPath® without an additional license. FastPath® accelerates the use of SSD only configurations. The RAID controller supports all of the important RAID levels including RAID 6 and 60. The optional flash battery backup (FBU) combined with the already included TFM module ensures the integrity of the data stored in the cache on the RAID controller in case of a power outage. In this event, the data will be copied to a non-volatile flash memory (TFM). The TFM module is bundled with the controller, the FBU is optional.

Important information for later upgrade from or downgrade to std. SAS controller: Specific cable sets per system can be required as L-Part, please refer to Paper Configurator, order tool or controller and system documentation. Orders ex factory are configured with appropriate cables.



Main Features

- 16 lines of 12Gbit/s SAS ports PCI Express® 3.0
- SAS3516 12Gbit/s RAID-on-Chip
- 16 lines of 8 Gbit/s PCle Gen 3 for up to 4x x4 NVMe drives
- 4GB 2133MHz DDR4 cache memory
- Optional Flash Backup Unit (FBU), TFM is included
- SafeStore for Disk Encryption is included free of charge
- User Management Options
- RAID Advanced Software Options. FastPath® is supported free of charge by controller firmware. CacheCade® is no longer supported.

Benefits

- Connect up to 64 HDDs and SSDs
- RAID levels 0, 1, 5 and 6 for more data security, RAID spans 10, 50 and 60 for more data security
- NVMe is an interface with lower overhead, lower latency and drastically increased bandwidth and IOPS
- Improves performance for storage intensive workloads (such as databases) and for certain load profiles like random access to databases (especially for SSD drives)
- Ensures the integrity in case of power outage, Long-term, secure store of data and better serviceability compared to BBU
- Safe data encryption and data safety for hard disks in case of removal.
- Seamless merging of the RAID management into system management

Technical details

Controller Silicon		RoC (RAID on Chip) SAS3516					
Controller type		RAID 5/6 Ctrl.					
Operating system pre-installed		Information to released operating systems can be found in the server datasheets. Details can be found in the released drivers list on the support portal.					
Released drivers list link		http://support.ts.fujitsu.com/Download/Index.asp					
Number of ports		16 ports int.					
Connector internal		4x SFF8643 (Mini-SAS HD)					
Data transfer rate up to		12 Gbit/s; 8 Gbit/s					
Bus type		PCIe 3.0					
Bus width		x8					
RAID Management		ServerView RAID Manager StorCLI (command-line interface) BIOS Configuration Utility					
		- Fast initialization - Load Balancing - Configurable strip - Fast initialisation - Check consistence - Patrol read for me - Up to 64 logical c - S.M.A.R.T support - Global and dedica - Automatic rebu - Enclosure affini - Enclosure manag - SES (inband) - SGPIO (outbance	expansion (OCE) Migration (RLM) I loss of system power during for quick array setup The size up to 1MB I for quick array setup I for background data integed in the scanning and repairing frives per controller to the stated Hot Spare with Revertical to the scanning and the setup for the scanning and sepairing frives per controller to the scanning and sepairing frives per controller to the scanning and sepairing frives per controller to the scanning are with Revertical for the scanning frive scanni		M)		
RAID level		0, 1, 10, 5, 50, 6, 60					
RAID cache backup unit		Optional FBU					
RAID controller notes		based on SAS3516					
Interface technology		SAS/SATA/PCIe-NV/	Ле				
Order code	Product Nam	e	Height of bracket	RAID controller cache s	size Number of C	Connector	
S26361-F4042-E204	PRAID EP540i	LP	Low Profile (LP)	4 GB	4		
S26361-F4042-E214	PRAID EP540i	(for RX2530 M4)	Low Profile (LP)	4 GB	4		
S26361-F4042-E4	PRAID EP540i	FH	Full Height (FH)	4 GB	4		
S26361-F4042-L504	PRAID EP540i	FH/LP	Full Height / Low Profile	4 GB	4		
Order code	Product Nam	ne		Notes			
S26361-F4042-E125	RAID Ctrl FBL	J option for PRAID I	EP5xx with 25cm cable	installed - Super-capacitor inc	l. cable		
S26361-F4042-E155	RAID Ctrl FBL	J option for PRAID I	EP5xx with 55cm cable	installed - Super-capacitor inc	l. cable		
S26361-F4042-E183	RAID Ctrl FBL	J option for PRAID I	EP5xx with 83cm cable	installed - Super-capacitor incl. cable			
S26361-F4042-E156		J option for PRAID I	EP5xx with 55cm cable for	installed - Super-capacitor inc	l. cable		
	CX25x0 M4						

RX4770 M4

Order code	Product Name	Notes		
S26361-F4042-L110	RAID Ctrl FBU option for PRAID EP5xx with 25,55,83cm cable	installed - Super-capacitor incl. cable		
S26361-F4042-L112	RAID Ctrl FBU option for PRAID EP5xx with 55cm cable for CX25x0 M4	installed - Super-capacitor incl. cable		
S26361-F4042-L113	RAID Ctrl FBU option for PRAID EP5xx with 70cm cable for RX4770	installed - Super-capacitor incl. cable		
Compliance				
Compliance notes	According to the corresponding system			
Compliance link	https://sp.ts.fujitsu.com/sites/certificates			

More information

Fujitsu products, solutions & services

In addition to Fujitsu with PRAID EP540i, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu PRAID EP540i, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

http://www.fujitsu.com/primergy

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/qlobal/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html

Copyright 2019 FUJITSU LIMITED

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Limited Website: www.fujitsu.com/primergy 2019-11-01 WW-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html
Copyright 2019 FUJITSU LIMITED