



### Heat shrinkable tubing 3:1 in a kit

#### ShrinkKit 321 Universal Basic - 177 pcs. - coloured


With ShrinkKit 321 HellermannTyton has set a new standard in heat shrink tubing: ShrinkKit tubings cover many applications with their ideal shrink ratio of 3:1.

#### Features and benefits

- Compact and handy kit
- Black and coloured tubing
- Available in a wide size range of 3 mm to 18.0 mm
- 177 precut pieces in five sizes



ShrinkKit 321 Universal Basic - 177 pcs 3:1 heat shrink assortment.



Heat Shrinkable Tubing 3:1

<b>MATERIAL</b>	Polyolefin, cross-linked (PO-X)
<b>Shrink Ratio</b>	3:1
<b>Operating Temperature</b>	-55 °C to +135 °C
<b>Min. Shrink Temperature</b>	+90 °C
<b>Longitudinal Change After Shrinkage</b>	+5%/-10% max.
<b>Dielectric Strength</b>	20 kV/mm
<b>Flammability</b>	self-extinguishing
<b>Insulation Class</b>	B (VDE 0530)



COMP.	Supplied Ø D min.	Recov. Ø d max.	Length (L)	Wall (WT)	Colour	Content	Tools	Article-No.
1	12.0	4.0	35.0	0.70	Black (BK)	12 pcs.	30	380-03005
2	6.0	2.0	80.0	0.70	Blue (BU)	5 pcs.		
	6.0	2.0	80.0	0.70	Red (RD)	5 pcs.		
	6.0	2.0	80.0	0.70	White (WH)	5 pcs.		
	12.0	4.0	80.0	0.70	Black (BK)	2 pcs.		
	12.0	4.0	80.0	0.70	Blue (BU)	2 pcs.		
	12.0	4.0	80.0	0.70	Red (RD)	2 pcs.		
3	6.0	2.0	35.0	0.70	Blue (BU)	10 pcs.		
	6.0	2.0	35.0	0.70	Red (RD)	10 pcs.		
	6.0	2.0	35.0	0.70	White (WH)	10 pcs.		
4	9.0	3.0	35.0	0.70	Green-Yellow (GNYE)	15 pcs.		
5	9.0	3.0	35.0	0.70	Black (BK)	20 pcs.		
6	3.0	1.0	35.0	0.55	Black (BK)	10 pcs.		
	3.0	1.0	35.0	0.55	Blue (BU)	10 pcs.		
	3.0	1.0	35.0	0.55	Red (RD)	10 pcs.		
	3.0	1.0	35.0	0.55	White (WH)	10 pcs.		
7	6.0	2.0	35.0	0.70	Black (BK)	20 pcs.		
	6.0	2.0	35.0	0.70	Green-Yellow (GNYE)	10 pcs.		
8	18.0	6.0	160.0	0.80	Black (BK)	3 pcs.		
	18.0	6.0	160.0	0.80	Green-Yellow (GNYE)	3 pcs.		
	18.0	6.0	160.0	0.80	White (WH)	3 pcs.		

All dimensions in mm. Subject to technical changes. Minimum Order Quantity (MOQ) may differ from package content.

Recommended Tools	
	30 H6100
	566

For more information on toolings please refer to the Application Tooling chapter.



Add items to your watchlist!

[www.HT.click/49-217](http://www.HT.click/49-217)

