

#### M.2 SSD Enclosure for M.2 SATA SSDs - USB 3.0 (5Gbps) with UASP

#### **Product ID: SM2NGFFMBU33**



The SM2NGFFMBU33 external USB 3.0 to M.2 (NGFF) enclosure turns your SATA M.2 solid state drive into a portable, high speed USB 3.0 drive.

Get higher external performance by using an M.2 SSD in place of a platter drive, harnessing the full potential of your USB 3.0 computer system. The enclosure supports UASP, enabling you to achieve transfer speeds up to 70% faster than traditional USB 3.0 when used with a UASP-enabled host computer.

This slim, pocket-sized SSD enclosure has been specifically engineered for mobility. The enclosure features a lightweight yet durable design, which fits easily into your pocket or laptop bag. For further convenience, the enclosure is powered entirely using the USB host bus and requires no external power adapter.

Durable aluminum construction helps to ensure your drive won't be damaged while you're on the move. Plus, to maximize heat dissipation the enclosure features specially engineered ventilation holes which help maintain a cooler operating environment for optimal performance and a longer life span for your drive.<img alt="maximize heat dissipation with ventilation holes specially engineered to increase air flow" src="http://sgcdn.startech.com/005329/media/ProductPhotos/SM2NGFFMBU33content1.jpg">

For wide compatibility with all of the common M.2 solid state drives, the enclosure can mount multiple drive heights including: 2242, 2260, and 2280.

The M.2 enclosure is backed by a StarTech.com 2-year warranty and free lifetime technical support.

UASP is supported in Windows 8, Mac OSX (10.8 or above), and Linux. In testing UASP performs with a 70% faster read speed and 40% faster write speed over traditional USB 3.0 at peak performance.

<img alt="UASP Speed Diagram"
src="http://sgcdn.startech.com/005329/media/products/gallery\_large/UASPSPEEDGraph.jpg" width="400" />

At the same peak in testing UASP also shows an 80% reduction in required processor resources.

<img alt="UASP Speed Diagram" src="http://sgcdn.startech.com/005329/media/products/gallery\_large/UASPCPUGraph.jpg" width="400" />



Testing results were obtained using an Intel Ivy Bridge system, a UASP enabled StarTech.com Enclosure, and a SATA III solid state drive.

## Certifications, Reports and Compatibility

### **Applications**

- Re-purpose an M.2 SATA SSD as a USB 3.0 external drive
- Carry with your laptop for a highly portable external storage solution
- Transfer files to or from your external drive faster, by using a high performance SATA M.2 SSD as your external drive

#### **Features**

- Boost external performance by leveraging the speed of your SATA M.2 SSD in a UASP-supported USB 3.0 enclosure
- · Maximize portability with a small footprint, lightweight design and USB-powered performance
- Broad compatibility with support for the most common SATA M.2 SSDs (30mm, 42mm, 60mm, 80mm)
- Not compatible with M.2 NVMe or AHCI PCI-Express SSDs
- Compatible with USB 3.0/2.0/1.1 (5 Gbps / 480 Mbps / 1.5 Mbps)
- Compatible with SATA revision I/II/III (1.5 / 3.0 / 6.0 Gbps)
- Aluminum housing with ventilation holes for added heat dissipation

Prominence			

Warranty	2 Years
----------	---------

Description CDW 75 - 1st StarTech.com M.2 SSD Enclosure for M.2 SATA SSD - USB 3.0

5Gbps - Aluminum Line

Hardware

Interface **USB 3.0** 

Bus Type **USB 3.0** 

Number of Drives

Compatible Drive Types M.2 (SATA, B-Key, NGFF)



M.2 SATA (NGFF, B+M-Key)

Drive Installation Fixed

Chipset ID ASMedia - ASM1153E

**Performance** 

Maximum Data Transfer

Rate

5 Gbps

Type and Rate

USB 3.0 - 5 Gbit/s

**UASP Support** 

Yes

**TRIM Support** 

No

4Kn Support

Yes

Type and Rate

SATA III (6 Gbps)

**General Specifications** 

Not compatible with M.2 NVMe or AHCI PCI-Express SSDs

Connector(s)

**Drive Connectors** 

M.2 (SATA, B-Key, NGFF)

**Host Connectors** 

USB 3.0 Micro-B (10 pin, SuperSpeed)

**Software** 

OS Compatibility

OS independent; No software or drivers required

Special Notes / Requirements

Note

Windows 7 and earlier Windows versions do not support TRIM with

USB to SATA devices.

**Power** 

**Power Source** 

**USB-Powered** 

**Environmental** 

Operating Temperature

0C to 50C (32F to 122F)

Storage Temperature

-10C to 85C (14F to 185F)

Humidity

5% to 95% RH

**Physical** 



#### Characteristics

Color Black

Material Aluminum

Product Length 3.9 in [100 mm]

Product Width 1.4 in [35 mm]

Product Height 0.6 in [15 mm]

Weight of Product 1.8 oz [50 g]

## Packaging Information

Package Length 5.2 in [13.1 cm]

Package Width 6.4 in [16.3 cm]

Package Height 1.2 in [31 mm]

Shipping (Package)

Weight

4.4 oz [125 g]

# What's in the Box

Included in Package USB 3.0 to M.2 NGFF SSD Enclosure

USB 3.0 Cable

SSD screw kit

Mini screw driver

Instruction manual

<sup>\*</sup>Product appearance and specifications are subject to change without notice.