



Downlight Covers - For Residential Buildings

SpotClip-I

SpotClip-I is a unique product that has been developed for mounting down lights in dry mortarless construction and acoustic construction applications.

The innovative, 4-leg ceiling brace has a number of outstanding features and is suitable for use in both panelling and plasterboard.

SpotClip-I consists of non-flammable, fibreglass reinforced polyamide and offers a number of thermal and mechanical benefits and can even be installed retrospectively.

As a result, it opens up a variety of possibilities for applications in both old and new buildings.

SpotClip-I can be used in ceiling cavities with diameters of 62 to 90 mm.

SpotClip-I ensures that a safe distance is kept between the down light, insulation foil and roof insulation.

It reduces the risk of damage being caused to any insulation material as a result of overheating and heat accumulation and may also have a positive effect on the life time of the lamp.




www.HellermannTyton.co.uk/SpotClip-I-cat22



SpotClip-II ensures reliability and safety of lighting installations.



Optimization of 4 fastening feet.



SpotClip-I

MATERIAL	Polyamide 6.6, glass-fibre reinforced (PA66GF15%)
Operating Temperature	-20 °C to +120 °C
Flammability	UL94 V0 at 1.5mm thickness, Glow Wire Test (GWT) 960 °C



TYPE	Hole Ø (FH) min.	Hole Ø (FH) max.	Height (H)	Height (H2)	Colour	Pack Cont.	Article-No.
SpotClip-I	62.0	90.0	82.0	70.0	Black (BK)	10 pcs.	148-00076

All dimensions in mm. Subject to technical changes.
Minimum Order Quantity (MOQ) may differ from package content.





Downlight Covers - For Residential Buildings

SpotClip-I

Features and benefits

- Mount down lights in dry, mortarless construction and acoustic construction
- Innovative, 4-leg ceiling spacer
- Suitable for both panelling and plasterboard
- Non-flammable, fibreglass reinforced polyamide
- Thermal and mechanical benefits
- Can be installed after construction, useful for both old and new buildings
- Use in ceiling cavities 62-90 mm in diameter
- Keeps safe distance between down light, insulation foil and roof insulation
- Reduces risk of damage to insulation from overheating, heat accumulation
- Improves life span and reliability of lamps
- Tested according to EN 60598-1, EN 60598-2-2, and NF C 15100



Cable retainers on the heat protection top hold the supply cable in place.



Additional retaining spikes prevent movement during mounting.



Bearing wings ensure that the spacer locates securely on the plasterboard.



1. Use the delivered tool to install SpotClip in the fixing hole as easy as possible.



2. Push the spikes into the plasterboard to prevent shifting and disconnect the tool.



3. Start the installation of the downlight in a safe way.