## T4111001051-000 ACTIVE



#### M12 Connector

TE Internal #: T4111001051-000

Standard Circular Connectors, Wire-to-Wire, 5 Position, Sealable,

Wire & Cable, Signal, PBT, A Polarization Code, Polyamide 66

GF25, M12 Connector

View on TE.com >




Connectors > Circular Connectors > Standard Circular Connectors > M12 Field Installable Unshielded











Connector System: Wire-to-Wire

Number of Positions: 5

Sealable: Yes

Connector & Contact Terminates To: Wire & Cable

Contact Current Rating (Max): 4A

All M12 Field Installable Unshielded (102)

#### **Features**

### **Product Type Features**

Product TypeConnectorAccessory ColorBlackAssembly TypeElectrical ConnectorConnector SystemWire-to-WireSealableYesConnector & Contact Terminates ToWire & Cable	Prewired	No
Assembly Type  Connector System  Wire-to-Wire  Sealable  Yes  Connector & Contact Terminates To  Wire & Cable	Product Type	Connector
Connector System  Sealable  Yes  Connector & Contact Terminates To  Wire-to-Wire  Yes  Wire & Cable	Accessory Color	Black
Sealable  Connector & Contact Terminates To  Wire & Cable	Assembly Type	Electrical Connector
Connector & Contact Terminates To Wire & Cable	Connector System	Wire-to-Wire
	Sealable	Yes
	Connector & Contact Terminates To	Wire & Cable
Circular Connector Type Plug	Circular Connector Type	Plug
Shell Type Plastic	Shell Type	Plastic

Factory Installed Backshell	No
Keying	A
Number of Positions	5



Number of Power Positions	0
Number of Signal Positions	5
Contacts Preloaded	Yes
Electrical Characteristics	
Operating Voltage	60 VAC
Body Features	
Peripheral Seal Material	Silicone
Environmental Protection	IP67
O-Ring Material	Silicone
Environmental Protection Type	Elastomer Sealed
Shell Base Material	PBT
Circular Connector Insulation Material Type	Polyamide 66 GF25
Contact Features	
Contact Current Rating (Max)	4 A
Reverse Gender	No
Circular Connector Contact Type	Pin
Mechanical Attachment	
Mating Retention Type	Threaded Coupling
Mating Alignment	With
Polarization Code	A
Mating Alignment Type	Keyed
Housing Features	
Circular Connector Shell Size	20
Dimensions	
Wire Size	.82 – .2 mm²
Usage Conditions	
IP Dust Sealing Level	6
IP Water Sealing Level	IP67
Operating Temperature Range	-40 - 85 °C[-40 - 185 °F]
Operation/Application	
Durability Rating	100 Cycles



Circuit Application	Signal
Shielded	No
Industry Standards	
UL Flammability Rating	UL 94HB
Packaging Features	
Packaging Quantity	1
Other	
Field Serviceable	Yes

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2022 (223) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Pb (3.7% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**

Standard Circular Connectors, Wire-to-Wire, 5 Position, Sealable, Wire & Cable, Signal, PBT, A Polarization Code, Polyamide 66 GF25, M12 Connector









## Also in the Series | M12 Connector






M8/M12 Cable Assemblies(230)

## Customers Also Bought







TE Part #E12502-000

SP050100WE10









TE Part #4-1768399-0 SP100375WE2.5-SP

## **Documents**

**Product Drawings** 

M12, MALE, STRAIGHT, A CODE, 5P, PG7, GOLD

English

**CAD Files** 

3D PDF

3D



**Customer View Model** 

ENG\_CVM\_CVM\_T4111001051-000\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_T4111001051-000\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_T4111001051-000\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### Datasheets & Catalog Pages

M8 / M12 Connector System Catalog

English

**Product Specifications** 

**Application Specification** 

English