

## Network cable - VS-FSBPXS-OE-94F/1,0 - 1424148

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Assembled Ethernet cable, CAT6<sub>A</sub>, shielded, 4-pair, 26 AWG stranded (7-wire), RAL 5021 (water blue), M12 flush-type socket, rear/screw mounting with M16 thread to free cable end, length: 1 m

### Why buy this product

- ✓ Pre-assembled with cables in various standard lengths for immediate use
- ✓ Customer-specific assemblies and cable lengths can be supplied
- ✓ Sealed on the cable side for optimum tightness of seal
- ✓ Cable designs for all common networks and fieldbuses
- ✓ For high transmission safety: shield connection to the housing with optional EMC nut



### Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 692625
GTIN	4046356692625
Custom tariff number	85444290

### Technical data

#### Mechanical characteristics

Number of positions	8
Number of slots	1
Insertion/withdrawal cycles	≥ 100
Cable exit	straight
Length of cable	1 m
Insulation resistance	≥ 100 MΩ
Degree of protection	IP67
	IP65/IP67
No. of cable outlets	1

# Network cable - VS-FSBPXS-OE-94F/1,0 - 1424148

## Technical data

### Ambient conditions

Ambient temperature (operation)	-25 °C ... 90 °C (Plug / socket)
	-40 °C ... 90 °C (without mechanical actuation)
Degree of protection	IP65
	IP67

### Material data

Flammability rating according to UL 94	V0
Contact carrier material	PPA
Contact material	CuZn
Contact surface material	Au
Cable gland material	Zinc die-cast, nickel-plated
Sealing material	FKM

### Electrical characteristics

Rated surge voltage	0.8 kV
Insulation resistance	≥ 100 MΩ
Transmission characteristics (category)	CAT6 <sub>A</sub>

### Standards and Regulations


Flammability rating according to UL 94	V0
--	----

### Environmental Product Compliance


China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

## Drawings

Dimensional drawing




Schematic diagram



M12 socket pin assignment, 8-pos, view of socket side


# Network cable - VS-FSBPXS-OE-94F/1,0 - 1424148

Cable cross section



Ethernet 10 Gbit [94F]

Circuit diagram



Contact assignment of the M12 plug

## Approvals

### Approvals

#### Approvals

EAC / UL Recognized / cUL Recognized / cULus Recognized

#### Ex Approvals

### Approval details

EAC		B.00767
-----	--	---------

UL Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	FILE E 335024
Nominal current IN	0.5 A		
Nominal voltage UN	60 V		

cUL Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	FILE E 335024
Nominal current IN	0.5 A		
Nominal voltage UN	60 V		

## Network cable - VS-FSBPXS-OE-94F/1,0 - 1424148

### Approvals

cULus Recognized



<http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm>

Phoenix Contact 2017 © - all rights reserved  
<http://www.phoenixcontact.com>