

Pressure Sensor - EPT2100



Eurosensor

- Long life and high performance
- Light weight stainless steel design
- Low cost pressure measuring

The newly designed **EPT2100** is an ideal pressure transducer for various cost sensitive applications.

The silicon measuring cells used within this design coupled with the high level output circuitry, assures excellent accuracy and long term stability within a light weight design.

The silicon sensing element is compatible with many medias, including oil, compressed air and dry non aggressive gases and is suitable for applications with measuring ranges from **250 mbar to 40 bar**.



Specification

Performance		Shock	1000 G, 11 msec., 1/2 Sine
Accuracy @ RT	% of the range < 1.00 (< 0.5 optional) BFUL ≤ 0.25	Vibration	16 G peak, 20 to 2000 Hz
	(incl. nonlinearity, hysteresis, repeatability, zero-offset and final offset acc. to IEC 61298-2)	Sealing	IP 66
Non-linearity	% of the range ≤ 0.15	Electronics	
Repeatability	% of the range ≤ 0.10	Excitation	5 VDC for 0.5 – 4.5 V output, 10 - 32 VDC for 0 - 5 V, 1 - 5 V, 4...20 mA output 12 - 32 VDC for 0 – 10V output
Stability/year	% of the range ≤ 0.10	Current consumption	< 7.5 mA
Overrange pressure	up to 2x rated pressure / max 69bar	Short circuit protection	Yes
Burst pressure	up to 5x rated pressure / max 103bar	Reverse voltage protection	Yes
Pressure cycles	> 10 million	Mechanics	
Environment		Housing	304 stainless steel
Temperature [°C]:		Wetted parts	Silicon, Aluminium, Silicone adhesive, Stainless Steel 304, NBR O-Ring seal
Measuring medium	-40...125	Pressure port	see select table
Ambience	-40...105 (85 for 4...20mA output)	Electrical connection	see select table
Storage	-40...105	Weight	ca. 25 g
Compensated range	-20...85		
Temperature coefficient within the compensated range:			
Mean TC offset	% of the range ≤ 0,15 / 10K		
Mean TC range	% of the range ≤ 0,15 / 10K		

Ordering Information

(Please use the characters in the chart below to construct your product code)

Sample Code: **EPT2100 - H - 01000 - B - 5 - A**

Series	Port Configuration	Pressure Range	Pressure Unit	Output Signal *	Electrical Interface
EPT 2100	B - 1/4 NPT G - 1/4"SAE Female 7/16" UNF Female incl. Schrader valve opener H - 3/8 x 24 UNF Male (Dash Size 3) J - M10x1,25 Female M10 - M10x1 Male	Please use code from table below	B - relative / gauge A - absolute (possible from 4 bar)	1 = 0..10 V 2 = 4..20 mA 3 = 1..5 V 4 = 0..5 V 5 = 0.5..4.5 V ratiometric	A - 600 mm cable C - Connector - Packard Metripac

Pressure Range

Bar	0.25	0.6	1.0	1.6	2.5	4	6	10	16	25	35	40
Order Code	00025	00060	00100	00160	00250	00400	00600	01000	01600	02500	03500	04000

Notes:

* Not all configurations are possible, please contact our sales team to verify your configuration

Custom options available on request

The EPT2100 series are backed by a 1 Year Warranty. The purchaser is responsible for compatibility of the media, functional adequacy and correct installation of the transmitter.

The following models are typically available from stock: **EPT2100-H-01000-B-5-A**
EPT2100-H-01600-B-5-A

Dimensions and wiring

Packard Metri-Pack

Cable

Connection colour codes

Type	Output	PIN A	PIN B	PIN C
Packard	0.5 - 4.5V 1 - 5 V 0 - 10 V	- Supply	+ Supply	Output +
	4..20mA	Current output -	+ Supply	N/A
	Output	Red	Black	White
Cable	0.5 - 4.5V 1 - 5 V 0 - 10 V	+ Supply	- Supply	Output +
	4..20mA	+ Supply	Current output -	N/A



Variohm EuroSensor - Williams' Barn - Tiffeld Road - Towcester - Northants - NN12 6HP - UK
sales@variohm.com • www.variohm.com • +44 (0) 1327 351004

Subject to change without notice