

elma clean 70 (EC 70)

**ALKALINE, UNIVERSALLY APPLICABLE CLEANING CONCENTRATE
FOR LABORATORY AND WORKSHOP**

Description

For laboratory instruments and work pieces made of:

- glass,
- ceramics,
- metals, non-ferrous metals, also light metals.
- alkaline-resistant plastics,
- rubber (excellent for breathing masks),

It removes contaminations such as:

- oils, fats and greases,
- dust,
- soot, cokings, etc.

Application and dosage

Use 1 – 5 % at 20 – 80° C in an ultrasonic bath; in an immersion bath without ultrasound: 5 – 10 %. After cleaning, rinse items thoroughly and dry.

Hotline for application consulting

Working days: Tel. ++49 (0) 7731 882-287. Email: chemlab@elma-ultrasonic.com

Safety recommendations

The concentrate is classified as Irritant (Xi, R41-38) according to the German regulations on dangerous substances / EC directives. Observe the hints indicated in the Safety Data Sheet. Always handle chemicals with care.

Physical-chemical characterisation

Density: 1132 g/l, pH (concentrate): ~13.

Ingredients according to Annex VII, A, EC-Regulation 648/2004 (detergents): 5-15% anionic tensides, <5% amphoteric tensides, 5-15% phosphates, <5% NTA.

Disposal

The surfactants in our product meet the criteria for biodegradation as laid down in Annex III of the Regulation (EC) No 648/2004 on detergents. The cleaning bath can be fed into the public sewage system after neutralisation; observe the local pH limit values and check the contamination contained in the used solution (observe local sewage regulations). Do not discharge the concentrate into the public sewage system or into the private waste before neutralisation.

For neutralisation we recommend: use acetic or citric acid in an ultrasonic bath – do not use hydrochloric acid or sulphuric acid there !

European waste code: 20 01 29*, „detergents containing dangerous substances“.

Volumes, storage and transport

Available volumes: 1l, 10l, and 25l.

Store in closed original container at a temperature between -5 and +30 °C, protected from heat and direct solar radiation. Do not store with acids.

Shelf life: 5 years from date of production (see stamp on label).

Classification for all means of transport: no hazardous material.

Elma Hans Schmidbauer GmbH&Co KG

Kolpingstr. 1-7, D-78224 Singen

e-mail: info@elma-ultrasonic.com

18.02.11/ P:\Produkte\PROInfo\Produkte\englisch\word_GB\P_EC 70_GB.doc

Tel.: ++49 (0) 7731 882-0

Fax: ++49 (0) 7731 882-266

www.elma-ultrasonic.com

