Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

| Supplier' | 's name or | trade mark: | Bailey |
|-----------|------------|-------------|--------|
|-----------|------------|-------------|--------|

Supplier's address: Yvo Hendriks, Everdenberg 21, 4902TT, Oosterhout, The Netherlands

Model identifier: 142619

| _ | • | | | |
|------|-----|-------|----------------|---|
| Tyna | Λt | lioht | source | • |
| IVDE | VI. | HEILL | 3 Uulle | • |

| Type of light source. | | | |
|-------------------------------|----------------|---------------------------------|-------|
| Lighting technology used: | HL | Non-directional or directional: | NDLS |
| Light source cap-type | GY6.35 | | |
| (or other electric interface) | | | |
| Mains or non-mains: | MLS | Connected light source (CLS): | No |
| Colour-tuneable light source: | No | Envelope: | - |
| High luminance light source: | No | | |
| Anti-glare shield: | No | Dimmable: | Yes |
| | Product pa | rameters | |
| Parameter | Value | Parameter | Value |
| | General produc | t parameters: | |

| | | i rodact parar | | I |
|---|--|-------------------------|--|--------------|
| Parameter | | Value | Parameter | Value |
| | | General product p | arameters: | |
| <u> </u> | nption in on- 00 h), rounded st integer | 38 | Energy efficiency class | G |
| dicating if it refe a sphere (360º) | s flux (фuse), in- ers to the flux in , in a wide cone errow cone (90º) | 770 in Sphere (360°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 900 |
| On-mode pow pressed in W | ver (P _{on}), ex- | 35,0 | Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal | 0,00 |
| (P _{net}) for CLS, 6 | andby power expressed in W the second dec- | - | Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set | 100 |
| Outer dimen- | Height | 42 | Spectral power dis- | See image |
| sions without | Width | 10 | tribution in the | in last page |
| separate con- trol gear, light- ing control | Depth | 10 | range 250 nm to 800 nm, at full-load | |

| parts and non- lighting con- trol parts, if any (millime- tre) | | | |
|--|---|------------------------------------|----------------|
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - |
| | | Chromaticity coordinates (x and y) | 0,440 0,403 |

(a)'-': not applicable; (b)'-': not applicable;