





**Complete device, top mounting****Part no.****M22-D-R-X0/KC11/I****Article no.****216521**

Actuator flush

**Delivery programme**

Range			RMQ-Titan (drilling dimensions 22.5 mm)
Basic function			Pushbutton actuators
Single unit/Complete unit			Complete unit
Description			Flush
Number of locations		Qty.	1
Auxiliary contacts:  = safety function, by positive opening to IEC/EN 60947-5-1			
N/O = Normally open			1 N/O
N/C = Normally closed			1 N/C 
Contact sequence			
Colour of enclosure top			
RAL Value			RAL 7035
Front ring			Bezel: Silver
Connection to SmartWire-DT			no

**Approbationen**

Product Standards  
 UL CCN  
 CSA File No.  
 CSA Class No.  
 NA Certification  
 Degree of Protection

IEC/EN 60947-5; UL 508; CSA-C22.2 No. 14-05; CSA-C22.2 No. 94-91; CE marking  
 NKCR  
 012528  
 3211-03  
 UL Listed, CSA certified  
 UL/CSA Type 3R, 4X, 12, 13

**General**

Standards			IEC/EN 60947 VDE 0660
Lifespan, mechanical	Operations	$\times 10^6$	> 1
Operating frequency	Operations/h		$\leq 1800$
Actuating force		n	5
Protection type			IP67, IP69K
Climatic proofing			Damp heat, constant to IEC 60068-2-78 Damp heat, cyclic to IEC 60068-2-30
Ambient temperature		°C	
Open		°C	- 25 - + 70
Mounting position			As required

Mechanical shock resistance		g	30 Shock duration 11 ms Sinusoidal according to IEC 60068-2-27
Cable entry knockouts			
Base		Quantity x M...	2 x 16
Sides		Quantity x M...	1 x 20 2 x 25/20

## Technische Daten nach ETIM 4.0

Number of contacts as N/Cs			1
Color bezel			Chrome
Number of locations			1
Hole diameter		mm	22
Momentary			YES
Color button			red
Supply voltage lamp		V	0
Number of contacts as changeover contact			0
Height meter opening		mm	0
Suitable for illumination			No
Material front ring			Insulated material
Width of opening		mm	22
Lens design			Round
Type of electric connection			Screw connection
Number of contacts as N/O			1
Protection type (IP)			IP66
Switching function latching			No
With bezel			YES
Design of button			flush

## CAD-Daten

Product standards CAD data:

<http://eaton-moeller.partcommunity.com>

## Additional product information (links)

AWA1160-1745 (IL04716002Z) The RMQ-Titan system

[ftp://ftp.moeller.net/DOCUMENTATION/AWA\\_INSTRUCTIONS/17450510.pdf](ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/17450510.pdf)