


**Dekafix  
DEK 6 FWZ L1-ERDE I.KRE**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



The dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a large range of ready-printed markers. Strips for fast installation in one work step. The printing is easy to read, rich in contrast, and is available in five widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Connector markers, suitable for all Weidmüller cable connectors
- Available as blank cards, MultiCard or as cards with standard printing

**General ordering data**

Delivery status	<b>This article will no longer be available in the future.</b>
Available until	2014-11-30
Type	DEK 6 FWZ L1-ERDE I.KRE
Order No.	<a href="#">0631961203</a>
Version	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00 Weidmueller, White
GTIN (EAN)	4008190037208
Qty.	500 pc(s).
Alternative product	<a href="#">1038650000</a>

## Data sheet

### Dekafix DEK 6 FWZ L1-ERDE I.KRE

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

Length	5 mm	Width	6 mm
Net weight	0.064 g		

### General data

Application/manufacture	Weidmueller	Colour	White
Colour of printing	Black	Length	5 mm
Material	Polyamide 66	Material colour according to resistance code	9
Operating temperature range, max.	100 °C	Operating temperature range, min.	-40 °C
Orientation of print	horizontal	Printed characters	Symbols
Printing method	MC Laser	UL 94 flammability rating	V-2
Width	6 mm		

### Connector markers

Pitch in mm (P)	6 mm
-----------------	------

### Classifications

ETIM 3.0	EC000761	ETIM 4.0	EC000761
ETIM 5.0	EC000761	ETIM 6.0	EC000761
UNSPSC	30-21-18-07	eClass 5.1	27-14-11-37
eClass 6.2	27-14-11-37	eClass 7.1	27-14-11-37

### Approvals

ROHS	Conform
------	---------