

Material: 60008010 **ELASTOSIL® N10 TRANSPARENT**

Date of print: 28.02.2017 Date of last alteration: 22.07.2016 Version: 3.5 (GB)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Commercial product name: **ELASTOSIL® N10 TRANSPARENT**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of substance / preparation:

Industrial.

Adhesive / sealant .

1.3 Details of the supplier of the safety data sheet

> Manufacturer/distributor: Wacker Chemie AG Street/POB-No.: Hanns-Seidel-Platz 4 D 81737 München State/postal code/city: Telephone: +49 89 6279-0 Telefax: +49 89 6279-1770

Information about the Safety Data Sheet: Telephone +49 8677 83-4888 Telefax +49 8677 886-9722

eMail

WLCP-MSDS@wacker.com

1.4 **Emergency telephone number**

> **Emergency Information (German):** Plant fire brigade +49 8677 83-2222 **Emergency Information (internat.): National Response Center** +49 621 60-43333

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008:

Class	Category	Route of exposure	H-Code
Carcinogenicity	Category 2		H351
Reproductive toxicity	Category 1B (developmental toxicity)		H360D
Reproductive toxicity	Category 1B (impair fertility)		H360F

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008:

Pictogram(s):



Signal Word: Danger

H-Code	Hazard Statements
H351	Suspected of causing cancer.
H360FD	May damage fertility. May damage the unborn child.
P-Code	Precautionary Statements
P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P280	Wear protective gloves/protective clothing/eye protection.
P405	Store locked up.
P501	Dispose of contents/container to waste disposal.

Hazard ingredients (labelling): 2-Butanone oxime Silicic acid, tetraethyl ester, RP with bis(acetyloxy)dibutylstannane



Material: 60008010 ELASTOSIL® N10 TRANSPARENT

Version: 3.5 (GB) Date of print: 28.02.2017 Date of last alteration: 22.07.2016

Special labelling instructions:

Contains methylbutane-2-one-trioximo-silane, 2-butanone oxime, butan-2-ontetraoximosilane, 3-(2-aminoethylamino)propyl trimethoxysilane. May produce an allergic reaction. Restricted to professional users.

2.3 Other hazards

During the use of the product, 2-butanone oxime (methyl ethyl ketoxime, MEKO, CAS No. 96-29-7) is generated, which evaporates. 2-butanone oxime is classified as a health risk.

SECTION 3: Composition/information on ingredients

3.1 Substances

not applicable

3.2 Mixtures

3.2.1 Chemical characteristics

Polydimethylsiloxane and fillers and auxiliaries and oximosilane cross-linker

3.2.2 Hazardous ingredients

Туре	CAS No.	EC-No.	Material	Content %	Classification	Comment
		REACH no.			according to Regulation (EC) No. 1272/2008*	
INHA	22984-54-9	245-366-4	Methyl-O,O',O"-butan-2-on-	<7	Skin Sens. 1B; H317	[1]
		01-2119987100-43	trioximo-silane		Eye Irrit. 2; H319 STOT RE 2; H373	
INHA	96-29-7	202-496-6	2-Butanone oxime	<2	Acute Tox. 4 dermal;	[1]
		01-2119539477-28			H312 Carc. 2; H351 Skin Sens. 1; H317 Eye Dam. 1; H318	
INHA	93925-42-9	300-344-4	Silicic acid, tetraethyl ester, RP	<1	STOT SE 1; H370	[1]
		01-2119560586-30	with bis(acetyloxy)dibutylstannane		Muta. 2; H341 Repr. 1B; H360F Repr. 1B; H360D Acute Tox. 4 by inhalation; H332 Aquatic Chronic 3; H412 Acute Tox. 4 oral; H302 Eye Dam. 1; H318 STOT RE 1; H372 Flam. Liq. 3; H226	
INHA	1760-24-3	217-164-6 01-2119970215-39	3-(2-Aminoethylamino)propyl trimethoxysilane	<1	Eye Dam. 1; H318 Skin Sens. 1B; H317	[1]
INHA	34206-40-1	251-882-0	Butanone tetraoximo silane	<0,5	Skin Sens. 1B; H317 Eye Irrit. 2; H319 STOT RE 2; H373	[1]

Type: INHA: ingredient, VERU: impurity

[1] = Hazardous or environmentally harmful substance; [2] = substance with a Community workplace exposure limit; [3] = PBT substance; [4] = vPvB substance

^{*}Classification codes are explained in section 16.



Material: 60008010 ELASTOSIL® N10 TRANSPARENT

Version: 3.5 (GB) Date of print: 28.02.2017 Date of last alteration: 22.07.2016

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Take persons to a safe place. Observe self-protection for first aid.

After contact with the eyes:

Rinse immediately with plenty of water for 10-15 minutes. Keep eyelids well open to rinse the whole eye surface and eyelids with water. Seek medical advice in case of continuous irritation.

After contact with the skin:

Remove contaminated or soaked clothing. Immediately rinse with plenty of soap and water. In serious cases, use emergency shower immediately. In the event of a visible skin change or other complaints, seek medical advice (show label or SDS where possible).

After inhalation:

Keep the patient calm. If unconscious place in stable sideways position. Protect against loss of body heat. Seek medical advice and clearly identify substance.

After swallowing:

If conscious, give several small portions of water to drink. Do not induce vomiting. Seek medical advice and clearly identify substance.

4.2 Most important symptoms and effects, both acute and delayed

Any relevant information can be found in other parts of this section.

4.3 Indication of any immediate medical attention and special treatment needed

Product may cause cancer. In the event of prolonged contact with the substance, long-term monitoring of relevant parameters is advisable.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

water spray, extinguishing powder, alcohol-resistant foam, carbon dioxide, sand.

Extinguishing media which must not be used for safety reasons:

water jet .

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products: nitrous gases .

5.3 Advice for firefighters

Special protective equipment for fire fighting:

Use respiratory protection independent of recirculated air.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment (see section 8). Avoid contact with eyes and skin. Avoid inhaling mists and vapours.

6.2 Environmental precautions

Prevent material from entering sewers or surface waters.

6.3 Methods and material for containment and cleaning up

Do not flush away with water. Take up mechanically and dispose of according to local/state/federal regulations. Absorb with a liquid binding material such as diatomaceous earth and dispose of according to local/state/federal regulations. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner.

6.4 Reference to other sections

Relevant information in other sections has to be considered. This applies in particular for information given on personal protective equipment (section 8) and on disposal (section 13).



Material: 60008010 ELASTOSIL® N10 TRANSPARENT

Version: 3.5 (GB) Date of print: 28.02.2017 Date of last alteration: 22.07.2016

SECTION 7: Handling and storage

7.1 Precautions for safe handling

General information:

Avoid exposure - obtain special instructions before use.

Precautions for safe handling:

Ensure adequate ventilation. Keep away from incompatible substances in accordance with section 10.

Precautions against fire and explosion:

Observe the general rules for fire prevention.

7.2 Conditions for safe storage, including any incompatibilities

Conditions for storage rooms and vessels:

none known

Advice for storage of incompatible materials:

not applicable

Further information for storage:

Protect against moisture. Keep container tightly closed and store in a cool, well ventilated place.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Maximum airborne concentrations at the workplace:

not applicable

Further information:

Maximum concentration at workplace recommended by producer: methyl ethyl ketoxime (MEKO, CAS no. 96-29-7, product of hydrolysis) = 3 ppm.

8.2 Exposure controls

8.2.1 Exposure in the work place limited and controlled

General protection and hygiene measures:

Avoid contact with eyes and skin. Do not inhale gases/vapours/aerosols. Do not eat, drink or smoke when handling. Wash hands at the end of work and before eating. Avoid exposure of the substance to pregnant women.

Personal protection equipment:

Respiratory protection

In case of long or strong exposure: gas mask filter ABEK .

Eye protection

protective goggles.

Hand protection

Protective gloves made of butyl rubber, Protective gloves made of nitrile rubber. Gloves suitable for up to 60 minutes' use. The selection of appropriate gloves not only depends on the material, but also on other quality characteristics, and may vary depending on the manufacturer. Please observe information from your glove supplier in terms of permeability and breakthrough time.

Skin protection

protective clothing.

8.2.2 Exposure to the environment limited and controlled

Prevent material from entering surface waters and soil.



Material: 60008010 ELASTOSIL® N10 TRANSPARENT

Version: 3.5 (GB) Date of print: 28.02.2017 Date of last alteration: 22.07.2016

SECTION 9: Physical and chemical properties

9.1	Information or	basic p	hvsical and	l chemical	properties
-----	----------------	---------	-------------	------------	------------

Property:	Value:	Method:
Appearance		
Physical state / form	•	
Colour	colourless	
Odour	15.1	
Odour	slight	
pH-Value		
pH-Value	not applicable	
Melting point/freezing point		
Melting point / melting range	not applicable	
Initial boiling point and boiling range		
Boiling point / boiling range	not applicable	
Flash point		
Flash point	not applicable	
Upper/lower flammability or explosive limits		
Lower explosion limit (LEL)	not applicable	
Vapour pressure		
Vapour pressure	not determined	
Solubility(ies)		
Water solubility / miscibility	virtually insoluble	
Vapour density		
Relative gas/vapour density	No data known.	
Relative Density		
Relative Density:		(DIN 53217)
	(Water / 4 °C = 1,00)	
Density:	approx. 1,02 g/cm³ (23 °C)	(DIN 53217)
Partition coefficient: n-octanol/water		
Partition coefficient: n-octanol/water	No data known.	
Auto-ignition temperature		
Ignition temperature:	approx. 404 °C	(EN 14522)
Decomposition temperature		
Thermal decomposition:	No decomposition when used according to regulations.	
Viscosity		
Viscosity (dynamic):	8000 mPa.s at 23 °C	(Brookfield)
Other information		

9.2 Other information

Re 9.2 solubility in water: Hydrolytic decomposition occurs.

SECTION 10: Stability and reactivity

10.1 - 10.3 Reactivity; Chemical stability; Possibility of hazardous reactions

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

Relevant information can possibly be found in other parts of this section.

10.4 Conditions to avoid

moisture.

10.5 Incompatible materials

none known

10.6 Hazardous decomposition products

By hydrolysis: 2-butanone oxime . Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C (302 °F) through oxidation.



Material: 60008010 ELASTOSIL® N10 TRANSPARENT

Version: 3.5 (GB) Date of print: 28.02.2017 Date of last alteration: 22.07.2016

SECTION 11: Toxicological information

11.1 Information on toxicological effects

11.1.1 Acute toxicity

Product details:

Route of exposu	ure Result/Effect	Species/Test system	Source
oral	LD ₅₀ : > 2009 mg/kg	rat	Conclusion by analogy
dermal	LD ₅₀ : > 2009 mg/kg	rat	Conclusion by analogy

11.1.2 Skin corrosion/irritation

Product details:

Result/Effect	Species/Test system	Source
not irritating	rabbit	Conclusion by
		analogy

11.1.3 Serious eye damage / eye irritation

Product details:

Result/Effect	Species/Test system	Source
not irritating	rabbit	Conclusion by
		analogy

11.1.4 Respiratory or skin sensitization

Product details:

Route of exposure	Result/Effect	Species/Test system	Source
dermal	not sensitizing	guinea-pig; Bühler	test report
			OECD 406

11.1.5 Germ cell mutagenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.6 Carcinogenicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.7 Reproductive toxicity

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.8 Specific target organ toxicity (single exposure)

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.9 Specific target organ toxicity (repeated exposure)

Assessment:

For this endpoint no toxicological test data is available for the whole product.

11.1.10 Aspiration hazard

Assessment:

For this endpoint no toxicological test data is available for the whole product.



Material: 60008010 ELASTOSIL® N10 TRANSPARENT

Version: 3.5 (GB) Date of print: 28.02.2017 Date of last alteration: 22.07.2016

11.1.11 Further toxicological information

Hydrolysis product / Impurity: 2-Butanone oxime (MEKO, CAS 96-29-7) is a dermal sensitizer and strongly irritating to the eyes. 2-Butanone oxime is rapidly absorbed from the gastrointestinal tract, upon contact with skin and after inhalation. After oral exposure of rats to MEKO in an acute neurotoxicity study, transient motor incoordination effects were observed. Prolonged exposure of animals led to damages of the olfactory epithelium and to an increase in the incidence of corneal dystrophy and opacities. Systemic effects in repeated dose studies (oral, inhalative) were hemolytic anemia and compensatory and extramedullary hematopoiesis as well as hemosiderosis in spleen and liver and increased levels of methemoglobin. In several of these studies, the effects were reversible. Gross histopathologic alterations were seen in spleen, lung and kidney. After chronic inhalative exposure to high vapor concentrations an increased incidence of hepatocellular carcinomas and adenomas was observed predominantly in male rats and mice. The significance of these results to human users has not been assessed.

SECTION 12: Ecological information

12.1 Toxicity

Assessment:

Evaluation on basis of physical-chemical properties: No expected damaging effects to aquatic organisms. According to current knowledge adverse effects on water purification plants are not expected.

12.2 Persistence and degradability

Assessment:

Biologically not degradable.

12.3 Bioaccumulative potential

Assessment:

Bioaccumulation is not expected to occur.

12.4 Mobility in soil

Assessment:

No data known.

12.5 Results of PBT and vPvB assessment

No data available.

12.6 Other adverse effects

none known

12.7 Additional information

In cross-linked state not soluble in water. Easily separable from water by filtration.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

13.1.1 Material

Recommendation:

Dispose of according to regulations by incineration in a special waste incinerator. Observe local/state/federal regulations.

13.1.2 Uncleaned packaging

Recommendation:

Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations.

13.1.3 Waste Disposal Legislation Ref.No.(EC)

It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Page: 7/9



Material: 60008010 ELASTOSIL® N10 TRANSPARENT

Version: 3.5 (GB) Date of print: 28.02.2017 Date of last alteration: 22.07.2016

SECTION 14: Transport information

14.1 - 14.4 UN number; UN proper shipping name; Transport hazard class(es); Packing group

Road ADR:

Valuation Not regulated for transport

Railway RID:

Valuation Not regulated for transport

Transport by sea IMDG-Code:

Valuation Not regulated for transport

Air transport ICAO-TI/IATA-DGR:

Valuation Not regulated for transport

14.5 Environmental hazards

Hazardous to the environment: no

14.6 Special precautions for user

Relevant information in other sections has to be considered.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

Bulk transport in tankers is not intended.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National and local regulations must be observed.

For information on labelling please refer to section 2 of this document.

Relevant regulations:

SI 2002/1689: CHIP Regulations 2002 SI 2002/2677: COSHH Regulations 2002

SI 1999/3242: Management of Health & Safety at Work Regulations 1999

Health & Safety at Work Act 1974

SI 1993/1643: Environmental Protection Act 1993 & Subsidiary Regulations.

Other national and local measures relating to the workplace, pollution control, environmental protection and waste control.

Other specifications, restrictions and prohibitions:

REACh Annex XVII: This product contains dibutyltin compounds in an amount of over 0.1 wt.%. Annex XVII, entry 20, of regulation 1907/2006, in its current version, must be taken into account.

15.2 Chemical safety assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

15.3 Details of international registration status

Relevant information about individual substance inventories, where available, is given below.

South Korea (Republic of Korea): ECL (Existing Chemicals List):

This product is listed in, or complies with, the substance inventory.

This product is listed in, or complies with, the substance inventory.



Material: 60008010 ELASTOSIL® N10 TRANSPARENT

Version: 3.5 (GB) Date of print: 28.02.2017 Date of last alteration: 22.07.2016

European Economic Area (EEA)...... REACH (Regulation (EC) No 1907/2006):

General note: the registration obligations for substances imported into the EEA or manufactured within the EEA by the supplier mentioned in section 1 are fulfilled by the said supplier. The registration obligations for substances imported into the EEA by customers or other downstream users must be fulfilled by the latter.

SECTION 16: Other information

16.1 Material

The details in this document are based on the state of our knowledge at the time of revision. They do not constitute an assurance of the described product properties in terms of statutory warranty requirements.

The providing of this document to a recipient does not relieve the recipient of his or her responsibility toward compliance with all laws and stipulations applicable to the product. This applies in particular to the further sale or distribution of the product or substances or items containing the product, in other jurisdictions and with regard to the protection of third-party intellectual property rights. If the described product is processed or mixed with other substances or materials, the details stated in this document cannot be conferred to the resultant new product unless this has been expressly mentioned. If the product is repackaged, the recipient is obligated to additionally provide the required safety-related information.

All deliveries are subject to the WACKER SILICONES Health Care Policy, which is available at www.wacker.com.

16.2 Further information:

Commas appearing in numerical data denote a decimal point. Vertical lines in the left-hand margin indicate changes compared with the previous version. This version supersedes all previous versions.

Explanation of the GHS classification code:

Skin Sens. 1B; H317..: Skin sensitization Category 1B; May cause an allergic skin reaction.

Eye Irrit. 2; H319: Serious eye damage / eye irritation Category 2A; Causes serious eye irritation.

STOT RE 2; H373.....: Specific target organ toxicity (repeated exposure) Category 2; May cause damage to organs through

prolonged or repeated exposure.

Acute Tox. 4; H312: Acute toxicity Category 4; Harmful in contact with skin.

Carc. 2; H351..... Carcinogenicity Category 2; Suspected of causing cancer.

Skin Sens. 1; H317: Skin sensitization Category 1; May cause an allergic skin reaction.

Eye Dam. 1; H318.....: Serious eye damage / eye irritation Category 1; Causes serious eye damage.

STOT SE 1; H370: Specific target organ toxicity (single exposure) Category 1; Causes damage to organs.

Repr. 1B; H360D.......: Reproductive toxicity Category 1B (developmental toxicity); May damage the unborn child.

Acute Tox. 4; H332: Acute toxicity Category 4; Harmful if inhaled.

Aquatic Chronic 3; H412 Hazardous to the aquatic environment chronic, category 3; Harmful to aquatic life with long lasting

..... effects.

Acute Tox. 4; H302: Acute toxicity Category 4; Harmful if swallowed.

Eye Dam. 1; H318.....: Serious eye damage / eye irritation Category 1; Causes serious eye damage.

STOT RE 1; H372.....: Specific target organ toxicity (repeated exposure) Category 1; Causes damage to organs through

prolonged or repeated exposure.

Flam. Liq. 3; H226.....: Flammable liquids Category 3; Flammable liquid and vapour.

Eye Dam. 1; H318......: Serious eye damage / eye irritation Category 1; Causes serious eye damage.

Skin Sens. 1B; H317... Skin sensitization Category 1B; May cause an allergic skin reaction. Skin Sens. 1B; H317... Skin sensitization Category 1B; May cause an allergic skin reaction.

Eye Irrit. 2; H319 Serious eye damage / eye irritation Category 2A; Causes serious eye irritation.

STOT RE 2; H373: Specific target organ toxicity (repeated exposure) Category 2; May cause damage to organs through

prolonged or repeated exposure.

Classification	Rationale:
Carcinogenicity, Category 2	Calculation method
Reproductive toxicity, Category 1B (developmental toxicity)	Calculation method
Reproductive toxicity, Category 1B (impair fertility)	Calculation method

- End of Safety Data Sheet -