"FPF" SERIES FAN-FILTER UNITS

Filter Code: FPF20KR230BE-120

Description: Fan Filter 230 Va.c.

MECHANICAL SPECIFICATIONS

Dimensions: 325x325x161 mm

Weight: 3,62 Kg

Type of material: ABS/PC UL94V-0

Colour: RAL 7032

Protection degree: IP54 (EN60529) Fastener: by elastic hooks Plate thickness: from 1,5 to 2,2 mm Storage temp.: -30°C to +75°C

Electric connection: by terminals block 2,5mm² Earth connection: by terminal block 2,5mm²

OPERATING FEATURES

Rated voltage: 230 [V] Rated frequency: 50/60 [Hz] Rated power: 67/90 [W] Rated current: 300/360 [mA] Fan speed: 2480/2650 [rpm]

Noise: 61.0/63.0 [dB(A)] Operating temp.: - 10°C to +50°C

Relative humidity: 90% max Life (L10) at 40°C: 53.000 hours

PERFORMANCES and APPROVALS

Max air flow: **520/580** [m³/h] Max static pressure: 160/186 [Pa] Type of media: P15/350S


Flammability: F1 (DIN 53438) Filtering class: EU3 (DIN 24185) Degree of separation: 85% (DIN 24185) Degree of efficacy: < 20% (DIN 24185)

Dust storage capacity: 600 g/m²


Approvals:

Note: the media is washable


FAN FILTER DIMENSIONS [mm]



DIMENSIONS CUT-OUT [mm]



PERFORMANCE CURVES



Please refer to out terms of sales including our warranty and limited liabilities clauses.

